


MCL914, MCL914A, MCL914B

SILICON EPITAXIAL PLANAR DIODES

LS-31

Features

- Saving space
- Hermetic sealed parts
- Fits onto SOD 323 / SOT 23 footprints
- Electrical data identical with the device 1N4148
- Micro Melf package




Applications

- Extreme fast switches


Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$)

Characteristic	Symbol	Value	Unit
Non-Repetitive Peak Reverse Voltage	V_{RM}	100	V
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V_{RRM} V_{RWM} V_R	75	V
RMS Reverse Voltage	$V_{R(RMS)}$	53	V
Forward Continuous Current (Note 1)	MCL914 MCL914A / B I_{FM}	150 300	mA
Average Rectified Output Current (Note 1)	MCL914 MCL914A / B I_o	75 200	mA
Non-Repetitive Peak Forward Surge Current	I_{FSM}	1 1 4	A
Power Dissipation (Note 1) Derate Above 25°C	P_d	500 1.68	mW mW/ $^\circ\text{C}$
Thermal Resistance, Junction to Ambient Air (Note 1)	$R_{\theta JA}$	300	K/W
Operating and Storage Temperature Range	T_j, T_s	-65 to +175	$^\circ\text{C}$



SEMTECH ELECTRONICS LTD.

(Subsidiary of Sino-Tech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)



ISO/TS 16949 : 2002 Certificate No. 05103
ISO 14001:2004 Certificate No. 7116
ISO 9001:2000 Certificate No. 0506098

Dated : 20/08/2002



MCL914, MCL914A, MCL914B

Characteristics at $T_j = 25^\circ\text{C}$

Characteristic	Symbol	Min.	Max.	Unit
Forward Voltage at $I_F = 5\text{mA}$ at $I_F = 100\text{mA}$ at $I_F = 10\text{mA}$ at $I_F = 20\text{mA}$	V_F	0.62 - - -	0.72 1 1 1	V
Peak Reverse Current at $V_R = 75\text{V}$ at $V_R = 20\text{V}, T_A = 150^\circ\text{C}$ at $V_R = 20\text{V}$	I_R	- - -	5 50 25	μA μA nA
Diode Capacitance at $V_R = 0, f = 1\text{MHz}$	C_o	-	4	pF
Reverse Recovery Time at $I_F = 10\text{mA}$ to $I_R = 1\text{mA}, V_R = 6\text{V}, R_L = 100\Omega$	T_{RR}	-	4	nS

Note 1: Valid provided that lead are kept at ambient temperature at a distance of 8 mm.

Dimensions in mm



SEMTECH ELECTRONICS LTD.

(Subsidiary of Sino-Tech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)



ISO/TS 16949 : 2002
Certificate No. 05103



ISO 14001:2004
Certificate No. 71116



ISO 9001:2000
Certificate No. 0506098

Dated : 20/08/2002


MCL914, MCL914A, MCL914B

Technical Information

Taping of SMD-Components


We supplies the SMD components either in bulk or in 8-mm or 12-mm blister tapes depending on type of case.

Both the tape dimensions for the cases MicroMELF and dimensions of the reels are shown in the following figures.



Accumulated pitch tolerance is ± 0.2 mm over 10 pitches

8-mm carrier tape for MicroMELF package dimensions in mm



SEMTECH ELECTRONICS LTD.

(Subsidiary of Sino-Tech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)



ISO/TS 16949 : 2002
Certificate No. 05103



ISO 14001:2004
Certificate No. 7116




ISO 9001:2000
Certificate No. 0506098

Dated : 20/08/2002

MCL914, MCL914A, MCL914B

Technical Information



The beginning of the tape comprises a 200 mm long lead-in with vacant nests and at the hub end of the tape there are 10 to 20 sealed nests containing no devices. This end of the tape automatically detaches from the hub of the reel at the end of the in reeling procedure (Draft DIN IEC 49(CO)564).


The packaging units for taped devices are

Type of case	Qty / reel	Reel Ø
MicroMELF	2,500	178mm

	8-mm carrier tape	12-mm carrier tape
B	2±0.5	2±0.5
C	13±0.5	13±0.5
D	178±2	330±2
G	8.4±1.5	12.4±2
H	4±0.5	4±0.5
N	60	60
T	<14.9	<20

Dimensions in mm


Pull-out direction



Reel for 8-mm and 12-mm carrier tapes

The carrier tape consists of a plastic tape with "nests" having a size corresponding to the components requirements. The sprocket holes are on one side of the tape. The blister tapes are sealed with a cover tape.

The cathode side of the components MicroMELF cases are adjacent to the sprocket holes. Other orientation can be supplied on demand.



SEMTECH ELECTRONICS LTD.

(Subsidiary of Sino-Tech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)



ISO/TS 16949 : 2002
Certificate No. 05103



ISO 14001:2004
Certificate No. 7116



ISO 9001:2000
Certificate No. 0506098

Dated : 20/08/2002