

ERB05GGR & ERB05JGR

**SINTERED GLASS JUNCTION
FAST SWITCHING PLASTIC RECTIFIER**
VOLTAGE:400 & 600V CURRENT: 0.5A




FEATURE

High temperature metallurgically bonded construction
Sintered glass cavity free junction
Capability of meeting environmental standard of MIL-S-19500
High temperature soldering guaranteed
350°C /10sec/0.375"lead length at 5 lbs tension
Operate at Ta =55°C with no thermal run away
Typical Ir<0.1µA

MECHANICAL DATA

Terminal: Plated axial leads solderable per MIL-STD 202E, method 208C
Case: Molded with UL-94 Class V-0 recognized Flame Retardant Epoxy
Polarity: color band denotes cathode
Mounting position: any

DO-41\DO-204AL



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(single-phase, half-wave, 60HZ, resistive or inductive load rating at 25°C, unless otherwise stated)

	SYMBOL	ERB05GGR	ERB05JGR	units
Maximum Recurrent Peak Reverse Voltage	V _{rrm}	400	600	V
Maximum RMS Voltage	V _{rms}	280	420	V
Maximum DC blocking Voltage	V _{dc}	400	600	V
Maximum Average Forward Rectified Current 3/8"lead length at Ta =55°C	I _{f(av)}	0.5		A
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load	I _{fsm}	10.0		A
Maximum Forward Voltage at rated Forward Current and 25°C IF=0.5A	V _f	1.2		V
Maximum full load reverse current full cycle average at 55°C Ambient	I _{r(av)}	100.0		µA
Maximum DC Reverse Current Ta =25°C at rated DC blocking voltage Ta =150°C	I _r	5.0	100.0	µA
Maximum Reverse Recovery Time (Note 1)	T _{rr}	150		nS
Typical Junction Capacitance (Note 2)	C _j	15.0		pF
Typical Thermal Resistance (Note 3)	R(ja)	55.0		°C /W
Storage and Operating Junction Temperature	T _{stg, Tj}	-65 to +175		°C

Note:

1. Reverse Recovery Condition I_f =0.5A, I_r =1.0A, I_{rr} =0.25A
2. Measured at 1.0 MHz and applied reverse voltage of 4.0Vdc
3. Thermal Resistance from Junction to Ambient at 3/8"lead length, P.C. Board Mounted

RATINGS AND CHARACTERISTIC CURVES ERB05GGR & ERB05JGR

FIG. 1 - FORWARD CURRENT DERATING CURVE




FIG. 2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG. 3 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 4 - TYPICAL REVERSE CHARACTERISTICS




FIG. 5 - TYPICAL JUNCTION CAPACITANCE




FIG. 6 - TYPICAL TRANSIENT THERMAL IMPEDANCE

