

RGPB50J

**SINTERED GLASS JUNCTION
FAST SWITCHING PLASTIC RECTIFIER**
VOLTAGE: 600V CURRENT: 5.0A




FEATURE

High temperature metallurgically bonded construction
Sintered glass cavity free junction
Capability of meeting environmental standard of MIL-S-19500
High temperature soldering guaranteed
350°C /10sec/0.375"lead length at 5 lbs tension
Operate at Ta =55°C with no thermal run away
Typical Ir<0.1µA

MECHANICAL DATA

Terminal: Plated axial leads solderable per MIL-STD 202E, method 208C
Case: Molded with UL-94 Class V-0 recognized Flame Retardant Epoxy
Polarity: color band denotes cathode
Mounting position: any



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(single-phase, half-wave, 60HZ, resistive or inductive load rating at 25°C, unless otherwise stated)

	SYMBOL	RGPB50J	units
Maximum Recurrent Peak Reverse Voltage	Vrrm	600	V
Maximum RMS Voltage	Vrms	420	V
Maximum DC blocking Voltage	Vdc	600	V
Maximum Average Forward Rectified Current 3/8"lead length at Ta =55°C	If(av)	5.0	A
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load	Ifsm	125	A
Maximum Forward Voltage at rated Forward Current and 25°C	Vf	1.2	V
Maximum full load reverse current full cycle average at 55°C Ambient	Ir(av)	100	µA
Maximum DC Reverse Current Ta =25°C at rated DC blocking voltage Ta =150°C	Ir	5.0 100	µA
Maximum Reverse Recovery Time (Note 1)	Trr	200	nS
Typical Junction Capacitance (Note 2)	Cj	60	pF
Typical Thermal Resistance (Note 3)	Rth(ja)	20	°C /W
Storage and Operating Junction Temperature	Tstg, Tj	-65 to +175	°C

Note:

- Reverse Recovery Condition If =0.5A, Ir =1.0A, Irr =0.25A
- Measured at 1.0 MHz and applied reverse voltage of 4.0Vdc
- Thermal Resistance from Junction to Ambient at 3/8"lead length, P.C. Board Mounted

RATINGS AND CHARACTERISTIC CURVES RGPB50J

