



SPECIFICATION FOR APPROVAL

REF :

PAGE: 1


PROD. NAME	SHIELDED SMD POWER INDUCTOR	ABC'S DWG NO.	SP1206□□□□L□-□□□
		ABC'S ITEM NO.	

. MECHANICAL DIMENSIONS :



A	: 12.50±0.30	m/m
B	: 12.50±0.30	m/m
C	: 5.70±0.30	m/m
D	: 1.90±0.20	m/m
E	: 2.50 nom.	m/m
E1	: 2.00 ref.	m/m
E2	: 2.00 ref.	m/m
F	: 7.50±0.25	m/m
F1	: 6.40 ref.	m/m
F2	: 5.20 ref.	m/m
H	: 10.50 ref.	m/m
I	: 4.15 ref.	m/m
J	: 3.00 ref.	m/m
K	: 13.00 ref.	m/m
M	: 4.70 ref.	m/m
N	: 4.50 ref.	m/m
P	: 7.50 ref.	m/m
P1	: 3.75 ref.	m/m
P2	: 3.75 ref.	m/m

. SCHEMATIC DIAGRAM :




. MATERIALS LIST :


- a . Core : Ferrite ER core
- b . Core : Ferrite SB core
- c . Wire : Ultra-fine rectangular
Enamelled copper wire (class F)
- d . Terminal : Cu/Sn
- e . Adhesive : Epoxy resin
- f . Adhesive : Epoxy resin
- g . Remark : Products comply with RoHS' requirements

. GENERAL SPECIFICATION :

- a . Temp. rise : 40 max.
- b . Storage temp. : -40 ~ +125
- c . Operating temp. : -40 ~ +105
- d . Resistance to solder heat : 260 . 10 secs.



Peak Temp : 260 max.
Max time above 230 : 50sec max.
Max time above 200 : 70sec max.



AR-001A

SPECIFICATION FOR APPROVAL

REF :

PAGE: 2


PROD. NAME	SHIELDED SMD POWER INDUCTOR	ABC'S DWG NO.	SP1206□□□□L□-□□□
		ABC'S ITEM NO.	

. ELECTRICAL CHARACTERISTICS :


DWG No.	Initial Inductance L0 (uH)	Inductance at flat point L1 (uH)	Flat point ref. (A)	Irms (A)	Isat (A)	DC Resistance max. (mΩ)
SP1206R47YL□-□□□	0.70±25%	0.47±25%	5.0	30.0	30.0	2.3
SP1206R60YL□-□□□	0.90±25%	0.60±25%	5.0	28.0	26.0	2.3
SP1206R80YL□-□□□	1.10±25%	0.80±25%	5.0	26.0	25.0	3.2
SP12061R3YL□-□□□	1.50±25%	1.30±25%	4.0	22.0	19.0	3.6
SP12062R0YL□-□□□	2.20±25%	2.00±25%	4.0	17.0	15.0	6.0
SP12062R8YL□-□□□	3.00±25%	2.80±25%	3.0	15.0	13.0	7.0

- 1). □ : Packaging information... **[A]**: Bulk **[B]**: Taping Reel
- 2). "-□□□": Reference code
- 3). Measured frequency of inductance is 100 KHz / 1V
- 4). Isat base on inductance drop 20% typ. of L1 value
- 5). Irms base on temp. rise 40 max.

@ Inductance VS. DC Superposition Characteristics



AR-001A









SPECIFICATION FOR APPROVAL

REF :

PAGE: 3

PROD.	SHIELDED SMD	ABC'S DWG NO.	SP1206□□□□L□-□□□
NAME	POWER INDUCTOR	ABC'S ITEM NO.	

@ DC Current VS Temperature Rise



AR-001A

SPECIFICATION FOR APPROVAL



REF :

PAGE: 4

PROD. NAME	SHIELDED SMD POWER INDUCTOR	ABC'S DWG NO.	SP1206□□□□□□□□□□
		ABC'S ITEM NO.	

PACKAGING INFORMATION :

(1) Configuration



(2) Dimensions

Unit:m/m

Style	A	B	C	D	G	N	T
13 - 24	330	21±0.8	13±0.5	24	26 ⁺⁰	50 ⁻⁰	30.4

(3) Q'TY & G.W. Per package

Series	Inner : Reel			Outer : Carton		
	Q'TY (pcs)	G.W. (gw)	Style	Q'TY (pcs)	G.W. (Kg)	Size (cm)
SP1206	600	2,150	13 - 24	2,400	11.30	40 x 40 x 24

AR-001A


SPECIFICATION FOR APPROVAL

REF :

PAGE: 5

PROD. NAME	SHIELDED SMD POWER INDUCTOR	ABC'S DWG NO.	SP1206□□□□L□-□□□
		ABC'S ITEM NO.	

. DWGING NUMBER EXPRESSION :



Appendix code 1 : Product Classification

- L : Lead Free Standard products comply with RoHS' requirements
- 1 ~ 9 : Lead Free Special products comply with RoHS' requirements

Appendix code 2 : Package Information

Code	Inner package	Inner package Q'TY	Remark
A	T.B.D.	T.B.D.	
B	T / R (Reel package)	600 pcs	

AR-001A



SPECIFICATION FOR APPROVAL

REF :

PAGE: 6

PROD. NAME	SHIELDED SMD POWER INDUCTOR	ABC'S DWG NO. ABC'S ITEM NO.	SP1206□□□□L□-□□□
---------------	--------------------------------	---------------------------------	------------------

. RELIABILITY TEST :

Test item	Specification	Test condition						
Solderability	More than 90% of the terminal electrode shall be covered With fresh solder.	Preheat : 150±25 for 60 seconds Solder : Sn96.5 / Ag3 / Cu0.5 or equivalent Solder temp. : 235±5 Flux : Rosin Dip time : 4±1 seconds						
Thermal shock test (Temp. cycle)	Inductance shall not change more than ±20%	<table style="width: 100%; border: none;"> <tr> <td style="text-align: center;">Room temp. 15 minutes</td> <td style="text-align: center;">→</td> <td style="text-align: center;">-25±2 30 minutes</td> </tr> <tr> <td style="text-align: center;">Room temp. 15 minutes</td> <td style="text-align: center;">→</td> <td style="text-align: center;">85±2 30 minutes</td> </tr> </table> <p>Total : 50 cycles</p>	Room temp. 15 minutes	→	-25±2 30 minutes	Room temp. 15 minutes	→	85±2 30 minutes
Room temp. 15 minutes		→	-25±2 30 minutes					
Room temp. 15 minutes		→	85±2 30 minutes					
Humidity Resistance test		Temperature : 40±2 Humidity : 90 ~ 95% Applied current : Per spec. Time : 500 hours						
High temp. Resistance test	Temperature : 105±2 Applied current : Per spec. Time : 500 hours							

AR-001A



SPECIFICATION FOR APPROVAL

REF :

PAGE: 7

PROD. NAME	SHIELDED SMD POWER INDUCTOR	ABC'S DWG NO.	SP1206□□□□L□-□□□
		ABC'S ITEM NO.	

. UL CARD :

OBMW2	January 7, 1988				
Component-Magnet Wire					E104048 (S)
MITSUBISHI CABLE INDUSTRIES LTD					
4-3 IKEJIRI ITAMI , HYOGO 664 JAPAN					
Mtl		Coat Typ	ANSI	Temp	
Dsg	BC	Oyercoat	Type	Class	
EDW-R52	Medis	Ester-imide	—	155	

Marking : Company name and type designation on package or reels.

See General Information Preceding These Recognitions.

For use only in equipment where the acceptability of the combination is determined by Underwriters Laboratories Inc.

Report : January 5, 1988.

302279005	H7642	Underwriters Laboratories Inc.®	D11/0149909
-----------	-------	---------------------------------	-------------

AR-001A

