



CHENMKO ENTERPRISE CO.,LTD

SURFACE MOUNT

N-Channel Enhancement Mode Field Effect Transistor

VOLTAGE 25 Volts CURRENT 60 Ampere

CHM75A3PAPT

Lead free devices

APPLICATION

- * Servo motor control.
- * Power MOSFET gate drivers.
- * Other switching applications.


FEATURE

- * Small package. (TO-252A)
- * Super high dense cell design for extremely low Rds(ON).
- * High power and current handing capability.


CONSTRUCTION

- * N-Channel Enhancement

CIRCUIT



TO-252A



1 Gate
2 Source
3 Drain(Heat Sink)

Dimensions in inches and (millimeters)

TO-252A

Absolute Maximum Ratings

T_A = 25°C unless otherwise noted

Symbol	Parameter	CHM75A3PAPT	Units
V _{DSS}	Drain-Source Voltage	25	V
V _{GSS}	Gate-Source Voltage	±20	V
I _D	Maximum Drain Current - Continuous	60	A
	- Pulsed (Note 3)	200	
P _D	Maximum Power Dissipation at T _c = 25 °C	56	W
T _J	Operating Temperature Range	-55 to 150	°C
T _{STG}	Storage Temperature Range	-55 to 150	°C

Note : 1. Surface Mounted on FR4 Board , t <=10sec
 2. Pulse Test , Pulse width <= 300us , Duty Cycle <= 2%
 3. Repetitive Rating , Pulse width limited by maximum junction temperature
 4. Guaranteed by design , not subject to production testing

Thermal characteristics

R _{θJA}	Thermal Resistance, Junction-to-Ambient (Note 1)	50	°C/W
------------------	--	----	------

2007-06

ELECTRICAL CHARACTERISTIC (CHM75A3PAPT)

Electrical Characteristics $T_A = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Conditions	Min	Typ	Max	Units
--------	-----------	------------	-----	-----	-----	-------

OFF CHARACTERISTICS

BV_{DSS}	Drain-Source Breakdown Voltage	$V_{\text{GS}} = 0 \text{ V}, I_D = 250 \mu\text{A}$	25			V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{\text{DS}} = 25 \text{ V}, V_{\text{GS}} = 0 \text{ V}$			1	μA
I_{GSSF}	Gate-Body Leakage	$V_{\text{GS}} = 20\text{V}, V_{\text{DS}} = 0 \text{ V}$			+100	nA
I_{GSSR}	Gate-Body Leakage	$V_{\text{GS}} = -20\text{V}, V_{\text{DS}} = 0 \text{ V}$			-100	nA

ON CHARACTERISTICS (Note 2)

$V_{\text{GS(th)}}$	Gate Threshold Voltage	$V_{\text{DS}} = V_{\text{GS}}, I_D = 250 \mu\text{A}$	1		3	V
$R_{\text{DS(ON)}}$	Static Drain-Source On-Resistance	$V_{\text{GS}}=10\text{V}, I_D=30\text{A}$		7	9	$\text{m}\Omega$
		$V_{\text{GS}}=4.5\text{V}, I_D=30\text{A}$		10	13	
g_{FS}	Forward Transconductance	$V_{\text{DS}} = 10\text{V}, I_D = 15\text{A}$		12		S

Dynamic Characteristics

C_{iss}	Input Capacitance	$V_{\text{DS}} = 15\text{V}, V_{\text{GS}} = 0\text{V}, f = 1.0 \text{ MHz}$		1180		pF
C_{oss}	Output Capacitance			270		
C_{rss}	Reverse Transfer Capacitance			145		

SWITCHING CHARACTERISTICS (Note 4)

Q_g	Total Gate Charge	$V_{\text{DS}}=15\text{V}, I_D=20\text{A}$ $V_{\text{GS}}=5\text{V}$		10	13	nC
Q_{gs}	Gate-Source Charge			3.6		
Q_{gd}	Gate-Drain Charge			2.9		
t_{on}	Turn-On Time	$V_{\text{DD}}= 15\text{V}$ $I_D=1\text{A}, V_{\text{GS}}= 10 \text{ V}$ $R_{\text{GEN}}= 6\Omega$		12	25	nS
t_r	Rise Time			4	10	
t_{off}	Turn-Off Time			32	65	
t_f	Fall Time			6	15	

DRAIN-SOURCE DIODE CHARACTERISTICS AND MAXIMUM RATINGS

I_s	Drain-Source Diode Forward Current			50	A
V_{SD}	Drain-Source Diode Forward Voltage	$I_s = 20\text{A}, V_{\text{GS}} = 0 \text{ V}$		0.85	V

RATING CHARACTERISTIC CURVES (CHM75A3PAPT)

Typical Electrical Characteristics

Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Gate Charge




Figure 4. On-Resistance Variation with Temperature




Figure 5. Gate Threshold Variation with Temperature

