



CHENMKO ENTERPRISE CO.,LTD

SURFACE MOUNT

P-Channel Enhancement Mode Field Effect Transistor

VOLTAGE 30 Volts CURRENT 8.8 Ampere

CHM4435AZPT

Lead free devices

APPLICATION

- * Servo motor control.
- * Power MOSFET gate drivers.
- * Other switching applications.


FEATURE

- * Small flat package. (SC-73/SOT-223)
- * High density cell design for extremely low $R_{DS(ON)}$.
- * Rugged and reliable.


CONSTRUCTION

- * P-Channel Enhancement

CIRCUIT



SC-73/SOT-223



- 1 Gate
- 2 Source
- 3 Drain (Heat Sink)

Dimensions in millimeters

SC-73/SOT-223

Absolute Maximum Ratings $T_A = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	CHM4435AZPT	Units
V_{DSS}	Drain-Source Voltage	-30	V
V_{GSS}	Gate-Source Voltage	± 20	V
I_D	Maximum Drain Current - Continuous	-8.8	A
	- Pulsed (Note 3)	-35	
P_D	Maximum Power Dissipation	3000	mW
T_J	Operating Temperature Range	-55 to 150	$^\circ\text{C}$
T_{STG}	Storage Temperature Range	-55 to 150	$^\circ\text{C}$

- Note : 1. Surface Mounted on FR4 Board , $t \leq 10\text{sec}$
- 2. Pulse Test , Pulse width $\leq 300\mu\text{s}$, Duty Cycle $\leq 2\%$
- 3. Repetitive Rating , Pulse width limited by maximum junction temperature
- 4. Guaranteed by design , not subject to production testing

Thermal characteristics

$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient (Note 1)	42	$^\circ\text{C/W}$
-----------------	--	----	--------------------

RATING CHARACTERISTIC CURVES (CHM4435AZPT)

Electrical Characteristics $T_A = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Conditions	Min	Typ	Max	Units
--------	-----------	------------	-----	-----	-----	-------

OFF CHARACTERISTICS

BV_{DSS}	Drain-Source Breakdown Voltage	$V_{GS} = 0\text{ V}, I_D = -250\ \mu\text{A}$	-30			V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS} = -24\text{ V}, V_{GS} = 0\text{ V}$			-1	μA
I_{GSSF}	Gate-Body Leakage	$V_{GS} = 20\text{ V}, V_{DS} = 0\text{ V}$			+100	nA
I_{GSSR}	Gate-Body Leakage	$V_{GS} = -20\text{ V}, V_{DS} = 0\text{ V}$			-100	nA

ON CHARACTERISTICS (Note 2)

$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS} = V_{GS}, I_D = -250\ \mu\text{A}$	-1		-3	V
$R_{DS(ON)}$	Static Drain-Source On-Resistance	$V_{GS} = -10\text{ V}, I_D = -8.8\text{ A}$		20	24	$\text{m}\Omega$
		$V_{GS} = -4.5\text{ V}, I_D = -5.0\text{ A}$		27	35	
g_{FS}	Forward Transconductance	$V_{DS} = -15\text{ V}, I_D = -8.8\text{ A}$		12		S

SWITCHING CHARACTERISTICS (Note 4)

Q_g	Total Gate Charge	$V_{DS} = -15\text{ V}, I_D = -4.6\text{ A}$ $V_{GS} = -5\text{ V}$		22	28	nC
Q_{gs}	Gate-Source Charge			7		
Q_{gd}	Gate-Drain Charge			8		
t_{on}	Turn-On Time	$V_{DD} = -15\text{ V}$ $I_D = -1.0\text{ A}, V_{GS} = -10\text{ V}$ $R_{GEN} = 6\ \Omega$		12	24	nS
t_r	Rise Time			6	18	
t_{off}	Turn-Off Time			110	140	
t_f	Fall Time			35	70	

DRAIN-SOURCE DIODE CHARACTERISTICS AND MAXIMUM RATINGS

I_S	Drain-Source Diode Forward Current	(Note 1)			-2.1	A
V_{SD}	Drain-Source Diode Forward Voltage	$I_S = -2.1\text{ A}, V_{GS} = 0\text{ V}$ (Note 2)			-1.2	V