



1. CONFIGURATION & DIMENSIONS :



UNIT : mm (inch)

SIZE	L	W	H	A	B	gram
6	48.10 (1.894)	38.10 (1.500)	21.50 (0.846)	40.50 (1.594)	9.50 (0.374)	198.45

2. SCHEMATIC :



3. ELECTRICAL CHARACTERISTICS (@ 25°C) :

a. Primary Voltage	AC 115/230 V 50/60 Hz .
b. NO Load Primary Current	Less Than 35mA .
Input AC 115V 60Hz .	Less Than 40mA .
Input AC 230V 50Hz .	Series AC 25.40V .
c. Secondary Voltage (±5%)	Parallel AC 12.70V .
d. Secondary Load Current	Series 350mA .
	Parallel 700mA .
e. Full Load Primary Current	Less Than 55mA .
Input AC 115V 60Hz .	Less Than 100mA .
Input AC 230V 50Hz .	Series 16.00V .
f. Full Load Secondary Voltage (±5%)	Parallel 8.00V .
g. DC Resistance	
Pin 1-2	Primary = 455 Ohm .
Pin 3-4	= 455 Ohm .
Pin 5-6	Secondary = 5.12 Ohm .
Pin 7-8	= 5.12 Ohm .
h. Insulation Resistance	DC 500V 100Meg Ohm Of More .
i. Withstand Voltage (Hi-Pot)	AC 1500V 60Hz 1 Minutes .
j. Temperature Rise	Less Than 60 Deg C .
k. Core Size	UI-29 x 10.30 m/m .



RoHS Compliant

NOTE : Specifications subject to change without notice. Please check our website for latest information.

05.06.2008



SUPERWORLD ELECTRONICS (S) PTE LTD