

# VTX-5786E Pulsed Coupled Cavity TWT

The VTX-5786E pulsed-coupled cavity TWT covers 9.5 GHz to 10.0 GHz with 1.0 kW peak output power, 50 % duty cycle. This device has a non intercepting grid pulsed and single stage depressed collector to achieve 47 dB gain.

Custom configurations are also available. These variations in the performance and configuration include: cooling method (affects average power level), mechanical configuration, electrical and RF connections, & Multiple stage depressed collector.

## Typical Operating Parameters

### Features

- 9.5 GHz to 10.0 GHz
- 1.0 kW PEAK OUTPUT POWER
- 50% DUTY CYCLE
- NON INTERCEPTING GRID PULSED
- 47 dB GAIN
- SINGLE STAGE DEPRESSED COLLECTOR
- FORCED LIQUID COOLED
- PPM FOCUSED
- WR 90 WAVEGUIDE, INPUT AND OUTPUT

PARAMETER	MIN	MAX	UNIT
Cathode Voltage	-12	-11	kV
Cathode Current	---	1	a
Heater Voltage	6	8	V
Heater Current	---	3	A
Collector Voltage	8	9	kV
Grid Bias Voltage	-250	-300	V
Grid Pulse Voltage	220	320	v
RF Drive Power	---	.03	mW
Pulse Width	---	50	μsec
Duty Cycle	---	30	%
Cooling Flow Rate	2	---	gpm
Pressure Drop	---	15	psi
Weight	---	12	lbs
Dimensions	---	4 dia X 16 lg	inches

The values listed above represent specified limits for the product and are subject to change. The data should be used for basic information only. Formal, controlled specifications may be obtained from CPI for use in equipment design.

For additional information on CPI MPP products contact:

CPI MPP, Coupled Cavity TWT Operation - 3120 Hansen Way, Palo Alto, CA 94303-0750  
 Phone: 650-846-3073, Fax: 650-857-1708, Email: [marketing@mpp.cpii.com](mailto:marketing@mpp.cpii.com), [www.cpii.com/mpp](http://www.cpii.com/mpp)