

**LED DOT MATRIX**
**BL-M19X881**
**Features:**

- 46.80mm (1.9") F 4.8 dot matrix LED display.
- Low current operation.
- Excellent character appearance.
- Easy mounting on P.C. Boards or sockets.
- I.C. Compatible.
- ROHS Compliance.


**Super Bright**
**Electrical-optical characteristics: (Ta=25 ) (Test Condition: IF=20mA)**

Part No		Chip			VF Unit:V		Iv TYP.(mcd)
Row Cathode Column Anode	Row Anode Column Cathode	Emitted Color	Material	λ <sub>p</sub> (nm)	Typ	Max	
BL-M19C881S-XX	BL-M19D881S-XX	Hi Red	GaAlAs/GaAs,SH	660	1.85	2.20	270
BL-M19C881D-XX	BL-M19D881D-XX	Super Red	GaAlAs/GaAs,DH	660	1.85	2.20	310
BL-M19C881UR-XX	BL-M19D881UR-XX	Ultra Red	GaAlAs/GaAs,DDH	660	1.85	2.20	450
BL-M19C881E-XX	BL-M19D881E-XX	Orange	GaAsP/GaP	635	2.10	2.50	220
BL-M19C881Y-XX	BL-M19D881Y-XX	Yellow	GaAsP/GaP	585	2.10	2.50	220
BL-M19C881G-XX	BL-M19D881G-XX	Green	GaP/GaP	570	2.20	2.50	240

**Ultra Bright**
**Electrical-optical characteristics: (Ta=25 ) (Test Condition: IF=20mA)**

Part No		Chip			VF Unit:V		Iv TYP.(mcd)
Row Cathode Column Anode	Row Anode Column Cathode	Emitted Color	Material	λ <sub>p</sub> (nm)	Typ	Max	
BL-M19C881UHR-XX	BL-M19D881UHR-XX	Ultra Red	AlGaInP	645	2.10	2.50	450
BL-M19C881UE-XX	BL-M19D881UE-XX	Ultra Orange	AlGaInP	630	2.10	2.50	255
BL-M19C881YO-XX	BL-M19D881YO-XX	Ultra Amber	AlGaInP	619	2.10	2.50	255
BL-M19C881UY-XX	BL-M19D881UY-XX	Ultra Yellow	AlGaInP	590	2.10	2.50	255
BL-M19C881UG-XX	BL-M19D881UG-XX	Ultra Green	AlGaInP	574	2.20	2.50	380
BL-M19C881PG-XX	BL-M19D881PG-XX	Ultra Pure Green	InGaN	525	3.80	4.50	400
BL-M19C881B-XX	BL-M19D881B-XX	Ultra Blue	InGaN	470	2.70	4.20	270
BL-M19C881W-XX	BL-M19D881W-XX	Ultra White	InGaN	/	2.70	4.20	350

--XX: Surface / Lens color :

Number	0	1	2	3	4	5
Ref Surface Color	White	Black	Gray	Red	Green	
Epoxy Color	Water clear	White diffused	Red Diffused	Green Diffused	Yellow Diffused	

**LED DOT MATRIX**
**BL-M19X881**
**Absolute maximum ratings (Ta=25 )**

Parameter		S	D	UR	E	Y	G	Unit
Forward Current $I_f$		25	25	25	25	25	30	mA
Power Dissipation $P_d$		60	60	60	60	60	65	mW
Reverse Voltage $V_R$		5	5	5	5	5	5	V
Peak Forward Current $I_{PF}$ (Duty 1/10 @1KHZ)		150	150	150	150	150	150	mA
Operation Temperature $T_{OPR}$	-40 to +80							
Storage Temperature $T_{STG}$	-40 to +85							
Lead Soldering Temperature $T_{SOL}$	Max.260±5 for 3 sec Max. (1.6mm from the base of the epoxy bulb)							

**■ Absolute maximum ratings (Ta=25°C)**


Parameter	UHR	UE	YO	UY	UG	PG	B	W	Unit
Forward Current $I_f$	30	30	30	30	30	30	30	30	mA
Power Dissipation $P_d$	75	65	65	65	75	110	120	120	mW
Reverse Voltage $V_R$	5	5	5	5	5	5	5	5	V
Peak Forward Current $I_{PF}$ (Duty 1/10 @1KHZ)	150	150	150	150	150	150	100	100	mA
Operation Temperature $T_{OPR}$	-40 to +80								
Storage Temperature $T_{STG}$	-40 to +85								
Lead Soldering Temperature $T_{SOL}$	Max.260±5 for 3 sec Max. (1.6mm from the base of the epoxy bulb)								

LED DOT MATRIX


BL-M19X881

Package configuration & Internal circuit diagram


BL-M19X881 Series



BL-M19C881



BL-M19D881




Notes:

1. All dimensions are in millimeters (inches)
2. Tolerance is  $\pm 0.25(0.01)$  unless otherwise noted.
3. Specifications are subject to change without notice.

## LED DOT MATRIX

BL-M19X881

### Typical electrical-optical characteristics curves:



- |   |                                      |
|---|--------------------------------------|
| (1) - GaAsP/GaAs 655nm/Red                | (9) - GaAlAs 880nm                   |
| (2) - GaP 570nm/Yellow Green              | (10) - GaAs/GaAs & GaAlAs/GaAs 940nm |
| (3) - GaAsP/GaP 585nm/Yellow              | (A) - GaN/SiC 430nm/Blue             |
| (4) - GaAsP/GaP 635nm/Orange & Hi-Eff Red | (B) - InGaN/SiC 470nm/Blue           |
| (5) - GaP 700nm/Bright Red                | (C) - InGaN/SiC 505nm/Ultra Green    |
| (6) - GaAlAs/GaAs 660nm/Super Red         | (D) - InGaAl/SiC 525nm/Ultra Green   |
| (8) - GaAsP/GaP 610nm/Super Red           |                                      |



FORWARD VOLTAGE (Vf)  
FORWARD CURRENT VS.  
FORWARD VOLTAGE




FORWARD CURRENT (mA)  
RELATIVE LUMINOUS  
INTENSITY VS. FORWARD  
CURRENT



AMBIENT TEMPERATURE Ta( )  
FORWARD CURRENT VS. AMBIENT  
TEMPERATURE



AMBIENT TEMPERATURE Ta( )



NOTE:25 free air temperature unless otherwise specified