



### 1. CONFIGURATION & DIMENSIONS :



UNIT : mm (inch)

SIZE (VA)	L	W	H	A-6 6 PIN	B	WT. (gram)	OPTIONAL BRACKET *		
							NO.	MW	MD
1.0	25.40 (1.000)	35.30 (1.390)	21.08 (0.830)	6.35 (0.250)	30.48 (1.200)	98.93	---	---	---

### 2. SCHEMATIC :



### 3. ELECTRICAL CHARACTERISTICS ( @ 25°C ) :

a. Primary Voltage	AC 115 V 60 Hz .
b. No Load Primary Current	Less Than 10mA .
c. Secondary Voltage (±5%)	Series AC 41.00 V . Parallel AC 20.50 V .
d. Secondary Load Current	Series 25mA . Parallel 50mA .
e. Full Load Primary Current	Less Than 15 mA .
f. Full Load Secondary Voltage (±5%)	Series 34.00V . Parallel 17.00V .
g. DC Resistance	
Pin 1-2	Primary = 820 Ohm .
Pin 3-4	Secondary = 74.50 Ohm .
Pin 5-6	= 80.20 Ohm .
h. Insulation Resistance	DC 500V 100Meg Ohm Of More .
i. Withstand Voltage (Hi-Pot)	AC 1500V 60Hz 1 Minutes .
j. Temperature Rise	Less Than 60 Deg C .
k. Core Size	EI-25.4 x 18.50 m/m .
l. Turns & Wire Gauge	
Primary      Pin 1-2	3000 Turns Diameter 0.07 mm
Secondary-1   Pin 3-4	535 Turns Diameter 0.11 mm
Secondary-2   Pin 5-6	535 Turns Diameter 0.11 mm



**RoHS Compliant**

NOTE : Specifications subject to change without notice. Please check our website for latest information.

25.02.2008



**SUPERWORLD ELECTRONICS (S) PTE LTD**