

Silicon PNP Power Transistors

2N6229 2N6230 2N6231

DESCRIPTION

- With TO-3 package
- Low collector saturation voltage
- Excellent safe operating area

APPLICATIONS

- For high power audio; disk head positioners and other linear applications.

PINNING

PIN	DESCRIPTION
1	Base
2	Emitter
3	Collector




Fig.1 simplified outline (TO-3) and symbol

Absolute maximum ratings($T_a = 25^\circ\text{C}$)

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
V_{CBO}	Collector-base voltage	2N6229	-100	V
		2N6230	-120	
		2N6231	-140	
V_{CEO}	Collector-emitter voltage	2N6229	-100	V
		2N6230	-120	
		2N6231	-140	
V_{EBO}	Emitter-base voltage	Open collector	-7	V
I_C	Collector current		-10	A
P_D	Total power dissipation	$T_C=25$	150	W
T_j	Junction temperature		150	
T_{stg}	Storage temperature		-65~200	

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	VALUE	UNIT
$R_{th\ j-c}$	Thermal resistance junction to case	0.875	/W

Silicon PNP Power Transistors

2N6229 2N6230 2N6231

CHARACTERISTICS

T_j=25 unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{CEO(SUS)}	Collector-emitter sustaining voltage	2N6229	-100			V
		2N6230	-120			
		2N6231	-140			
V _{CEsat}	Collector-emitter saturation voltage	I _C =-4A; I _B =-0.4A			-1.0	V
V _{BE}	Base-emitter on voltage	I _C =-5A; V _{CE} =-2V			-2.0	V
I _{CEO}	Collector cut-off current	V _{CE} =Rated V _{CEO} ; I _B =0			-5.0	mA
I _{CBO}	Collector cut-off current	V _{CB} =Rated V _{CBO} ; I _E =0			-1.0	mA
I _{EBO}	Emitter cut-off current	V _{EB} =-7V; I _C =0			-0.1	mA
h _{FE}	DC current gain	2N6229	25		100	
		2N6230	20		80	
		2N6231	15		60	
f _T	Transition frequency	I _C =-0.5A; V _{CE} =-4V	1			MHz

Silicon PNP Power Transistors

2N6229 2N6230 2N6231

PACKAGE OUTLINE

