

P-tec Corp. Tel:(800)688-0613  
 2405 Commerce Circle Tel:(719) 589 3122  
 Alamosa Co. 81101 Fax:(719) 589 3592  
 www.p-tec.net sales@p-tec.net



## PL00240 Series SMD LED Right Angle 0803 Package

### Features

- \*Oval Lens Side View Package 3.0 x 2.0 x 1.0mm
- \*GaN Ultra Bright White Chip used
- \*Low Current Requirements
- \*High Light Output
- \*Compatible with IR Solder-Process
- \*Industry Standard Footprint
- \*2000 or 1000 pcs per Reel
- \*RoHS Compliant




### Absolute Maximum Ratings at $T_A = 25^\circ\text{C}$

Power Dissipation .....	120mW
Reverse Voltage (<math><100\mu\text{A}</math>) .....	5.0V
Max Forward Current .....	30mA
Peak Forward Current(1/10 Duty Cycle, 0.1ms Pulse Width) .....	100mA
Operating Temperature Range .....	-40°C to +85°C
Storage Temperature Range .....	-40°C to +85°C
Reflow Soldering Temperature.....	260°C for 10 seconds

### Electrical & Optical Characteristics at $T_A = 25^\circ\text{C}$

Part Number	Emitting Color	Chip Material	Chromaticity Coordinates Typ		Viewing Angle 2θ1/2 Deg	Forward Voltage @20mA (V)		Luminous Intensity @20mA (mcd)	
			X	Y		Typ	Max	Min	Typ
PL00240-WCW03	White	GaN	0.31	0.31	120°	3.5	4.0	50.0	135.0

Package Dimensions are in **Millimeters**. Tolerance is  $\pm 0.25\text{mm}$  unless otherwise specified.



#### Recommended Soldering Pad Layout

