



Bulk Metal® Foil Technology Power and Current Sensing Resistors with TCR of 2 ppm/°C, Tolerance to ± 0.01 % and power up to 10 Watts



Any value available within resistance range

The basic features of Vishay Bulk Metal® Foil resistors; tight resistance tolerance, fast response time, low TCR, and exceptional long-term stability, are available for power-circuit applications. Typical applications are non-inductive design, current sensing applications, deflection amplifiers, constant current power supplies, forced balance electronic scales, graphic display computers, character generation on CRTs, and electron beam controls.

Our Application Engineering Department is available to advise and to make recommendations. For non-standard technical requirements and special applications, please contact us.



FEATURES

- Temperature Coefficient of Resistance (TCR): ± 2 ppm/°C typical (- 55 °C to + 125 °C, + 25 °C Ref.) (see Tables 1 and 2)
- Tolerance: to ± 0.01 % (see Tables 1 and 2)
- Power Rating (heat-sinked): 10 W
- Load Life Stability: ± 0.005 % at 25 °C, 2000 hours at Rated Power
- Resistance Range: 0.05 Ω to 80 k Ω
- Electrostatic Discharge (ESD) above 25 000 V
- Non Inductive, Non Capacitive Design
- Rise Time: 1 ns without Ringing
- Current Noise: < - 40 dB
- Thermal EMF: 0.05 μ V/°C typical
- Voltage Coefficient: < 0.1 ppm/V
- Non Inductive: < 0.08 μ H
- Non Hot Spot Design
- Terminal Finishes Available: Lead (Pb)-free Tin/Lead Alloy
- Any Value available within Resistance Range (e.g. 1K2345)
- Prototype Samples available from 48 hours. For more Information, please contact foil@vishay.com
- For better Performances, please see VFP-3Z and VFP-4Z Datasheets



RoHS* COMPLIANT

TABLE 1 - VFP-3 ¹⁾ SPECIFICATIONS			
RESISTANCE RANGE (Ω)	STANDARD TOLERANCE	TYPICAL TCR ³⁾	MAXIMUM TCR ³⁾
50 to 80K	± 0.01 %	± 2 ppm/°C	± 5 ppm/°C
25 to < 50	± 0.02 %		± 7 ppm/°C
10 to < 25	± 0.05 %		± 10 ppm/°C
5 to < 10	± 0.1 %		± 13 ppm/°C
2 to < 5	± 0.25 %		± 20 ppm/°C
1 to < 2	± 0.5 %		± 25 ppm/°C
0.5 to < 1	± 1.0 %		± 50 ppm/°C
0.25 to < 0.5	± 2.0 %		
0.1 to < 0.25	± 5.0 %		

TABLE 2 - VFP-4 ^{1), 2)} SPECIFICATIONS			
RESISTANCE RANGE (Ω)	STANDARD TOLERANCE	TYPICAL TCR ³⁾	MAXIMUM TCR ³⁾
10 to 500	± 0.01 %	± 2 ppm/°C	± 5 ppm/°C
5 to < 10	± 0.02 %		± 6 ppm/°C
2 to < 5	± 0.05 %		± 8 ppm/°C
1 to < 2	± 0.1 %		± 10 ppm/°C
0.5 to < 1	± 0.25 %		± 15 ppm/°C
0.25 to < 0.5	± 0.5 %		± 20 ppm/°C
0.1 to < 0.25	± 1.0 %		± 25 ppm/°C
0.05 to < 0.1	± 2.0 %		± 30 ppm/°C

Notes

Tighter tolerance available upon request
See page 3 in this data sheet for numbered footnotes.

1. Weight = 15 g Max
2. VFP-4 available up to 500 Ω .
3. - 55 °C to + 125 °C, + 25 °C Ref.

* Pb containing terminations are not RoHS compliant, exemptions may apply

FIGURE 1 - STANDARD IMPRINTING AND DIMENSIONS in inches (millimeters)




TABLE 3 - SPECIFICATIONS

Stability Load Life at 2000 hours	± 0.05 % maximum ΔR under full rated power (3 W at + 25 °C)
Power Rating At + 25 °C	10 W or 3 A ¹⁾ on heat sink ²⁾ 3 W or 3 A ¹⁾ in free air Power rating based on ΔR. Further derating not necessary.
Current Noise	< 0.010 μV (RMS)/V of applied voltage (- 40 dB)
High Frequency Operation Rise Time Inductance (L) ³⁾ Capacitance (C)	1.0 ns at 1 kΩ 0.1 μH maximum; 0.08 μH typical 1.0 pF maximum; 0.5 pF typical
Voltage Coefficient	< 0.1 ppm/V ⁴⁾
Operating Temp. Range	- 55 °C to + 150 °C
Maximum Working Voltage⁵⁾	350 V
Thermal EMF⁶⁾	0.5 μV/°C typical (lead effect)

FIGURE 2 - POWER DERATING CURVE





FIGURE 3 - TRIMMING TO VALUES
(Conceptual Illustration)





Bulk Metal® Foil Technology Power and Current Sensing Resistors with TCR of 2 ppm/°C, Tolerance to ± 0.01 % and power up to 10 Watts

Vishay Foil Resistors

TABLE 4 - POWER RESISTOR ENVIRONMENTAL PERFORMANCE COMPARISON

	METHOD PARAGRAPH ⁷⁾	MIL-PRF-39009 ΔR LIMITS	VFP-3, VFP-4 MAXIMUM TEST DATA ¹⁰⁾
TEST GROUP I			
Conditioning	4.8.2	± 0.2 % + 0.01 Ω	± 0.03 %
TEST GROUP II			
Resistance Temperature Characteristic (- 55 °C to + 125 °C)	4.8.4	< 1 Ω: ± 100 ppm/°C; 1 Ω to 19.6 Ω: ± 50 ppm/°C; ≥ 20 Ω: ± 30 ppm/°C	See tables 1 and 2
Low Temp Storage DWV (750 V at atmosphere pressure)	4.8.16	± 0.3 % + 0.01 Ω	± 0.01 %
Insulation Resistance	4.8.5	± 0.2 % + 0.01 Ω	± 0.005 %
Low Temp Operation	4.8.6	10 ⁴ MΩ	> 10 ⁴ MΩ
Short time Overload ⁹⁾	4.8.7	± 0.3 % + 0.01 Ω	± 0.01 %
Moisture Resistance	4.8.8	± 0.3 % + 0.01 Ω	± 0.01 %
Terminal Strength	4.8.9	± 0.5 % + 0.01 Ω	± 0.05 %
	4.8.10	± 0.2 % + 0.01 Ω	± 0.005 %
TEST GROUP III			
Shock - Specified Pulse	4.8.11	± 0.2 % + 0.01 Ω	± 0.01 %
Vibration - High Frequency	4.8.12	± 0.2 % + 0.01 Ω	± 0.005 %
TEST GROUP IV			
Life Test 10 W at + 25 °C for 2000 hours 60 % power at + 70 °C for 2000 hours	4.8.13	± 1.0 % + 0.01 Ω	± 0.05 %
	-	-	± 0.05 %
TEST GROUP V			
High Temp Exposure (2000 hours at + 150 °C)	4.8.14	± 1.0 % + 0.01 Ω	± 0.03 %


Notes

- Whichever is lower.
- Heat sink chassis dimensions and requirements per MIL-PRF-39009:

	INCHES	MILLIMETERS
L	6.00	152.4
W	4.00	101.6
H	2.00	50.8
T	0.04	1.0
- Inductance (L) due mainly to the leads.
- The resolution limit of existing test equipment (within the measurement capability of the equipment, or "essentially zero").
- Not to exceed power rating of resistor.
- μV/°C relates to EMF due to lead temperature difference and μV/watt due to power applied to the resistor.
- Vishay test data as compared to MIL-PRF-39009 is shown for illustration purposes, Vishay test conditions that deviate from the MIL test method are noted within parentheses.
- Maximum ambient temperature rating is + 150 °C.
- Maximum overload rating is 15 W (5 x rated power in free air; 1.5 x rated power on heat sink), with applied voltage not to exceed 750 V.
- ΔR's are as shown plus 0.001 Ω to allow for measurement errors at low resistance values.

TABLE 5 - GLOBAL PART NUMBER INFORMATION


NEW GLOBAL PART NUMBER: Y073321K5000T9L (preferred part number format)



FOR EXAMPLE: ABOVE GLOBAL ORDER Y0733 21K5000 T 9 L:

TYPE: VFP-3
 VALUE: 21.5 kΩ
 ABSOLUTE TOLERANCE: ± 0.01 %
 TERMINATION: Lead (Pb)-free
 PACKAGING: Bulk Pack

HISTORICAL PART NUMBER: VFP-3T 21K500 T B (will continue to be used)



Note

* For non-standard requests, please contact Application Engineering.



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.