

### Features

- + 5dBm Output Level at 766.5 MHz
- Channel Step Size : 100 kHz
- 2<sup>nd</sup> Harmonic : < - 25dBc
- Spurious Level : < - 70dBc
- Lock Time : < 10 ms
- 30mA Current Consumption
- Strip-line Resonator

### Description

The plerow™ PLL synthesizer module was designed for use in wireless and wireline systems in a wide range of frequency from 50 MHz to 6 GHz. ASB's PLL provides exceptionally low spurious and phase noise performance with fast locking time and low current consumption. All products are available in a surface-mount type package.



### Specifications

Parameter	Unit	Min.	Typical	Max.
Frequency Range	MHz	761.7	766.5	771.3
Output Power	dBm	3	5	7
Supply Voltage	V	4.7	5	5.3
Current Consumption	mA		30	
Channel Step Size	kHz		100	
2 <sup>nd</sup> Harmonics	dBc		-25	
Spurious Level	dBc		-70	
Lock Time	ms		3	10
Reference Frequency	MHz		10	
Reference Input Level	dBm	-5	2	7
Phase Noise (C / N)				
@ 1 kHz	dBc/Hz		-80	
@ 10 kHz			-103	
@ 100 kHz			-120	
Output Impedance	Ω		50	
Operating Temp. Range	°C	-40	25	85
Package Type & Size	mm	SMT, 19.0W×19.0L×5.8H		

1) Measurement conditions are as follows: T = 25°C, V<sub>CC</sub> = 5.0 V, Freq. = 766.5 MHz, 50 ohm system.


### More Information

Website: [www.asb.co.kr](http://www.asb.co.kr)  
E-mail: [sales@asb.co.kr](mailto:sales@asb.co.kr)

Tel: (82) 42-528-7220  
Fax: (82) 42-528-7222

ASB Inc., 4th Fl. Venture Town  
Bldg., 367-17 Gojeong-Dong,  
Seo-Gu, Daejeon 302-716, Korea

### Outline Drawing



Pin Configuration	
1	CLOCK
2	DATA
3	ENABLE
4	OSC IN
9	VCC (VCO)
13	RF OUT
15	VCP (PLL)
16	LOCK DETECT
Others	Ground

Dimension (mm)	
A	19.0
B	19.0
C	5.8
D	1.5
E	0.5
F	1.75
G	1.35
H	15.0
I	0.9

Tolerance: ± 0.2