


High Performance BGA Cooling Solutions w/ Thermal Tape Attachment

ATS PART # ATS-54190K-C2-R0

Features & Benefits

- » High aspect ratio, straight fin heat sinks that are ideal for compact PCB environments
- » Designed specifically for BGAs and other surface mount packages
- » Comes preassembled with high performance thermal interface material



Thermal Performance

*Image above is for illustration purposes only.

| AIR VELOCITY | | THERMAL RESISTANCE | | |
|--------------|-----|----------------------|--------------------|--|
| FT/MIN | M/S | °C/W (UNDUCTED FLOW) | °C/W (DUCTED FLOW) | |
| 200 | 1.0 | 12 | 7.4 | |
| 300 | 1.5 | 9.6 | | |
| 400 | 2.0 | 8.4 | | |
| 500 | 2.5 | 7.5 | | |
| 600 | 3.0 | 6.9 | | |
| 700 | 3.5 | 6.4 | | |
| 800 | 4.0 | 6 | | |

Product Details

| DIMENSION A | DIMENSION B | DIMENSION C | DIMENSION D | INTERFACE MATERIAL | FINISH |
|-------------|-------------|-------------|-------------|--------------------|----------------|
| 19 mm | 19 mm | 14.5 mm | 19 mm | SAINT-GOBAIN C675 | BLACK-ANODIZED |

NOTES

- 1) Dimension C = heat sink height from bottom of the base to the top of the fin field.
- Thermal performance data are provided for reference only. Actual performance may vary by application.
- ATS reserves the right to update or change its products without notice to improve the design or performance.
- Contact ATS to learn about custom options available.



For more information, to find a distributor or to place an order, visit www.qats.com or call: 781.769.2800 (North America); +31 (0) 3569 84715 (Europe).