

SPECIFICATION SHEET
JFW MODEL 50DR-063
DUAL ROTARY ATTENUATOR

JFW Industries, Inc.
 Phone: 317-887-1340
 sales@jfwindustries.com
 www.jfwindustries.com

Frequency Range	DC-1100 MHz
Impedance	50 Ohms nominal
Attenuation Range	0-50 dB in 1 dB steps
VSWR	1.1:1 maximum DC-250 MHz 1.2:1 maximum 250-500 MHz 1.4:1 maximum 500-1100 MHz
Insertion Loss	0.5 dB maximum
Attenuation Accuracy	0.2 dB DC-250 MHz 0.5 dB 250-500 MHz 1.0 dB 500-1100 MHz
RF Input Power	2 Watts average 1000 Watts peak
Direction of Rotation	Attenuation increases in a Clockwise direction
Indexing	30 degrees with stops at Minimum and maximum
RF Connector	BNC, N, SMA or TNC female
Operating Temperature Range	-40°C to +85°C
Physical Size	See outline drawing 092-1919

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	04/16/1993			18362	03/05/2010	C	TRS 03/05/2010
887	11/12/1997	A					
9999	05/12/2003	B	TRS 03/05/2004				