

**Product SKU:** C2119.21.04

**Product Description:** Hook-Up Wire, UL 1015, CSA TEW, Gauge Size (AWG): 18, Conductor/Strands: Solid, Jacket:

Premium Grade PVC, Temperature Range: -20°C to +105°C - Orange - 1000 Ft. Spool

**Product Category:** Electronics - Hook-Up Wire - UL 1015, CSA TEW - SOLID CONDUCTORS - Orange



## **Product Construction:**

Conductor: • 24 thru 10 AWG

• Fully-annealed, tinned copper per ASTM B-33

Solid or stranded

Insulation: • Color Code: See chart below

• Premium grade color-coded PVC

• Temperature range:  $-20\hat{A}^{\circ}C$  to  $+105\hat{A}^{\circ}C$ 

## **Product Specification:**

Conductor Size (AWG): • 18

Conductor/Strands: • Solid

No. of Pairs: • 1

Jacket Color: • Orange

Nominal Insulation Thickness

(in):

• 0.032

Nominal Insulation Thickness

(mm):

• 0.81

Nominal Outside Diameter (in): • 0.104

Nominal Outside Diameter

(mm):

• 2.64

Standard Packaging: • 1000' Spool

Standard Package Quantity:	• 1
UPC #:	• 079407769643
Put-up:	• 1000
SCC-14:	• 50079407769644
Cube:	• 277.0596
Weight Per Unit of Measure:	• .009
ColorOption:	• Red
Product Information:	
Applications:	Internal wiring of electrical and electronic equipment
	• Internal wiring of panels and meters
	Point-to-point wiring
	• Suggested voltage rating: 600 Volts
Compliances:	• CSA Type TEW
	• Designed to Meet UL VW-1 Vertical Wire Flame Test
	• UL Style 1015 - 105°C, 600V
Packaging:	• 10,000 foot (3048m) Reels
	• 1000' (305 m) Spools
	Other put-ups available- consult Customer Service
Reference Charts	
Color Code Chart	
<b>Technical Specifications</b>	
<u>Unit Conversion Factors</u> <u>Cable Design Equations - Balanced Pair</u>	
Insulation and Jacket Properties	
Temperature Conversion Chart	
Decimal and Unit Conversion Factors  Cable Design Equations - Proid Shield	
<u>Cable Design Equations - Braid Shield</u> <u>AWG Conductor Chart</u>	
Conduit Capacity Chart	

<u>Cable Design Equations - Coaxial Cable</u> <u>Engineering Prefixes</u> <u>Coax Connector Cross Reference</u>



Glossary



Designed to Meet UL VW-1 Vertical Wire Flame Test Underwriters Laboratories Inc.

