



General ordering data

| | |
|------------------|---|
| Order No. | 1748260000 |
| Part designation | B2L 3.5/24 F SN SW |
| Version | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 1 mm ² , Pitch: 3.50 mm, No. of poles: 24, 180°, Box |
| EAN | 4032248038091 |
| Qty. | 20 pc(s). |

System parameters

| | |
|---|--------------------------|
| Conductor connection system | Tension clamp connection |
| Outgoing direction of conductor | 180° |
| Pitch | 3.5 mm |
| Pitch in inch | 0.138 inch |
| No. of poles | 24 |
| No. of rows | 2 |
| Stripping length | 7 mm |
| L1 in mm | 38.5 mm |
| L1 in inch | 1.516 inch |
| Electric shock protection to DIN VDE 0470 | IP 20 |
| Electric shock protection to DIN VDE 0470 | Safe from finger touch |

Material data

| | |
|---------------------------|---------------------|
| Insulating material | PBT |
| Colour | black |
| colour chart | Similar to RAL 9011 |
| Insulating material group | IIIa |
| Flammability class UL 94 | V-0 |
| CTI | >= 200 |
| Contact base material | Copper alloy |
| Contact surface | tinned |

Connectable conductors

| | |
|----------------------|----------------------|
| Clamping range, min. | 0.08 mm ² |
|----------------------|----------------------|

Connectable conductors

| | |
|---|----------------------|
| Clamping range, max. | 1 mm ² |
| AWG, min. | 28 |
| AWG, max. | 18 |
| Solid, min. H05(07) V-U | 0.2 mm ² |
| Solid, max. H05(07) V-U | 1 mm ² |
| Flexible, min. H05(07) V-K | 0.2 mm ² |
| Flexible, max. H05(07) V-K | 1 mm ² |
| With wire end ferrule, acc. to DIN 46 228/1, min. | 0.13 mm ² |
| With wire end ferrule, acc. to DIN 46 228/1, max. | 0.34 mm ² |
| w. plastic collar ferrule, DIN 46228 pt 4, min. | 0.13 mm ² |
| w. plastic collar ferrule, DIN 46228 pt 4, max. | 0.34 mm ² |

DIN IEC rating data

| | |
|--|------------------|
| Rated voltage for overvoltage class/pollution severity II/2 | 250 V |
| Rated voltage for overvoltage class/pollution severity III/2 | 125 V |
| Rated voltage for overvoltage class/pollution severity III/3 | 80 V |
| Rated impulse withstand voltage for overvoltage class/pollution severity II/2 | 2.5 kV |
| Rated impulse withstand voltage for overvoltage class/pollution severity III/2 | 2.5 kV |
| Rated impulse withstand voltage for overvoltage class/pollution severity III/3 | 2.5 kV |
| Short-time withstand current resistance | 3 x 1s with 77 A |

CSA rating data

| | |
|------------------------------------|------|
| Rated voltage (Use group D) | 50 V |
| Rated current (Use group D) | 5 A |
| AWG conductor (field wiring), min. | 28 |
| AWG conductor (field wiring), max. | 18 |

UL 1059 rating data

| | |
|-----------------------------|-------|
| Rated voltage (Use group D) | 150 V |
| Rated current (Use group D) | 10 A |
| AWG conductor, min. | 22 |
| AWG conductor, max. | 16 |

Approvals

Approvals institutes



Downloads

| | |
|------|---|
| STEP | 1748260000_26643_B2L_3.5-24_F_SN_SW_STP.stp |
|------|---|

Classifications

| | |
|----------|----|
| ETIM 2.0 | NK |
|----------|----|

Classifications

| | |
|------------|-------------|
| ETIM 3.0 | EC001284 |
| eClass 4.1 | 27-26-07-01 |
| eClass 5.0 | 27-26-07-01 |
| eClass 5.1 | 27-26-07-01 |

Similar products

| Order No. | Part designation | Version |
|------------|--------------------|---|
| 1001260000 | B2L3.5/04F SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 1 mm ² , Pitch: 3.50 mm, No. of poles: 4, 180°, Box |
| 1001270000 | B2L3.5/04F SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 1 mm ² , Pitch: 3.50 mm, No. of poles: 4, 180°, Box |
| 1748010000 | B2L 3.5/6 F SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 1 mm ² , Pitch: 3.50 mm, No. of poles: 6, 180°, Box |
| 1748170000 | B2L 3.5/6 F SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 1 mm ² , Pitch: 3.50 mm, No. of poles: 6, 180°, Box |
| 1748020000 | B2L 3.5/8 F SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 1 mm ² , Pitch: 3.50 mm, No. of poles: 8, 180°, Box |
| 1748180000 | B2L 3.5/8 F SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 1 mm ² , Pitch: 3.50 mm, No. of poles: 8, 180°, Box |
| 1748030000 | B2L 3.5/10 F SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 1 mm ² , Pitch: 3.50 mm, No. of poles: 10, 180°, Box |
| 1748190000 | B2L 3.5/10 F SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 1 mm ² , Pitch: 3.50 mm, No. of poles: 10, 180°, Box |
| 1748040000 | B2L 3.5/12 F SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 1 mm ² , Pitch: 3.50 mm, No. of poles: 12, 180°, Box |
| 1748200000 | B2L 3.5/12 F SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 1 mm ² , Pitch: 3.50 mm, No. of poles: 12, 180°, Box |
| 1748050000 | B2L 3.5/14 F SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 1 mm ² , Pitch: 3.50 mm, No. of poles: 14, 180°, Box |
| 1748210000 | B2L 3.5/14 F SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 1 mm ² , Pitch: 3.50 mm, No. of poles: 14, 180°, Box |
| 1748220000 | B2L 3.5/16 F SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 1 mm ² , Pitch: 3.50 mm, No. of poles: 16, 180°, Box |

| | | |
|------------|--------------------|---|
| 1748060000 | B2L 3.5/16 F SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 1 mm ² , Pitch: 3.50 mm, No. of poles: 16, 180°, Box |
| 1748070000 | B2L 3.5/18 F SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 1 mm ² , Pitch: 3.50 mm, No. of poles: 18, 180°, Box |
| 1748230000 | B2L 3.5/18 F SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 1 mm ² , Pitch: 3.50 mm, No. of poles: 18, 180°, Box |
| 1748080000 | B2L 3.5/20 F SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 1 mm ² , Pitch: 3.50 mm, No. of poles: 20, 180°, Box |
| 1748240000 | B2L 3.5/20 F SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 1 mm ² , Pitch: 3.50 mm, No. of poles: 20, 180°, Box |
| 1748090000 | B2L 3.5/22 F SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 1 mm ² , Pitch: 3.50 mm, No. of poles: 22, 180°, Box |
| 1748250000 | B2L 3.5/22 F SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 1 mm ² , Pitch: 3.50 mm, No. of poles: 22, 180°, Box |
| 1748100000 | B2L 3.5/24 F SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 1 mm ² , Pitch: 3.50 mm, No. of poles: 24, 180°, Box |
| 1748110000 | B2L 3.5/26 F SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 1 mm ² , Pitch: 3.50 mm, No. of poles: 26, 180°, Box |
| 1748270000 | B2L 3.5/26 F SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 1 mm ² , Pitch: 3.50 mm, No. of poles: 26, 180°, Box |
| 1748120000 | B2L 3.5/28 F SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 1 mm ² , Pitch: 3.50 mm, No. of poles: 28, 180°, Box |
| 1748280000 | B2L 3.5/28 F SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 1 mm ² , Pitch: 3.50 mm, No. of poles: 28, 180°, Box |
| 1748130000 | B2L 3.5/30 F SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 1 mm ² , Pitch: 3.50 mm, No. of poles: 30, 180°, Box |
| 1748290000 | B2L 3.5/30 F SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 1 mm ² , Pitch: 3.50 mm, No. of poles: 30, 180°, Box |
| 1748140000 | B2L 3.5/32 F SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 1 mm ² , Pitch: 3.50 mm, No. of poles: 32, 180°, Box |
| 1748300000 | B2L 3.5/32 F SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 1 mm ² , Pitch: 3.50 mm, No. of poles: 32, 180°, Box |
| 1748150000 | B2L 3.5/34 F SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 1 mm ² , Pitch: 3.50 mm, No. of poles: 34, 180°, Box |

| | | |
|------------|--------------------|---|
| 1748310000 | B2L 3.5/34 F SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 1 mm ² , Pitch: 3.50 mm, No. of poles: 34, 180°, Box |
| 1748160000 | B2L 3.5/36 F SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 1 mm ² , Pitch: 3.50 mm, No. of poles: 36, 180°, Box |
| 1748320000 | B2L 3.5/36 F SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 1 mm ² , Pitch: 3.50 mm, No. of poles: 36, 180°, Box |