


PCM-3430

PC/104 Plus Ultra Wide SCSI Module



Features

- High Speed 32-bit PCI Bus Master DMA Transfer Up to 133MB/sec in Burst Mode
- Max Transfer Rate Up to 80MB/sec with Wide LVD SCSI Devices
- Up to 15 LVD SCSI Devices Supported
- LVD SCSI Cable Length Up to 12 Meters
- PCI 2.1 Compliant

Specifications


Processor	LSI Symbios 53C895 Ultra2 SCSI Processor
Max Transfer Rate	80MB/sec
Max Device	15
Power Requirement	+5V
Connector	68-pin Ultra2 LVD SCSI
Operating Temperature	32°F ~ 140°F (0°C ~ 60°C)
Driver Available	DOS, Windows® 95/98, Windows® NT, Windows® 2000, Netware, Linux, Unixware

Ordering Information

- **PCM-3430-A10**
PC/104 Plus Ultra Wide SCSI Module
- **PCM-3430-A10-01**
PC/104 Plus Ultra Wide SCSI Module with 68pin SCSI Cable

PCM-3116

PC/104 PCMCIA/CompactFlash™ to IDE Module



Features

- Allows System to Access the PCMCIA or CompactFlash™ ATA Card Directly as a Standard IDE Drive
- Supports Type I/II/III PCMCIA and Type I/II CompactFlash™ Cards
- No Driver Required

Specifications

Connector	40-pin IDE and 4-pin power connectors
Power Requirement	+5V
Operating Temperature	32°F ~ 158°F (0°C ~ 70°C)

Ordering Information

- **PCM-3116**
PC/104 PCMCIA/CompactFlash™ to IDE Module
- **PCM-3116CF**
PC/104 CompactFlash™ to IDE Module
- **PCM-3116PC**
PC/104 PCMCIA to IDE Module
- **PCM-3116PC/F**
PCMCIA to IDE Drive with 3.5" FDD Form Factor

1

Compact Boards

2

SubCompact Boards

3

Embedded Motherboards

4

Media PC

5

PC/104 CPU Modules

6

ETX CPU Modules

7

RISC CPU Module

8

Mini PCI Modules

9

PC/104 Peripheral Modules

10

Full-size SBC

11

Half-size SBC

12

Accessories