

SPECIFICATION SHEET
JFW MODEL 75DR-015
DUAL ROTARY ATTENUATOR

JFW Industries, Inc.
 Phone: 317-887-1340
 sales@jfwindustries.com
 www.jfwindustries.com

Frequency Range	DC-1000 MHz
Impedance	75 Ohms nominal
Attenuation Range	0-11 dB in 0.1 dB steps
VSWR	1.1:1 maximum DC-100 MHz 1.4:1 maximum 100-500 MHz 1.5:1 maximum 500-1000 MHz
Insertion Loss	1.00 dB typical 1.25 dB maximum
Attenuation Accuracy	DC-100 MHz ± 0.02 dB (0-1 dB) ± 0.05 dB (1-11 dB) 100-500 MHz ± 0.04 dB (0-1 dB) ± 0.20 dB (1-11 dB) 500-1000 MHz ± 0.05 dB (0-1 dB) ± 0.30 dB (1-11 dB)
RF Input Power	1 Watt average 1000 Watts peak
Indexing	30 degrees with no stops
RF Connector	BNC or F female
Physical Size	See outline drawing 092-2135

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
603	09/26/1996	B		9999	05/15/2003	E	BAC 05/18/2005
2401	06/15/2000	C		11230	05/26/2005	F	CLK 05/26/2005
2404	06/16/2000	D		17479	07/28/2009	G	TRS 07/28/2009