


### Features

- +2 dBm Output Level at 1750MHz
- 2nd Harmonic : < -20 dBc
- Spurious Level : < -70 dBc
- Lock Time : < 10ms
- 30 mA Current Consumption

### Description

The plerow™ PLL synthesizer module was designed for use in wireless and wireline systems in a wide range of frequency from 50 MHz to 6 GHz. ASB's PLL provides exceptionally low spurious and phase noise performance with fast locking time and low current consumption. All products are available in a surface-mount type package.



### Specifications

Parameter	Unit	Min.	Typical	Max.
Frequency Range	MHz	1700	1750	1800
Output Power	dBm	+0	+2	+4
Supply Voltage	V	4.75	5.00	5.25
Current Consumption	mA		23	30
Channel Step Size	kHz		100	
2nd Harmonics	dBc			-20
Spurious Level	dBc		-80	-70
Lock Time	ms		3	10
Reference Frequency	MHz		20	
Reference Input Level	dBm	-5	0	5
Phase Noise (C / N)	@ 10 kHz	dBc/Hz	-103	
	@ 100 kHz		-120	
Output Impedance	Ω		50	
Operating Temp. Range	°C	-40	25	+85
Package Type & Size	mm	SMT, 19.0W×19.0L×5.8H		

1) Measurement conditions are as follows: T = 25°C, V<sub>CC</sub> = 5.0 V, Freq. = 1750MHz, 50 ohm system.


### More Information

Website: [www.asb.co.kr](http://www.asb.co.kr)  
E-mail: [sales@asb.co.kr](mailto:sales@asb.co.kr)

Tel: (82) 42-528-7223  
Fax: (82) 42-528-7222

ASB Inc., 4th Fl. Venture Town  
Bldg., 367-17 Goijeong-Dong,  
Seo-Gu, Daejeon 302-716, Korea

### Outline Drawing



Pin Configuration		Dimension (mm)	
1	CLOCK	A	19.0
2	DATA	B	19.0
3	ENABLE	C	5.8
4	OSC IN	D	1.5
9	VCC (VCO)	E	0.5
13	RF OUT	F	1.75
15	VCP (PLL)	G	1.35
16	LOCK DETECT	H	15.0
Others	Ground	I	0.9
		Tolerance: ± 0.2	