

1M CMOS Static RAM (262144x4) 28PIN 624256

型名	社名	温度範囲 (°C)	スイッチング特性										電 源		入 力 [*typ]			出 力 [*typ]		備 考		
			TAAC max (ns)	TCAC max (ns)	TOE max (ns)	TOH min (ns)	TOD max (ns)	TWP min (ns)	TDS min (ns)	TDH min (ns)	TWD min (ns)	TWH max (ns)	VDD or VCC (V)	IDD max (mA)	IDD STANDBY (I SB/I SB2) (mA)	VIL max (V)	VIH min (V)	CI max (pF)	VOL/I VOL max (V/mA)		VOH/I VOH min (V/mA)	Co max (pF)
CY7C106-25	CYPRESS	0~70	25	25	10		10	20	15	0	0	0	4.5~5.5	130		30/25	0.8	2.2	10	0.4/8.0	2.4/4.0	12
CY7C106-35	CYPRESS	0~70	35	35	15		15	25	20	0	0	0	4.5~5.5	130		30/25	0.8	2.2	10	0.4/8.0	2.4/4.0	12
CY7C106-45	CYPRESS	0~70	45	45	20		20	30	25	0	0	0	4.5~5.5	130		30/25	0.8	2.2	10	0.4/8.0	2.4/4.0	12
DPM41028L-20	PARADIGM	0~70	20	20	0	3	8	16	10	0	0	0	4.5~5.5	175		50/5	0.8	2.2	8	0.5/10	2.4/4	8
DPM41028L-25	PARADIGM	0~70	25	25	0	3	8	16	10	0	0	0	4.5~5.5	165		50/5	0.8	2.2	8	0.5/10	2.4/4	8
DPM41028L-35	PARADIGM	0~70	35	35	0	3	12	20	16	0	0	0	4.5~5.5	155		50/5	0.8	2.2	8	0.5/10	2.4/4	8
DPM41028L-45	PARADIGM	0~70	45	45	0	3	15	25	15	0	0	0	4.5~5.5	155		50/5	0.8	2.2	8	0.5/10	2.4/4	8
DPM41028S-20	PARADIGM	0~70	20	20	0	3	8	16	10	0	0	0	4.5~5.5	175		60/10	0.8	2.2	8	0.5/10	2.4/4	8
DPM41028S-25	PARADIGM	0~70	25	25	0	3	8	16	10	0	0	0	4.5~5.5	165		60/10	0.8	2.2	8	0.5/10	2.4/4	8
DPM41028S-35	PARADIGM	0~70	35	35	0	3	12	20	13	0	0	0	4.5~5.5	155		60/10	0.8	2.2	8	0.5/10	2.4/4	8
DPM41028S-45	PARADIGM	0~70	45	45	0	3	15	25	15	0	0	0	4.5~5.5	155		60/10	0.8	2.2	8	0.5/10	2.4/4	8
EDI184256CS-20	EDI	0~70	20	20	3	3	8	15	12	0	0	0	4.5~5.5	150		30/10	0.8	2.2	6*	0.4/8.0	2.4/4.0	8*
EDI184256CS-25	EDI	0~70	25	25	3	3	10	20	15	0	0	0	4.5~5.5	150		30/10	0.8	2.2	6*	0.4/8.0	2.4/4.0	8*
EDI184256CS-35	EDI	0~70	35	35	3	3	20	30	20	0	0	0	4.5~5.5	150		30/10	0.8	2.2	6*	0.4/8.0	2.4/4.0	8*
EDI184256CS-45	EDI	0~70	45	45	3	3	25	35	25	0	0	0	4.5~5.5	150		30/10	0.8	2.2	6*	0.4/8.0	2.4/4.0	8*
EDI184256CS-55	EDI	0~70	55	55	3	3	25	40	25	0	0	0	4.5~5.5	150		30/10	0.8	2.2	6*	0.4/8.0	2.4/4.0	8*
EDI184256LPS/PS-20	EDI	0~70	20	20	3	3	8	15	12	0	0	0	4.5~5.5	150		30/5	0.8	2.2	6*	0.4/8.0	2.4/4.0	8*
EDI184256LPS/PS-25	EDI	0~70	25	25	3	3	10	20	15	0	0	0	4.5~5.5	150		30/5	0.8	2.2	6*	0.4/8.0	2.4/4.0	8*
EDI184256LPS/PS-35	EDI	0~70	35	35	3	3	20	30	20	0	0	0	4.5~5.5	150		30/5	0.8	2.2	6*	0.4/8.0	2.4/4.0	8*
EDI184256LPS/PS-45	EDI	0~70	45	45	3	3	25	35	25	0	0	0	4.5~5.5	150		30/5	0.8	2.2	6*	0.4/8.0	2.4/4.0	8*
EDI184256LPS/PS-55	EDI	0~70	55	55	3	3	25	40	25	0	0	0	4.5~5.5	150		30/5	0.8	2.2	6*	0.4/8.0	2.4/4.0	8*
HM624256ALP/JP-20	HITACHI	0~70	20	20	10	5	10	14	12	0	0	0	4.5~5.5	150		60/0.2	0.8	2.2	6	0.4/8	2.4/4	10
HM624256ALP/JP-25	HITACHI	0~70	25	25	12	5	10	17	15	0	0	0	4.5~5.5	120		60/0.2	0.8	2.2	6	0.4/8	2.4/4	10
HM624256ALP/JP-35	HITACHI	0~70	35	35	15	5	10	25	20	0	0	0	4.5~5.5	120		60/0.2	0.8	2.2	6	0.4/8	2.4/4	10
HM624256AP/JP-20	HITACHI	0~70	20	20	10	5	10	14	12	0	0	0	4.5~5.5	150		60/2.0	0.8	2.2	6	0.4/8	2.4/4	10
HM624256AP/JP-25	HITACHI	0~70	25	25	12	5	10	17	15	0	0	0	4.5~5.5	120		60/2.0	0.8	2.2	6	0.4/8	2.4/4	10
HM624256AP/JP-35	HITACHI	0~70	35	35	15	5	10	25	20	0	0	0	4.5~5.5	120		60/2.0	0.8	2.2	6	0.4/8	2.4/4	10
HM624256JP-35	HITACHI	0~70	35	35	18	5	10	30	20	0	0	3	4.5~5.5	120		60/2.0	0.8	2.2	6	0.4/8	2.4/4	11
HM624256JP-45	HITACHI	0~70	45	45	23	5	15	35	25	0	0	3	4.5~5.5	120		60/2.0	0.8	2.2	6	0.4/8	2.4/4	11
HM624256JP-55	HITACHI	0~70	55	55	23	5	15	35	25	0	0	3	4.5~5.5	120		60/2.0	0.8	2.2	6	0.4/8	2.4/4	11
HM624256LP-35	HITACHI	0~70	35	35	18	5	10	30	20	0	0	3	4.5~5.5	120		60/0.2	0.8	2.2	6	0.4/8	2.4/4	11
HM624256LP-45	HITACHI	0~70	45	45	23	5	15	35	25	0	0	3	4.5~5.5	120		60/0.2	0.8	2.2	6	0.4/8	2.4/4	11
HM624256P-35	HITACHI	0~70	35	35	18	5	10	30	20	0	0	3	4.5~5.5	120		60/2.0	0.8	2.2	6	0.4/8	2.4/4	11
HM624256P-45	HITACHI	0~70	45	45	23	5	15	35	25	0	0	3	4.5~5.5	120		60/2.0	0.8	2.2	6	0.4/8	2.4/4	11
HM624257AJP-20	HITACHI	0~70	20	20	5	10	14	12	0	0	0	0	4.5~5.5	150		60/2	0.8	2.2	5	0.4/8	2.4/4	10
HM624257AJP-25	HITACHI	0~70	25	25	5	12	17	15	0	0	0	0	4.5~5.5	120		60/2.0	0.8	2.2	5	0.4/8	2.4/4	10
HM624257AJP-35	HITACHI	0~70	35	35	5	15	25	20	0	0	0	0	4.5~5.5	120		60/2.0	0.8	2.2	5	0.4/8	2.4/4	10
HM624257ALJP-20	HITACHI	0~70	20	20	5	10	14	12	0	0	0	0	4.5~5.5	150		60/2	0.8	2.2	5	0.4/8	2.4/4	10
HM624257ALJP-25	HITACHI	0~70	25	25	5	12	17	15	0	0	0	0	4.5~5.5	120		60/2.0	0.8	2.2	5	0.4/8	2.4/4	10
HM624257ALJP-35	HITACHI	0~70	35	35	5	15	25	20	0	0	0	0	4.5~5.5	120		60/2.0	0.8	2.2	5	0.4/8	2.4/4	10
HM624257JP-35	HITACHI	0~70	35	35	5	20	30	20	0	0	3	0	4.5~5.5	120		60/2.0	0.8	2.2	5	0.4/8	2.4/4	11