

MATERIAL SAFETY DATA SHEET

Finished Product

Date-Issued: 01/20/2003
MSDS Ref. No: RX2600-6
Date-Revised: 01/20/2003
Revision No: New MSDS

ECG Label and Adhesive Remover

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: ECG Label and Adhesive Remover**PRODUCT DESCRIPTION:** Label/Adhesive Remover**PRODUCT CODE:** RX2600-6

MANUFACTURER

NTE Electronics, Inc.
 44 Farrand St.
 Bloomfield, NJ 07003

Phone: 973-748-5089

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (U.S.): (800) 424-9300**CANUTEC:** (613) 996-6666**Emergency Phone:** 1-888-748-1777 8:00 am - 5:00 pm CST

2. COMPOSITION / INFORMATION ON INGREDIENTS

<u>Chemical Name</u>	<u>Wt.%</u>	<u>CAS#</u>	<u>EINECS#</u>
d-Limonene	30 - 50	5989-27-5	
Mixed Aliphatic Hydrocarbons	70 - 85	64742-48-9	
Carbon dioxide	1 - 4	124-38-9	

EEC LABEL SYMBOL AND CLASSIFICATION



EEC Irritant - "Xi"

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE: Clear to amber, sticky resin.

POTENTIAL HEALTH EFFECTS

EYES: Liquid contact can cause irritation, which may be severe.

SKIN: Prolonged or repeated contact may cause skin irritation.

INGESTION: Harmful if swallowed.

INHALATION: Prolonged or excessive inhalation may cause respiratory tract irritation.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Contact may cause eye irritation.

SKIN: May cause slight irritation.

INGESTION: Not a likely route of exposure.

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

SKIN: Wash with soap and water. Get medical attention if irritation develops or persists.

INGESTION: Ingestion is unlikely because of the physical properties and is not expected to be hazardous. Do not induce vomiting unless instructed to do so by a physician.

INHALATION: Remove to fresh air.

5. FIRE FIGHTING MEASURES

FLAMMABLE LIMITS: 0.7% to 3.1%

GENERAL HAZARD: Combustible Liquid. Can form explosive mixtures at temperatures at or above the flash point.

HAZARDOUS COMBUSTION PRODUCTS: Smoke, fumes and oxides of carbon.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Avoid runoff into storm sewers and ditches which lead to waterways.

LARGE SPILL: -Implement cleanup procedures.

-If in public area, keep public away and advise authorities.

-Recover by pumping (use an explosion proof or hand pump) or with a suitable absorbent.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.

RELEASE NOTES: Spills and releases may have to be reported to Federal and/or local authorities.

SPECIAL PROTECTIVE EQUIPMENT: Only personnel equipped with proper respiratory and skin/eye protection should be permitted in area. See Section 8 for details.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Keep container closed when not in use.

HANDLING: Avoid prolonged or repeated contact with skin.

STORAGE: Keep away from sources of ignition.

STORAGE TEMPERATURE: (120°F) maximum

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES:

OSHA HAZARDOUS COMPONENTS (29 CFR 1910.1200)

	<u>EXPOSURE LIMITS</u>					
	<u>OSHA PEL</u>		<u>ACGIH TLV</u>		<u>Supplier OEL</u>	
	<u>ppm</u>	<u>mg/m³</u>	<u>ppm</u>	<u>mg/m³</u>	<u>ppm</u>	<u>mg/m³</u>
d-Limonene						[1]
Mixed Aliphatic Hydrocarbons						TWA 1900

OSHA TABLE COMMENTS:

1. NL = Not Listed

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

SKIN: The glove(s) listed below may provide protection against permeation. Gloves of other chemically resistant materials may not provide adequate protection.

Buna

Butyl

Natural Latex

Neoprene

Solvex

Viton

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Strong, fruity odor.

COLOR: Clear to Light yellow

pH: Not Applicable

PERCENT VOLATILE: 30

BOILING POINT: (325°F) to (332°F)

SPECIFIC GRAVITY: 0.7630 to 0.7930 @ 25°C

(VOC): 750 to 800 g/L (non-exempt VOC)

10. STABILITY AND REACTIVITY

STABLE: YES

HAZARDOUS POLYMERIZATION: NO

STABILITY: Stable under normal conditions.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Dioxide and carbon Monoxide may form when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

EYE EFFECTS: May be mildly irritating to eyes.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: There is limited information available on the environmental fate and effects of this material. The primary environmental concern for release is the impact on aquatic and terrestrial species. Due care should be taken to avoid the accidental release of this material into the environment.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Federal, State, and Local laws governing disposal of materials can differ. Ensure compliance with proper authorities before disposal.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: CONSUMER COMMODITY ORM-D

TECHNICAL NAME: Terpene Hydrocarbons N.O.S.

PRIMARY HAZARD CLASS/DIVISION: No classification

AIR (ICAO/IATA)

PROPER SHIPPING NAME: CONSUMER COMMODITY ID8000

PRIMARY HAZARD CLASS/DIVISION: 9

UN/NA NUMBER: ID8000

PACKING GROUP: NA

VESSEL (IMO/IMDG)

PROPER SHIPPING NAME: AEROSOLS IN LIMITED QUANTITIES OF CLASS 2

PRIMARY HAZARD CLASS/DIVISION: 2.2

UN/NA NUMBER: 1950

PACKING GROUP: NA

15. REGULATORY INFORMATION

UNITED STATES

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA STATUS: All components of this product are either listed or exempt from listing in the TSCA inventory.

CANADA

DOMESTIC SUBSTANCE LIST (INVENTORY): All components of this product are listed on the Canadian DSL.

EUROPEAN COMMUNITY

EEC LABEL SYMBOL AND CLASSIFICATION




EEC Irritant - "Xi"

16. OTHER INFORMATION

APPROVED BY: Pierce A. Pillon **TITLE:** Chemist

REVISION SUMMARY New MSDS

NFPA CODES



DATA SOURCES: Code of Federal Regulations (CFR)
The Sigma-Aldrich Library of Regulatory and Safety Data
OSHA Hazard Communication Standard (29CFR1910.1200)
Various Federal, State and Local Regulations

MANUFACTURER DISCLAIMER: To the best of our knowledge, the information contained herein is accurate. However, neither Stratus, or any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.