

4K CMOS Static RAM (65536×1) 22PIN 6287

型名	社名	温度範囲 (°C)	スイッチング特性										電 源				入力 [+typ]				出力 [+typ]			備 考
			TAAC max (ns)	TCAC max (ns)	T _{OE} max (ns)	T _{OH} min (ns)	T _{OD} max (ns)	T _{WP} min (ns)	T _{DS} min (ns)	T _{DH} min (ns)	T _{WD} min (ns)	T _{WR} max (ns)	VDD or VCC (V)	I _{DD} max (mA)	I _{ID} STANDBY (I _{SB} /I _{SB2}) (mA)	V _{IL} max (V)	V _{IH} min (V)	C _i max (pF)	V _{OL} /I _{VOL} max (V/mA)	V _{OH} /I _{VOH} min (V/mA)	C _o max (pF)			
P4C187L-10	PFM	0~70	10	10		0	5	3	7	0	0	0	4.5~5.5			35/0.2	0.8	2.2	5*	0.4/8	2.4/4	7*		
P4C187L-12	PFM	0~70	12	12		0	6	10	7	0	0	0	4.5~5.5	120		35/-	0.8	2.2	5	0.4/8	2.4/4	7		
P4C187L-15	PFM	0~70	15	15		1	8	12	10	0	0	0	4.5~5.5	120		35/-	0.8	2.2	5	0.4/8	2.4/4	7		
P4C187L-20	PFM	0~70	20	20		2	10	15	13	0	0	0	4.5~5.5	120		35/-	0.8	2.2	5	0.4/8	2.4/4	7		
P4C187L-25	PFM	0~70	25	25		2	12	20	15	0	0	0	4.5~5.5	120		35/-	0.8	2.2	5	0.4/8	2.4/4	7		
P4C187L-30	PFM	0~70	30	30		3	15	20	18	0	0	0	4.5~5.5	120		35/-	0.8	2.2	5	0.4/8	2.4/4	7		
P4C187L-35	PFM	0~70	35	35		3	17	25	20	0	0	0	4.5~5.5	120		35/-	0.8	2.2	5	0.4/8	2.4/4	7		
SR64K1-35	LATTICE	0~70	35	35		5	20	20	15	0	0	0	4.5~5.5	110		20/-	0.8	2.0	5	0.4/8	2.4/4	7		
SR64K1-45	LATTICE	0~70	45	45		5	20	25	20	0	0	0	4.5~5.5	110		20/-	0.8	2.0	5	0.4/8	2.4/4	7		
SR64K1-55	LATTICE	0~70	55	55		5	25	25	20	0	0	0	4.5~5.5	110		20/-	0.8	2.0	5	0.4/8	2.4/4	7		
TC5561P-45	TOSHIBA		45										5											
TC5561P-55	TOSHIBA		55										5											
TC5561P/J-45	TOSHIBA	0~70	45	45		5		30	25	0	0	0	4.5~5.5	100		2/0.1	0.8	2.2	10	0.4/8	2.4/8	10		
TC5561P/J-55	TOSHIBA	0~70	55	55		5		35	25	0	0	0	4.5~5.5	100		2/0.1	0.8	2.2	10	0.4/8	2.4/8	10		
TC5561P/J-70	TOSHIBA	0~70	70	70		5		35	30	0	0	0	4.5~5.5	100		2/0.1	0.8	2.2	10	0.4/8	2.4/8	10		
TC5562P/J-35	TOSHIBA	0~70	35	35		5		25	20	0	0	0	4.5~5.5	100		20/2	0.8	2.2	10	0.4/8	2.4/8	10		
TC5562P/J-45	TOSHIBA	0~70	45	45		5		30	25	0	0	0	4.5~5.5	100		20/2	0.8	2.2	10	0.4/8	2.4/8	10		
TMS6287-45	TI	0~70	45			5	30	25	25	0	0	0	4.5~5.5	100		30/2.0	0.8	2.2	5	0.4/8	2.4/4	7.5		
TMS6787-25	TI	0~70	25			5	15	20	20	0	0	5	4.5~5.5	100		40/2	0.8	2.2	5	0.5/16	2.4/4	7		
TMS6787-30	TI	0~70	30			5	15	25	25	0	0	5	4.5~5.5	100		40/2	0.8	2.2	5	0.5/16	2.4/4	7		
wPD4361BCR/LA-12	NEC	0~70	12	12		2	7	10	7	0	0	0	4.5~5.5	130		20/2	0.8	2.2	6	0.4/8	2.4/4.0	8		
wPD4361BCR/LA-15	NEC	0~70	15	15		3	7	12	7	0	0	0	4.5~5.5	120		20/2	0.8	2.2	6	0.4/8	2.4/4.0	8		
wPD4361BCR/LA-20	NEC	0~70	20	20		3	8	14	8	0	0	0	4.5~5.5	110		20/2	0.8	2.2	6	0.4/8	2.4/4.0	8		
wPD4361C-45	NEC	0~70	45	40		5	25	25	25	0	0	0	4.5~5.5	120		20/2	0.8	2.2	5	0.4/8	2.4/4	7		
wPD4361C-55	NEC	0~70	55	55		5	30	30	25	0	0	0	4.5~5.5	120		20/2	0.8	2.2	5	0.4/8	2.4/4	7		
wPD4361C-70	NEC	0~70	70	70		5	30	40	30	0	0	0	4.5~5.5	120		20/2	0.8	2.2	5	0.4/8	2.4/4	7		
wPD4361G-45	NEC	0~70	45	45			25	25	25	0	0	0	4.5~5.5	120		20/1	0.8	2.2	5	0.4/8	2.4/4	7		
wPD4361G-45L	NEC	0~70	45	45			25	25	25	0	0	0	4.5~5.5	120		20/0.05	0.8	2.2	5	0.4/8	2.4/4	7		
wPD4361G-55	NEC	0~70	55	55			30	30	25	0	0	0	4.5~5.5	120		20/1	0.8	2.2	5	0.4/8	2.4/4	7		
wPD4361G-55L	NEC	0~70	55	55			30	30	25	0	0	0	4.5~5.5	120		20/0.05	0.8	2.2	5	0.4/8	2.4/4	7		
wPD4361G-70	NEC	0~70	70	70			30	40	30	0	0	0	4.5~5.5	120		20/1	0.8	2.2	5	0.4/8	2.4/4	7		
wPD4361G-70L	NEC	0~70	70	70			30	40	30	0	0	0	4.5~5.5	120		20/0.05	0.8	2.2	5	0.4/8	2.4/4	7		
wPD4361K-40	NEC	-10~85	40	40		5	22	23	23	0	0	0	4.5~5.5	120		20/2	0.8	2.2	5	0.4/8	2.4/4	7		
wPD4361K-45	NEC	-10~85	45	45		5	25	25	25	0	0	0	4.5~5.5	120		20/2	0.8	2.2	5	0.4/8	2.4/4	7		
wPD4361K-55	NEC	-10~85	55	55		5	30	30	25	0	0	0	4.5~5.5	120		20/2	0.8	2.2	5	0.4/8	2.4/4	7		