



REV.	CHANGE CONTENT	BY	DATE

NOTE:

1. DISPLAY TYPE: STN-Y/G-POSITIVE
2. DISPLAY MODE: TRANSMISSIVE
3. DRIVE METHOD: 1/16 DUTY, 1/5 BIAS, 4.6V Vop
4. VIEWING DIR.: 6:00
5. OP. TEMP.: 0°C~50°C
6. ST. TEMP.: -20°C~60°C
7. CONTROLLER: S6A0069X01-C0CX
8. BACKLIGHT: LED Y/G 5.0V

PIN NO.	SYMBOL	Vss	Vdd	Vo	RS	R/W	E	DB0~DB7	LED+	LED-
1										
2										
3										
4										
5										
6										
7~14										
15										
16										

TOLERANCE		DESTGN		LI JINTANG		TECHNOLOGY		DRAWING No. :		SCALE : 1:1	
>0~6	±0.10										
>6~80	±0.20										
>80~240	±0.30										
>240~400	±0.50										
// 1.0	±0.10										

HTDISPLAY CO., LTD.

DRAWING No. : HC200402C-YT60L-VA
 DRAWING TITLE: LCM DRAWING
 FILE NO: 8

REV. : A
 PROJECTION:
 SCALE : 1:1
 UNIT : mm
 SHEET : 1/2