


[English](#) [日本語](#)
**Electronics**
*a vital part of your world*

 Find  
Answers:

Thursday, 25 August, 2005

**CATALOG**

- [Cross Reference](#)
- [Competitive Products](#)
- [Military Spec P/Ns](#)
- [Tyco Brand P/Ns](#)

- [Part Number Search](#)
- [Document Search](#)
- [Product Type Search](#)
- [Product Family Search](#)
- [Alphabetical Search](#)
- [RoHS/ELV Compliance & Alternates](#)
- [CAD Model Search](#)
- [Brand Search](#)
- [Tool Search](#)
- [Multiple Part Comparison](#)
- [Lead Free Solutions](#)
- [Help/Glossary](#)

[Home](#)

 e-bulletin newsletter  
**SUBSCRIBE NOW!**  
 click here

**Sockets**
**↳ DIP Sockets**
**AMP 528-AG10D**  [Active](#)
**Directive 2002/95/EC  
Compliant**
[RoHS Compliant](#)
**(Corporate P/N: 5-1437536-2)**
[Search for Parts](#)

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

**Related Part Information**

General Information	eCommerce	Related Part Information
<ul style="list-style-type: none"> <li>➤ <a href="#">General Info</a></li> <li>➤ <a href="#">Sales Info</a></li> <li>➤ <a href="#">Assembly Subcontractors</a></li> </ul>	<ul style="list-style-type: none"> <li>➤ <a href="#">Pricing</a></li> <li>➤ <a href="#">Product Availability</a></li> </ul>	<ul style="list-style-type: none"> <li>➤ <a href="#">Tooling</a></li> </ul>

**Photos & Line Drawings** - The photographs and/or line drawings are representative images of a product for viewing purposes only.

[Product Photo](#)
**Searchable Features:**

<b>Brand:</b>	AMP
<b>RoHS/ELV Compliance:</b>	RoHS compliant, ELV compliant
<b>Lead Free Solder Processes:</b>	Wave solder capable to 240°C, Wave solder capable to 265°C
<b>Product Type:</b>	DIP Socket
<b>Number of Positions:</b>	28
<b>Row-to-Row Spacing (mm [in]):</b>	15.24 [0.600]
<b>Contact Mount:</b>	Thru Hole
<b>Mount Style:</b>	Vertical

**Other Properties:**

<b>RoHS/ELV Compliance History:</b>	Always was RoHS compliant
<b>Insulation Resistance (M ):</b>	5,000
<b>Contact Resistance (m ):</b>	10
<b>Sleeve Material:</b>	Brass/Copper
<b>Contact Termination Area Plating:</b>	Gold
<b>Product Series:</b>	500 Series

<b>Centerline (mm [in]):</b>	2.54 [0.100]
<b>Profile:</b>	Standard
<b>Frame Style:</b>	Closed
<b>Leg Style:</b>	Straight
<b>Contact Material:</b>	Beryllium Copper
<b>Contact Mating Area Plating:</b>	Gold (25)
<b>Contact Style:</b>	Screw Machine
<b>Mating Contact Type:</b>	Four-Fingered
<b>Height Above PC Board (mm [in]):</b>	4.57 [0.180]
<b>Temperature Range (° C):</b>	125
<b>Packaging Method:</b>	Tube
<b>Termination Post Length (mm [in]):</b>	3.18 [0.125]

[Copyright and Privacy Statement](#)  
Visit [Tyco International Ltd.](#)

[ [Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#) ]