



- NOTE:
1. DISPLAY TYPE: STN-Y/G-POSITIVE-TRANSFLECTIVE
 2. DRIVE METHOD: 1/32 DUTY, 1/5 BIAS, 6.0V Vop(typ.), 3.3V VDD
 3. VIEWING DIR.: 6:00
 4. OP. TEMP.: $-20^{\circ}C \sim 70^{\circ}C$
 5. ST. TEMP.: $-40^{\circ}C \sim 80^{\circ}C$
 7. BACKLIGHT: LED(Y/G), Vf=5.0V, If<150mA 500CD/m²

Wavelength 570±2.5nm

8. DRIVER IC: NUU6450(OR EQUAL)
9. 提供和FCO配套使用的下接触的18PIN插座一个

TOLERANCE	
>0~6	±0.10
>6~80	±0.20
>80~240	±0.30
>240~400	±0.50
// L ⊙	±0.10



HTDISPLAY CO., LTD.

DRAWING No. : HG1233206C-YF62L-VC
 DRAWING TITLE: LCD MODULE
 FILE NO.: 8

DESIGN	LI JINTANG	06.06.23	STANDARD	REV. : A	SCALE : -
CHECKED			TECHNOLOGY	PROJECTION:	UNIT : MM
APPROVED			Q.A		SHEET : 1/2

REV.	CHANGE CONTENT	BY	DATE
B	增加泡棉、更改电极焊位置及接口	LJT	05.08.19