

MCS2400X
MCS2400,MCS2



**PHOTON COUPLED ISOLATOR Ga As
INFRARED EMITTING DIODE &
LIGHT ACTIVATED SCR**

APPROVALS

- UL recognised, File No. E91231

'X' SPECIFICATION APPROVALS

- VDE 0884 in 2 available lead forms : -
 - STD
 - G form

DESCRIPTION

The MCS2, MCS2400 are optically coupled isolators consisting of infrared light emitting diode and a light activated silicon controlled rectifier in a standard 6pin dual in line plastic package.


FEATURES

- Options :-
10mm lead spread - add G after part no.
Surface mount - add SM after part no.
Tape&reel - add SMT&R after part no.
- High Isolation Voltage ($5.3\text{kV}_{\text{RMS}}, 7.5\text{kV}_{\text{PK}}$)
- High Surge Anode Current (5.0 A)
- High Blocking Voltage (200V*¹, 400V*¹)
- Low Turn on Current (5mA typical)
- All electrical parameters 100% tested
- Custom electrical selections available




APPLICATIONS

- 10A, T²L compatible, Solid State Relay
- 25W Logic Indicator Lamp Driver
- 400V Symmetrical transistor coupler

**OPTION SM
SURFACE MOUNT**



OPTION G



**ABSOLUTE MAXIMUM RATINGS
(25°C unless otherwise specified)**

Storage Temperature	-55°C to + 150°C
Operating Temperature	-55°C to + 100°C
Lead Soldering Temperature (1/16 inch (1.6mm) from case for 10 secs)	260°C

INPUT DIODE

Forward Current	60mA
Forward Current (Peak) (1μs pulse, 300pps)	3A
Reverse Voltage	6V
Power Dissipation	100mW

DETECTOR

Peak Forward Voltage MCS2	200V* ¹
MCS2400	400V* ¹
Peak Reverse Gate Voltage	6V
RMS On-state Current	300mA
Peak On-state Current (100μs, 1% duty cycle)	10A
Surge Current (10ms)	5A
Power Dissipation	300mW

*1 IMPORTANT : A resistor must be connected between gate and cathode (pins 4 & 6) to prevent false firing ($R_{\text{GK}} < 56\text{k}\Omega$)

ISOCOM COMPONENTS LTD

Unit 25B, Park View Road West,
Park View Industrial Estate, Brenda Road
Hartlepool, Cleveland, TS25 1YD
Tel: (01429) 863609 Fax :(01429) 863581

ISOCOM INC

1024 S. Greenville Ave, Suite 240,
Allen, TX 75002 USA
Tel: (214)495-0755 Fax: (214)495-0901
e-mail info@isocom.com
http://www.isocom.com

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ Unless otherwise noted)

PARAMETER		MIN	TYP	MAX	UNITS	TEST CONDITION
Input	Forward Voltage (V_F) Reverse Voltage (V_R)	3	1.2	1.5	V V	$I_F = 20\text{mA}$ $I_R = 10\mu\text{A}$
Output (note 2)	Peak Off-state Voltage (V_{DM}) MCS2	200			V	$R_{GK}=10\text{k}\Omega, I_D=150\mu\text{A},$ $T_A=100^\circ\text{C}$
	MCS2400	400			V	$R_{GK}=10\text{k}\Omega, I_D=150\mu\text{A},$ $T_A=100^\circ\text{C}$
	Peak Reverse Voltage (V_{RM}) MCS2	200			V	$I_D=150\mu\text{A}, T_A=100^\circ\text{C}$
	MCS2400	400			V	$I_D=150\mu\text{A}, T_A=100^\circ\text{C}$
	On-state Voltage (V_{TM}) Off-state Current (I_{DM}) MCS2		1.1	1.3	V μA	$I_{TM} = 100\text{mA}$ $R_{GK}=27\text{k}\Omega, I_F = 0,$ $V_{DM} = 200\text{V}$
	MCS2400			2	μA	$R_{GK}=27\text{k}\Omega, I_F = 0,$ $V_{DM} = 400\text{V}$
	Reverse Current (I_R) MCS2			2	μA	$I_F = 0, V_{DM} = 200\text{V}$
	MCS2400			2	μA	$I_F = 0, V_{DM} = 400\text{V}$
	Holding Current (I_H)	10		500	μA	$R_{GK}=27\text{k}\Omega, V_{FX}=50\text{V}$
Coupled	Input Current to Trigger (I_{FT}) (note 2)	0.5		14	mA	$V_{AK}=100\text{V}, R_{GK}=27\text{k}\Omega$
	Turn on Time (t_{on})			50	μs	$R_{GK}=10\text{k}\Omega, I_F=30\text{mA},$ $V_{AK}=50\text{V}, R_L=200\Omega$
	Coupled dv/dt, Input to Output (dv/dt) Input to Output Isolation Voltage V_{ISO}	500 5300 7500			V/ μs V_{RMS} V_{PK}	See note 1 See note 1
	Input-output Isolation Resistance R_{ISO} Input-output Capacitance C_f	10^{11}		2	Ω pF	$V_{IO} = 500\text{V}$ (note 1) $V = 0, f = 1\text{MHz}$

Note 1 Measured with input leads shorted together and output leads shorted together.

Note 2 Special Selections are available on request. Please consult the factory.

