

| 0385 | 4001 | 1782 | 5960 |
|---|---|---|--|
| | | | |
| 0385-0-15-XX-43-XX-10-0 Press-fit in .046 mounting hole | 4001-0-15-XX-43-XX-04-0 Press-fit in .057 mounting hole | 1782-0-15-XX-43-XX-04-0 Press-fit in .045 mounting hole | 5960-0-15-XX-43-XX-04-0 Hex press-fit in .057 plated thru hole |

| 1401/3185 | 4310 | 1385 |
|---|--|---|
| | | |
| XXXX-0-15-XX-30-XX-10-0 Solder mount in .055 min. mounting hole | 4310-0-31-XX-43-XX-04-0 Compliant press-fit in .040±.003 plated hole. For .090→.130 thick board. | 1385-0-15-XX-43-XX-10-0 Surface mount |

| Basic Part Number | Depth N | Length L |
|-------------------|---------|----------|
| 1401-0 | .145 | .165 |
| 3185-0 | .109 | .130 |

| 3018 | 3907 | 8852 | 8363 |
|---|---|---|---|
| | | | |
| 3018-0-15-XX-30-XX-04-0 Press-fit in .057 mounting hole | 3907-0-18-XX-30-XX-10-0 Surface mount Also available on 12mm wide carrier tape: 4,000 parts per 13" reel. Order as: 3907-0-58-XX-30-XX-10-0 | 8852-0-15-XX-30-XX-04-0 Press-fit in .056 mounting hole | 8363-0-15-XX-35-XX-10-0 Solder mount in .057 min. mounting hole |

| | |
|---|--|
| <p>SPECIFICATIONS</p> <p>SHELL MATERIAL: Brass Alloy 360, 1/2 Hard</p> <p>CONTACT MATERIAL: Beryllium Copper Alloy 172, HT</p> <p>DIMENSION IN INCHES TOLERANCES ON: LENGTHS: ±.005 DIAMETERS: ±.002 ANGLES: ± 2°</p> | <p>ORDER CODE: XXXX - X - XX - XX - XX - XX - XX - 0</p> <p>BASIC PART # →</p> <p>SPECIFY SHELL FINISH:</p> <p>01 200µ" TIN/LEAD OVER NICKEL</p> <p>80 200µ" TIN OVER NICKEL ◊</p> <p>15 10µ" GOLD OVER NICKEL ◊</p> <p>SPECIFY CONTACT FINISH:</p> <p>02 100µ" TIN/LEAD OVER NICKEL</p> <p>84 100µ" TIN OVER NICKEL ◊</p> <p>27 30µ" GOLD OVER NICKEL ◊</p> <p>SELECT CONTACT</p> <p>#30, #35 or #43 CONTACT (DATA ON PAGE 218, 219 & 220)</p> |
|---|--|

