







Contact and Welding Tab Terminals (Continued)

Brush Contacts

Contact and Welding Tab Terminals



Type	Wire Range		Insul. Dia.	Stock Thickness	Dimensions			Tab Direction	Material	Part Number	
	AWG	mm ²			W	L	E				
A	22-17 Magnet Wire	0.3-1.0 Magnet Wire	—	.020 0.51	.215	.425	.425	L.H.	Phosphor Bronze	62214-1	
					5.46	10.80	10.80	R.H.	Phosphor Bronze	62214-2	
	18-14	0.8-2.0	—	.020 0.51	.187	.435	.640	R.H.	Phosphor Bronze	60812-1	
					4.75	11.05	16.25	L.H.	Phosphor Bronze	60812-2	
B	20-14	0.5-2.0	—	.018 0.46	.187	.620	.425	R.H.	Phosphor Bronze	62008-11	
						15.75	10.80	R.H.	Silver Plated Ph Bz	62008-21	
					4.75	.495	.300	L.H.	Phosphor Bronze	62009-11	
						12.57	7.62	L.H.	Silver Plated Ph Bz	62009-21	
C	20-18	0.5-0.8	—	.012 0.30	.125	.330	.305	R.H.	Phosphor Bronze	63182-11	
					3.18	8.38	7.75	L.H.	Phosphor Bronze	63183-11	
D	20-16	0.5-1.4	—	.018 0.46	.240	.275	.240	L.H.	Phosphor Bronze	1217698-1	
					6.10	6.98	6.10	R.H.	Phosphor Bronze	1217698-2	
					.018 0.46	.285	.210	—	—	Brass	61524-22
						7.24	5.33	—	—	Brass	61933-12
E	24-20	0.2-0.6	—	.016 0.41	.312	.185	—	—	Brass	63020-12	
					7.29	4.70	—	—	Brass	63020-12	
					.018 0.46	.285	.210	—	—	Brass	1217507-12
						7.24	5.33	—	—	Brass	1217507-12
F	18-14	0.8-2.0	—	.016 0.41	.360	.185	—	—	Brass	63930-12	
					9.14	4.70	—	—	Brass	63930-12	
F	18-14	0.8-2.0	.110-.160 2.79-4.06	.016 0.41	.255	.775	.355	—	Brass	61390-1	
					6.48	19.69	9.02	—	Brass	61390-1	

¹ Tab lock crimp.

² Carbon brush application equipment available.