

Compare Products















[English](#) |
 [Español](#) |
 [Français](#) |
 [Italiano](#) |
 [Deutsch](#) |
 [Português](#) |
 [Polski](#) |
 [한국어](#) |
 [日本語](#) |
 [한국어](#)

Compare Products
IDT and Solder Connectors


[Home](#) > [Products](#) > [IDT and Solder Connectors](#) > Compare Products

[Help](#)


14 Matching Products

														
	2.5 SPOX IDT RECEPTACLE WHITE 10CKT	2.5 SPOX IDT RECEPTACLE WHITE 11CKT	2.5 SPOX IDT RECEPTACLE WHITE 12CKT	2.5 SPOX IDT RECEPTACLE WHITE 13CKT	2.5 SPOX IDT RECEPTACLE WHITE 14CKT	2.5 SPOX IDT RECEPTACLE WHITE 15CKT	2.5 SPOX IDT RECEPTACLE WHITE 3CKT	2.5 SPOX IDT RECEPTACLE WHITE 3CKT	2.5 SPOX IDT RECEPTACLE WHITE 4CKT	2.5 SPOX IDT RECEPTACLE WHITE 5CKT	2.5 SPOX IDT RECEPTACLE WHITE 6CKT	2.5 SPOX IDT RECEPTACLE WHITE 7CKT	2.5 SPOX IDT RECEPTACLE WHITE 8CKT	2.5 SPOX IDT RECEPTACLE WHITE 9CKT
Circuits/Positions	10	11	12	13	14	15	2	3	4	5	6	7	8	9
RoHS Compliant	No	No	-	-	-	-	No	No	No	No	No	No	No	No
Date to be RoHS Compliant	2005-01	2005-01	-	-	-	-	2005-01	2005-01	2005-01	2005-01	2005-01	2005-01	2005-01	2005-01
Dimension A	27.00mm (1.079")	29.00mm (1.137")	32.00mm (1.259")	34.00mm (1.339")	37.00mm (1.457")	39.00mm (1.535")	7.00mm (0.276")	9.00mm (0.354")	12.00mm (0.472")	14.00mm (0.551")	17.00mm (0.669")	19.00mm (0.748")	22.00mm (0.867")	24.00mm (0.945")
Dimension B	22.00mm (0.867")	23.00mm (0.909")	27.00mm (1.063")	30.00mm (1.181")	32.00mm (1.260")	35.00mm (1.378")	2.50mm (0.099")	3.00mm (0.118")	7.00mm (0.276")	10.00mm (0.394")	12.00mm (0.472")	15.00mm (0.591")	17.00mm (0.669")	20.00mm (0.787")
Old Part Number	A-42219-00A	A-42219-11A	A-42219-12A	A-42219-13A	A-42219-14A	A-42219-15A	A-42219-02A	A-42219-03A	A-42219-04A	A-42219-05A	A-42219-06A	A-42219-07A	A-42219-08A	A-42219-09A
Common Features														
Status	Active													
Pitch/Center Spacing	2.50mm (0.099")													
Termination Method	Immersion Dip Solder (IDS)													
Wire Size (AWG)	24, 26													
Wire Entry Angle	Right Angle													
Gender	Female													
Packaging	Tape													
Housing Material	Polymer													
Color	Natural													
Flammability	UL 94V-0													
Contact	Phosphor Bronze (Cu50)													
Plating Contact	Tin Lead (Sn/Pb)													
Durability (mating cycles) min.	25 cycles													
Temperature Range	0°C to +75°C													
Current-max (amps)	3.0A													
Voltage-max (volts)	250V													
Withstanding Voltage	1000V AC													
Contact Resistance (ohms)	20 milliohms max.													
Insulation Resistance (ohms)	1000 Megohms min.													
Panel Mount	No													
Product Specification	PS-42219													
UL File Number	E20179													
CSA File No.	L819980													
Stackable	No													
Product Name	SPOX™													
Unmated Height	10.41mm (0.409")													
Designed In	Molded													
Mates With	4220, 4220T, 520T, 520B, Headers													
Comment	Spring Rate, 11oz with 24 AWG solder													
MS001 Catalog Page	B-001													
990 Catalog Page	J-4													
MoLEX Series	42219													
	2.5 SPOX IDT RECEPTACLE WHITE 10CKT	2.5 SPOX IDT RECEPTACLE WHITE 11CKT	2.5 SPOX IDT RECEPTACLE WHITE 12CKT	2.5 SPOX IDT RECEPTACLE WHITE 13CKT	2.5 SPOX IDT RECEPTACLE WHITE 14CKT	2.5 SPOX IDT RECEPTACLE WHITE 15CKT	2.5 SPOX IDT RECEPTACLE WHITE 3CKT	2.5 SPOX IDT RECEPTACLE WHITE 3CKT	2.5 SPOX IDT RECEPTACLE WHITE 4CKT	2.5 SPOX IDT RECEPTACLE WHITE 5CKT	2.5 SPOX IDT RECEPTACLE WHITE 6CKT	2.5 SPOX IDT RECEPTACLE WHITE 7CKT	2.5 SPOX IDT RECEPTACLE WHITE 8CKT	2.5 SPOX IDT RECEPTACLE WHITE 9CKT


Compare Products




22-43-3100




22-43-3110




22-43-3120




22-43-3130




22-43-3140




22-43-3150




22-43-3020




22-43-3030




22-43-3040




22-43-3050




22-43-3060



22-43-3070



22-43-3080



22-43-3090

© Copyright 2004 Molex Incorporated