

WN 10B (10 WATTS WALL MOUNT AC ADAPTER)

Features

- Two pin wall mount input receptacle
- Wide range AC input
- Level B EMI filter
- Fully enclosed plastic case
- Fully regulated output
- High efficiency
- High Quality



Electrical specifications

Input

- Voltage..... 90-264VAC (wide range)
- Current..... 1.0Arms Max.
- Frequency..... 47-63Hz

Output

- Voltage (Vo) (see table)
- Tolerance 5%
- Power (Po) 10W Max.
- Hold up time 12ms min. at full load, 230VAC
- OVP..... Build-in
- Overcurrent protection 150% of full load
- Short circuit protection Pulsing mode, auto recovery
- Efficiency 70% typ. at full load and 230VAC
- Ripple/Noise(Vp-p) 1% (20MHz bandwidth)

Environmental

Operating temperature

0 deg. C to +40 deg. C ambient

Storage temperature

-20 deg. C to +80 deg. C ambient

EMI

Meet FCC class B, VCCI class B, CISPR 22 class


Safety

- TUV: EN 60950
- IEC: 950
- CE:



Output Electronic Specifications

Model No.	Po	Vo	Io max
WN10B-050	10W	5.0V	2.0A
WN10B-060	10W	6.0V	1.66A
WN10B-075	10W	7.5V	1.33A
WN10B-090	10W	9.0V	1.11A
WN10B-120	10W	12.0V	0.83A



Power Systems – The Power Solution

Web: www.Power-Systems.de
 Email: Info@Power-Systems.de

Address: Dörnet 8 ; 74360 Ilfeld-Auenstein / Germany
 Tel. : + 49 / 70 62 / 67 59 - 6
 Fax: + 49 / 70 62 / 67 59 - 80