

1 Transistors

Applications	Type No		Electrical Characteristics (Ta = 25°C)										Package								
			Maximum Ratings			h _{FE}			V _{CE(sat)} MAX		f _T (TYP) MIN				NF (TYP) MAX						
	NPN	PNP	V _{CEO} (V)	I _C (mA)	P _C (mW)	V _{CE} (V)	I _C (mA)	h _{FE}	V _{CE} (V)	I _C (mA)	I _B (mA)	V _{CE} (V)	I _C (mA)	f (KHz)	R _g (KΩ)	Fig					
	2SC3875S	2SA1504S	50	150	150	6	2	70~700	0.25	100	10	80	1	10	6	0.1	1	10	SOT-23	F1	
	2SC3201	2SA1269	120	100	200	6	2	200~700	0.3	10	1	(100)	6	1	10	6	0.1	1	10	TO-92M	F5
	2SC3199	2SA1267	50	150	200	6	2	70~700	0.25	100	10	80	1	10	6	0.1	1	10	TO-92M	F5	
	2SC3198A	—	40	150	300	6	2	70~700	0.2	100	3	(250)	10	10	6	0.1	1	10	TO-92(C)	F3	
	2SC3198	2SA1266	50	150	400	6	2	70~700	0.25	100	10	80	*-1	10	6	0.1	1	10	TO-92(C)	F3	
	KTC100	—	25	50	250	6	2	70~700	0.5	10	1	50	*-1	-	-	-	-	-	TO-92(C)	F3	
	KTC9014	KTC9015	50	150	625	5	1	60~1000	0.25	100	10	60	*-1	10	6	0.1	1	10	TO-92(B)	F3	
General Purpose	BCW31	BCW29	20	100	200	5	2	110~220	0.25	10	0.5	(300)	5	10	5	0.2	1	10	2	SOT-23	F1
	BCW32	BCW30	20	100	200	5	2	200~450	0.25	10	0.5	(300)	5	10	5	0.2	1	10	2	SOT-23	F1
	BCW33	—	20	100	200	5	2	420~800	0.25	10	0.5	(300)	5	10	5	0.2	1	10	2	SOT-23	F1
	BCW71	BCW69	45	100	200	5	2	110~220	0.25	10	0.5	(300)	5	10	5	0.2	1	10	2	SOT-23	F1
	BCW72	BCW70	45	100	200	5	2	200~450	0.25	10	0.5	(300)	5	10	5	0.2	1	10	2	SOT-23	F1
	BCW81	—	45	100	200	5	2	420~800	0.25	10	0.5	(300)	5	10	5	0.2	1	10	2	SOT-23	F1
	BCV71	BCW89	60	100	200	5	2	110~220	0.25	10	0.5	(300)	5	10	5	0.2	1	10	2	SOT-23	F1
	BCV72	—	60	100	200	5	2	200~450	0.25	10	0.5	(300)	5	10	5	0.2	1	10	2	SOT-23	F1
	BSS64	—	80	100	200	1	10	80(TYP)	0.15	4	0.4	60	10	4	-	-	-	-	-	SOT-23	F1
	—	BSS63	100	100	200	1	10	30(MIN)	0.25	25	2.5	50	5	25	-	-	-	-	-	SOT-23	F1
	BCX20	—	25	100	310	1	100	100~600	0.62	500	50	(200)	5	10	-	-	-	-	-	SOT-23	F1
	BC238	BC308	20	100	300	5	2	120~800	0.6	100	5	50	5	10	10	6	0.1	1	10	TO-92(B)	F3
	BC168	BC258	20	100	300	5	2	120~800	0.6	100	5	150	5	10	10	6	0.1	1	10	TO-92(C)	F3
	BC167	BC257	45	100	300	5	2	120~460	0.6	100	5	150	5	10	10	6	0.1	1	10	TO-92(C)	F3
	BC237	BC307	45	100	300	5	2	120~460	0.6	100	5	150	5	10	10	6	0.1	1	10	TO-92(B)	F3
Low Noise Amp	2SC3277S	2SA1506S	120	400	150	6	2	200~700	0.3	10	1	(100)	6	1	3	6	0.1	1	10	SOT-23	F1
	2SC3199L	2SA1267L	50	150	200	6	2	70~700	0.25	100	10	80	1	3	6	0.1	1	10	TO-92M	F5	
	2SC3200	2SA1268	120	100	300	6	2	200~700	0.3	10	1	(100)	6	1	2	6	0.1	1	10	TO-92(C)	F3

Applications	Type No		Electrical Characteristics (Ta = 25°C)										Package								
			Maximum Ratings			h _{FE}			MAX			(TYP) MIN			(TYP) MAX						
	NPN	PNP	V _{CE0}	I _C	P _C	h _{FE}	(MIN)		V _{CE(sat)}		f _T		V _{CE}		I _C	f	R _g	Fig			
			(V)	(mA)	(mW)		V _{CE}	I _C	I _B	(MHz)	(MHz)	(V)	I _C	(dB)					(mA)	(kHz)	(KΩ)
Low Noise Amp	2SC3198L	2SA1266L	50	150	400	70~700	6	2	0.3	10	1	80	6	*-1	3	6	0.1	1	10	TO-92(C)	F3
	—	BCF29	20	100	200	120~260	5	2	0.3	10	0.5	(150)	5	10	4	5	0.2	1	2	SOT-23	F1
	BCF32	BCF30	20	100	200	(160)	5	10μA	0.25	10	5	(300)	5	5	4	5	0.2	1	2	SOT-23	F1
	BCF33	—	20	100	200	(250)	5	10μA	0.25	10	5	(300)	5	5	4	5	0.2	1MHz	2	SOT-23	F1
	—	BCF70	45	100	200	200~460	5	2	0.3	10	0.5	(150)	5	10	4	5	0.2	1	2	SOT-23	F1
	BCF81	—	45	100	200	(250)	5	10μA	0.25	10	5	(300)	5	5	4	5	0.2	1MHz	2	SOT-23	F1
	BC169	BC259	20	50	300	180~800	5	2	0.2	10	0.5	150	5	10	3	6	0.1	1	10	TO-92(C)	F3
	BC239	BC309	20	50	300	180~800	5	2	0.2	10	0.5	150	5	10	3	6	0.1	1	10	TO-92(B)	F3
	BC549	BC559	30	100	625	110~800	5	2	0.6	100	5	(300)	5	10	4	5	0.2	1	10	TO-92(B)	F3
	BC550	BC560	45	100	625	110~800	5	2	0.6	100	5	(300)	5	10	-	-	-	-	-	TO-92(B)	F3

Applications	Type No		Electrical Characteristics (Ta = 25°C)										Package								
			Maximum Ratings			h _{FE}			MAX			TYP			Cob						
	NPN	PNP	V _{CE0}	I _C	P _C	h _{FE}	(MIN)		V _{CE(sat)}		f _T		V _{CE}		I _C	f	V _{CB}	Fig			
			(V)	(A)	(W)		V _{CE}	I _C	I _B	(MHz)	(MHz)	(V)	I _C	(pF)					(MHz)		
AF Drive and Output	2SC3876S	2SA1505S	30	0.5	0.15	70~240	1	100	0.25	100	10	300	6	20	(7)	6	1	6	1	SOT-23	F1
	2SC3204	2SA1272	30	0.8	0.3	100~320	1	100	0.5	500	20	120	5	10	(13)	10	1	10	1	TO-92M	F-5
	2SC3202	2SA1270	30	0.5	0.5	70~240	1	100	0.25	100	10	300	6	*-20	(7)	6	1	6	1	TO-92(C)	F3
	2SC4372	2SA1660	150	0.05	*0.8	70~240	5	10	0.5	10	1	120	30	10	5	10	1	5	10	SOT-89	F2
	2SC4374	2SA1662	80	0.4	*1	70~240	2	50	0.4	200	20	100	10	10	(10)	10	1	10	1	SOT-89	F2
	2SC4376	2SA1664	30	0.8	*1	100~320	1	100	0.5	500	20	120	5	10	(13)	10	1	10	1	SOT-89	F2
	2SC4373	2SA1661	120	0.8	*1	80~240	5	100	1.0	500	50	120	5	100	30	10	1	30	10	SOT-89	F2
	2SC4375	2SA1663	30	1.5	*1	100~320	2	500	2.0	1.5A	30	120	2	500	40	10	1	500	40	SOT-89	F2
	2SC3227	2SA1274	80	0.4	0.8	70~240	2	50	0.4	200	20	100	10	10	(10)	10	1	10	1	TO-92L	F-4
	2SC4370	2SA1659	160	1.5	*20	70~240	5	100	1.5	500	50	100	10	100	(25)	10	1	10	1	TO-220IS	F7

Pc* Tc=25°C Pc* mounted on ceramic substrate (250mm² × 0.81) *I_B

Applications	Type No		Electrical Characteristics (Ta = 25°C)										Package				
			Maximum Ratings					(TYP) MIN							(TYP) MAX		
	NPN	PNP	V _{CE} (V)	I _C (A)	P _C (W)	h _{FE}	V _{CE(sat)} (V)	I _C (mA)	I _B (mA)	f _T (MHz)	V _{CE} (V)	I _C (mA)	Cob (pF)	V _{CB} (V)	f _r (MHz)	Fig	
	2SC4370A	2SA1659A	180	1.5	*20	70~240	5	100	50	(100)	10	100	(25)	10	1	TO-220IS	F7
	2SD2060	2SB1368	80	4	*25	40~240	5	0.5A	0.3A	(8.0)	5	0.5A	(90)	10	1	TO-220IS	F7
	2SD2059	2SB1367	100	5	*30	40~240	5	1A	0.4A	(12)	5	1A	(100)	10	1	TO-220IS	F7
	2SD1352	2SB989	80	4	*30	40~240	5	0.5A	0.3A	(8.0)	5	0.5A	(90)	10	1	TO-220AB	F6
	KTC200	KTA200	50	0.5	0.6	70~240	2	50	10	(300)	6	*-20	(7)	6	1	TO-92(C)	F3
	KTC2235	KTA965	120	0.8	0.9	80~240	5	100	50	(120)	5	100	30	10	1	TO-92L	F4
	KTC2238	KTA968	160	1.5	*25	70~240	5	100	50	(100)	10	100	(25)	10	1	TO-220AB	F6
	KTC2238A	KTA968A	180	1.5	*25	70~240	5	100	50	(100)	10	100	(25)	10	1	TO-220AB	F6
	KTD525	KTBS95	100	5	*40	40~240	5	1A	0.4A	(12)	5	1A	(100)	10	1	TO-220AB	F6
	KTD718	KTBS68	120	8	*80	55~160	5	1A	0.5A	(12)	5	1A	(170)	10	1	TO-3P(1)	F9
	KTC9013	KTC9012	30	0.5	0.625	64~246	1	50	20	140	6	*-20	(7)	6	1	TO-92(B)	F3
	KN4400	KN4402	40	0.6	0.31	50~150	1	50	50	(200)	10	*-20	(7)	10	1	TO-92(B)	F3
	KN4401	KN4403	40	0.6	0.31	100~300	1	150	50	(200)	10	*-20	(7)	10	1	TO-92(B)	F3
	BCX19	—	45	0.5	0.31	100~600	1	100	50	(200)	5	10	(6)	10	1	SOT-23	F1
	—	BCW67	32	0.8	0.36	100~630	1	100	10	100	10	80	18	10	1	SOT-23	F1
	—	BCW68	45	0.8	0.36	100~630	1	100	50	100	10	80	18	10	1	SOT-23	F1
	BC183	BC213	30	0.2	0.3	120~800	5	2	5	150	5	10	5	10	1	TO-92	F3
	BC184	BC214	30	0.2	0.3	250~800	5	2	0.5	150	5	10	5	10	1	TO-92	F3
	BC182	BC212	50	0.2	0.3	120~460	5	2	5	200	5	10	5	10	1	TO-92	F3
	BC548	BC558	30	0.1	0.5	75~800	5	2	5	(150)	5	10	4.5	10	1	TO-92(B)	F3
	BC547	BC557	45	0.1	0.5	75~450	5	2	5	(150)	5	10	4.5	10	1	TO-92(B)	F3
	BC546	BC556	65	0.1	0.5	75~450	5	2	5	(150)	5	10	4.5	10	1	TO-92(B)	F3
	BC338	BC328	25	0.8	0.625	100~400	1	100	50	(100)	5	10	(12)	10	1	TO-92(B)	F3
	BC337	BC327	45	0.8	0.625	100~400	1	100	50	(100)	5	10	(12)	10	1	TO-92(B)	F3

Pc*:Tc = 25°C

*:If