



FEATURES

- RoHS compliant
- Axial format
- Up to 5.35A Idc
- 4.7µH to 10mH
- Low DC resistance
- Compact size
- MIL-I-23053/5 class III sleeving
- Fully tinned leads
- Supplied in packs of 10
- Custom & radial parts available
- Backward compatible with Sn/Pb soldering systems

DESCRIPTION

The 1800 Series of inductors are particularly suited to use with a wide variety of switching regulators. Offering high current handling with a low mounting height, the devices are ideal where space is at a premium.

SELECTION GUIDE

Order Code	Inductance (1kHz, 0.1VAc)	DC Current ¹	DC Resistance	Q @ f kHz		SRF
	±10%	Max.	Max.	Nom.		Nom.
	µH	A	mΩ	Q	f	MHz
18472C	4.7	5.35	9.0	112	1000	36.4
18682C	6.8	4.15	12.0	78	500	23.6
18103C	10.0	3.45	15.0	64	500	19.0
18153C	15.0	3.00	18.0	55	500	15.9
18223C	22.0	2.42	25.0	59	500	11.8
18333C	33.0	2.00	40.0	48	500	11.5
18473C	47.0	1.65	55.0	55	500	8.5
18683C	68.0	1.35	70.0	31	100	6.6
18104C	100.0	1.20	100.0	40	100	7.4
18154C	150.0	1.10	165.0	47	100	4.4
18224C	220.0	0.90	230.0	46	100	3.5
18254C	250.0	0.80	255.0	50	100	3.7
18334C	330.0	0.73	335.0	58	100	3.0
18474C	470.0	0.60	465.0	56	100	2.2
18684C	680.0	0.53	630.0	55	100	2.0
18105C	1.0mH	0.44	1.0Ω	94	50	1.6
18155C	1.5mH	0.33	1.5Ω	107	50	1.3
18225C	2.2mH	0.30	2.2Ω	108	50	1.1
18335C	3.3mH	0.22	3.5Ω	143	50	0.8
18475C	4.7mH	0.20	4.6Ω	128	40	0.7
18685C	6.8mH	0.15	7.0Ω	144	40	0.6
18106C	10.0mH	0.13	12.0Ω	143	40	0.5

TYPICAL CORE/WIRE CHARACTERISTICS

Inductance Temperature Coefficient	Resistance Temperature Coefficient	Curie Temperature (T _c)	Saturation Flux (B _{SAT})
430ppm	4000ppm	190°C	325mT

ABSOLUTE MAXIMUM RATINGS

Operating free air temperature range	0°C to 70°C
Storage temperature range	-55°C to 125°C

SOLDERING INFORMATION²

Peak wave solder temperature	300°C for 10 seconds
Pin finish	Bright tin


All specifications typical at T_a=25°C

- 1 Maximum DC current occurs when either the inductance falls to 90% of its nominal value or when its temperature rise reaches 30°C, whichever is sooner.
- 2 For further information, please visit www.murata-ps.com/rohs



PACKAGE SPECIFICATIONS

MECHANICAL DIMENSIONS



Unless otherwise stated, all dimensions in mm (inches) ±0.25 (0.01).
 Package weight: 4.6g Typ.
 Package quantity: 10

Murata Power Solutions, Inc.
 11 Cabot Boulevard, Mansfield, MA 02048-1151 U.S.A.
 Tel: (508) 339-3000 (800) 233-2765 Fax: (508) 339-6356
www.murata-ps.com email: sales@murata-ps.com ISO 9001 REGISTERED

Murata Power Solutions, Inc. makes no representation that the use of its products in the circuits described herein, or the use of other technical information contained herein, will not infringe upon existing or future patent rights. The descriptions contained herein do not imply the granting of licenses to make, use, or sell equipment constructed in accordance therewith. Specifications are subject to change without notice.
 © 2008 Murata Power Solutions, Inc.

- USA:** Mansfield (MA), Tel: (800) 233 2765, email: sales@murata-ps.com
- Canada:** Toronto, Tel: (866) 740 1232, email: toronto@murata-ps.com
- UK:** Milton Keynes, Tel: +44 (0)1908 615232, email: mk@murata-ps.com
- France:** Montigny Le Bretonneux, Tel: +33 (0)1 34 60 01 01, email: france@murata-ps.com
- Germany:** München, Tel: +49 (0)89-544334-0, email: ped.munich@murata-ps.com
- Japan:** Tokyo, Tel: 3-3779-1031, email: sales_tokyo@murata-ps.com
 Osaka, Tel: 6-6354-2025, email: sales_osaka@murata-ps.com
Website: www.murata-ps.jp
- China:** Shanghai, Tel: +86 215 027 3678, email: shanghai@murata-ps.com
 Guangzhou, Tel: +86 208 221 8066, email: guangzhou@murata-ps.com