



微調電阻電位器總匯

T-6205

● 微調電阻

種類	規格	P/N	圈數	電阻值範圍	溫度係數	調整方式	P(w)	誤差度
		3006	15 圈	10Ω~2MΩ	±100ppm/°C	側調	.75W	±10%
		3296	25 圈	10Ω~5MΩ	±100ppm/°C	上調 側調	.5W	±10%
		3266	12 圈	10Ω~1MΩ	±100ppm/°C	上調 側調	.25W	±10%
		3386	單圈	10Ω~2MΩ	±100ppm/°C	側調	.5W	±10%
		3329	單圈	10Ω~1MΩ	±100ppm/°C	上調	.5W	±10%
		3323	單圈	20Ω~2MΩ	±100ppm/°C	上調 側調	.5W	±20%
		3306	單圈	100Ω~1MΩ	±200ppm/°C	上調	.3W	±25%

● 電位器

種類	規格	P/N	圈數	電阻值範圍	溫度係數	直徑	P(w)	誤差度			
		3590	10 圈	200Ω~100KΩ	±50ppm/°C	7/8"	2	± 5%			
		3540	10 圈	100Ω~100KΩ	±50ppm/°C	7/8"	2	± 5%			
		3851	3¾ 圈	1KΩ~2.5MΩ	±1000ppm/°C	3/4"	1	±20%			
		3852		50Ω~5MΩ	±150ppm/°C	3/4"	2	±10%			
	• 刻度盤'10轉 CT23/26 • 1 1/16", 1 1/4"			• 刻度盤'15轉 H506/507 • 直徑 7/8"			• 面板控制器 90 Series • 直徑 5/8"			• Model 6574 直徑2" • 適合伺服系統	

● 電阻排

4100R 系列	4300R 系列	4600X 系列
• 14, 16, 18, 20 pin DIP 包裝 • 10Ω~10Megohms • ±100ppm/°C • 適合自動插件機使用 • 有 Isolated, Bussed 及 Dual 三種形式	• 6, 8, 9, 10, 11 Pin SIP Low profile 包裝 • 10Ω~10 megohms • ±100ppm/°C • 適合自動插件機使用 • 有 Isolated, Bussed 及 Dual 三種形式	• 4~14 pin SIP low profile 包裝 • 10Ω~10 megohms • ±100 ppm/°C • 有 Isolated, Bussed 及 Dual 三種形式

● SMD元件

3304 SMD 元件	4800P SMD 元件	其他 SMD 元件
• 單圈, 4mm Square • 500~1 megohms • ±200 ppm/°C • Tape 包裝, 適合自動插件。	• 14, 16 pin, SOM 包裝 0.22" • 100Ω~1 megohms • ±100 ppm/°C • 有 Tape 及 Tube 二種包裝方式。	• 3269 12 圈 1/4" 10Ω~1 megohms • 3314 單圈 4mm 100~2 megohms • 4200P PCC 型排阻 • 4400P SOL 型排阻 • 4400J SOJ 型排阻