
HM628512 Series

524288-word × 8-bit High Speed CMOS Static RAM

HITACHI

ADE-203-236F (Z)

Rev. 6.0

Jun. 9, 1995

Description

The Hitachi HM628512 is a 4-Mbit static RAM organized 512-kword × 8-bit. It realizes higher density, higher performance and low power consumption by employing 0.5 μm Hi-CMOS process technology. The device, packaged in a 525-mil SOP (foot print pitch width) or 400-mil TSOP TYPE II or 600-mil plastic DIP, is available for high density mounting. LP-version is suitable for battery backup system.

Features

- High speed: Fast access time:
 - 55/65/70 ns (max)
- Low power
 - Standby: 10 μW (typ) (L/L-SL version)
 - Operation: 75 mW (typ) (f = 1 MHz)
- Single 5 V supply
- Completely static memory
 - No clock or timing strobe required
- Equal access and cycle times
- Common data input and output: Three state output
- Directly TTL compatible: All inputs and outputs
- Capability of battery backup operation (L/L-SL version)

HM628512 Series


Ordering Information

Type No.	Access Time	Package
HM628512P-5	55 ns	600-mil 32-pin plastic DIP (DP-32)
HM628512P-7	70 ns	
HM628512LP-5	55 ns	
HM628512LP-7A	65 ns	
HM628512LP-7	70 ns	
HM628512LP-5SL	55 ns	
HM628512LP-7SL	70 ns	
HM628512FP-5	55 ns	525-mil 32-pin plastic SOP (FP-32D)
HM628512FP-7	70 ns	
HM628512LFP-5	55 ns	
HM628512LFP-7A	65 ns	
HM628512LFP-7	70 ns	
HM628512LFP-5SL	55 ns	
HM628512LFP-7SL	70 ns	
HM628512LTT-5	55 ns	400-mil 32-pin plastic TSOP II (TTP-32D)
HM628512LTT-7A	65 ns	
HM628512LTT-7	70 ns	
HM628512LTT-5SL	55 ns	
HM628512LTT-7SL	70 ns	
HM628512LRR-5	55 ns	400-mil 32-pin plastic TSOP II reverse (TTP-32DR)
HM628512LRR-7A	65 ns	
HM628512LRR-7	70 ns	
HM628512LRR-5SL	55 ns	
HM628512LRR-7SL	70 ns	

HITACHI

2

Pin Arrangement




Pin Description

Pin name	Function
A0 – A18	Address
I/O0 – I/O7	Input/output
\overline{CS}	Chip select
\overline{OE}	Output enable
\overline{WE}	Write enable
V _{CC}	Power supply
V _{SS}	Ground

HM628512 Series

Block Diagram



HITACHI

Function Table

\overline{WE}	\overline{CS}	\overline{OE}	Mode	V_{CC} Current	Dout Pin	Ref. Cycle
X	H	X	Not selected	I_{SB}, I_{SB1}	High-Z	—
H	L	H	Output disable	I_{CC}	High-Z	—
H	L	L	Read	I_{CC}	Dout	Read cycle
L	L	H	Write	I_{CC}	Din	Write cycle (1)
L	L	L	Write	I_{CC}	Din	Write cycle (2)

Note: X: H or L

Absolute Maximum Ratings

Parameter	Symbol	Value	Unit
Voltage on any pin relative to V_{SS} ¹	V_T	-0.5 ² to +7.0	V
Power dissipation	P_T	1.0	W
Operating temperature	T_{opr}	0 to +70	°C
Storage temperature	T_{stg}	-55 to +125	°C
Storage temperature under bias	T_{bias}	-10 to +85	°C

Notes: 1. Relative to V_{SS} .

2. -3.0 V for pulse half-width \leq 30 ns

Recommended DC Operating Conditions ($T_a = 0$ to +70°C)

Parameter	Symbol	Min	Typ	Max	Unit
Supply voltage	V_{CC}	4.5	5.0	5.5	V
	V_{SS}	0	0	0	V
Input high (logic 1) voltage	V_{IH}	2.2	—	6.0	V
Input low (logic 0) voltage	V_{IL}	-0.3 ¹	—	0.8	V

Note: 1. -3.0 V for pulse half-width \leq 30 ns

HM628512 Series

DC Characteristics ($T_a = 0$ to $+70^\circ\text{C}$, $V_{CC} = 5\text{ V} \pm 10\%$, $V_{SS} = 0\text{ V}$)

Parameter	Symbol	Min	Typ ¹	Max	Unit	Test Conditions
Input leakage current	$ I_{Lil} $	—	—	1	μA	$V_{in} = V_{SS}$ to V_{CC}
Output leakage current	$ I_{Lo} $	—	—	1	μA	$\overline{CS} = V_{IH}$ or $\overline{OE} = V_{IH}$ or $\overline{WE} = V_{IL}$, $V_{IO} = V_{SS}$ to V_{CC}
Operating power supply current: DC	$I_{CC\text{ READ}}$	—	15	25	mA	$\overline{CS} = V_{IL}$, $\overline{WE} = V_{IH}$ others = V_{IH}/V_{IL} , $I_{IO} = 0\text{ mA}$
	$I_{CC\text{ WRITE}}$	—	20	45	mA	$\overline{CS} = V_{IL}$, $\overline{WE} = V_{IL}$ others = V_{IH}/V_{IL} , $I_{IO} = 0\text{ mA}$
Operating power supply current	-5/7A I_{CC1}	—	70	100	mA	Min cycle, duty = 100%
	-7 I_{CC1}	—	60	90	mA	$\overline{CS} = V_{IL}$, others = V_{IH}/V_{IL} $I_{IO} = 0\text{ mA}$
Operating power supply current	I_{CC2}	—	15	30	mA	Cycle time = 1 μs , duty = 100% $I_{IO} = 0\text{ mA}$, $\overline{CS} \leq 0.2\text{ V}$ $V_{IH} \geq V_{CC} - 0.2\text{ V}$, $V_{IL} \leq 0.2\text{ V}$
Standby power supply current: DC	I_{SB}	—	1	3	mA	$\overline{CS} = V_{IH}$
Standby power supply current (1): DC	I_{SB1}	—	0.02	2	mA	$V_{in} \geq 0\text{ V}$, $\overline{CS} \geq V_{CC} - 0.2\text{ V}$
		—	2	100 ²	μA	
		—	2	50 ³	μA	
Output low voltage	V_{OL}	—	—	0.4	V	$I_{OL} = 2.1\text{ mA}$
Output high voltage	V_{OH}	2.4	—	—	V	$I_{OH} = -1.0\text{ mA}$

Notes: 1. Typical values are at $V_{CC} = 5.0\text{ V}$, $T_a = +25^\circ\text{C}$ and specified loading, and not guaranteed.

2. This characteristics is guaranteed only for L version.

3. This characteristics is guaranteed only for L-SL version.

Capacitance ($T_a = 25^\circ\text{C}$, $f = 1\text{ MHz}$)

Parameter	Symbol	Typ	Max	Unit	Test Conditions
Input capacitance ¹	C_{in}	—	8	pF	$V_{in} = 0\text{ V}$
Input/output capacitance ¹	C_{IO}	—	10	pF	$V_{IO} = 0\text{ V}$

Note: 1. This parameter is sampled and not 100% tested.

HITACHI

6

AC Characteristics (Ta = 0 to +70°C, V_{CC} = 5 V ± 10%, unless otherwise noted.)

Test Conditions

- Input pulse levels: 0.8 V to 2.4 V
- Input rise and fall time: 5 ns
- Input and output timing reference levels: 1.5 V
- Output load: 1 TTL Gate + C_L (100 pF) (HM628512-7A/7)
 1 TTL Gate + C_L (50 pF) (HM628512-5)
 (Including scope & jig)


Read Cycle

HM628512									
		-5		-7A		-7			
Parameter	Symbol	Min	Max	Min	Max	Min	Max	Unit	Notes
Read cycle time	t _{RC}	55	—	65	—	70	—	ns	
Address access time	t _{AA}	—	55	—	60	—	70	ns	
Chip select access time	t _{CO}	—	55	—	65	—	70	ns	
Output enable to output valid	t _{OE}	—	25	—	30	—	35	ns	
Chip selection to output in low-Z	t _{LZ}	10	—	10	—	10	—	ns	2
Output enable to output in low-Z	t _{OLZ}	5	—	5	—	5	—	ns	2
Chip deselection to output in high-Z	t _{HZ}	0	20	0	20	0	25	ns	1, 2
Output disable to output in high-Z	t _{OHZ}	0	20	0	20	0	25	ns	1, 2
Output hold from address change	t _{OH}	10	—	10	—	10	—	ns	

- Notes: 1. t_{HZ} and t_{OHZ} are defined as the time at which the outputs achieve the open circuit conditions and are not referred to output voltage levels.
2. This parameter is sampled and not 100% tested.

HM628512 Series

Read Timing Waveform^{*1}




Write Cycle

HM628512									
Parameter	Symbol	-5		-7A		-7		Unit	Notes
Write cycle time	t_{WC}	55	—	55	—	70	—	ns	
Chip selection to end of write	t_{CW}	50	—	50	—	60	—	ns	2
Address setup time	t_{AS}	0	—	0	—	0	—	ns	3
Address valid to end of write	t_{AW}	50	—	50	—	60	—	ns	
Write pulse width	t_{WP}	40	—	40	—	50	—	ns	1, 8
Write recovery time	t_{WR}	5	—	5	—	5	—	ns	4
\overline{WE} to output in high-Z	t_{WHZ}	0	20	0	20	0	25	ns	5, 6, 7
Data to write time overlap	t_{DW}	25	—	25	—	30	—	ns	
Data hold from write time	t_{DH}	0	—	0	—	0	—	ns	
Output active from output in high-Z	t_{OW}	5	—	5	—	5	—	ns	6
Output disable to output in high-Z	t_{OHZ}	0	20	0	20	0	25	ns	5, 6


- Notes: 1. A write occurs during the overlap (t_{WP}) of a low \overline{CS} and a low \overline{WE} . A write begins at the later transition of \overline{CS} going low or \overline{WE} going low. A write ends at the earlier transition of \overline{CS} going high or \overline{WE} going high. t_{WP} is measured from the beginning of write to the end of write.
2. t_{CW} is measured from \overline{CS} going low to the end of write.
3. t_{AS} is measured from the address valid to the beginning of write.
4. t_{WR} is measured from the earlier of \overline{WE} or \overline{CS} going high to the end of write cycle.
5. During this period, I/O pins are in the output state so that the input signals of the opposite phase to the outputs must not be applied.
6. This parameter is sampled and not 100% tested.
7. t_{WHZ} is defined as the time at which the outputs achieve the open circuit conditions and is not referred to output voltage levels.
8. In the write cycle with \overline{OE} low fixed, t_{WP} must satisfy the following equation to avoid a problem of data bus contention. $t_{WP} \geq t_{DW} \text{ min} + t_{WHZ} \text{ max}$

HM628512 Series

Write Timing Waveform (1) ($\overline{\text{OE}}$ Clock)



Write Timing Waveform (2) (\overline{OE} Low Fixed)



HM628512 Series


Low V_{CC} Data Retention Characteristics ($T_a = 0$ to $+70^\circ\text{C}$)

This characteristics is guaranteed only for L/L-SL version.

Parameter	Symbol	Min	Typ	Max	Unit	Test Conditions ³
V_{CC} for data retention	V_{DR}	2	—	—	V	$\overline{CS} \geq V_{CC} - 0.2$ V, $V_{in} \geq 0$ V
Data retention current	I_{CCDR}	—	1 ⁴	50 ¹¹	μA	$V_{CC} = 3.0$ V, $V_{in} \geq 0$ V
		—	1 ⁴	15 ²	μA	$\overline{CS} \geq V_{CC} - 0.2$ V
Chip deselect to data retention time	t_{CDR}	0	—	—	ns	See retention waveform
Operation recovery time	t_R	5	—	—	ms	

- Notes:
1. For L-version and 20 μA (max.) at $T_a = 0$ to 40°C .
 2. For SL-version and 3 μA (max.) at $T_a = 0$ to 40°C .
 3. \overline{CS} controls address buffer, \overline{WE} buffer, \overline{OE} buffer, and D_{in} buffer. In data retention mode, V_{in} levels (address, \overline{WE} , \overline{OE} , I/O) can be in the high impedance state.
 4. Typical values are at $V_{CC} = 3.0$ V, $T_a = 25^\circ\text{C}$ and specified loading, and not guaranteed.

Low V_{CC} Data Retention Timing Waveform (\overline{CS} Controlled)



HITACHI


12

HM628512 Series

Package Dimensions

HM62851P/LP Series (DP-32)

Unit: mm




HITACHI

13

HM628512 Series


HM628512FP/LFP Series (FP-32D)

Unit: mm



HM628512LTT Series (TTP-32D)

Unit: mm




HITACHI

HM628512 Series

HM628512LRR Series (TTP-32DR)

Unit: mm



HITACHI

15