

Silicon NPN Power Transistors

2SC5241

DESCRIPTION


- With TO-220F package
- High voltage,high speed switching

APPLICATIONS

- For switching regulator and general purpose applications

PINNING

PIN	DESCRIPTION
1	Base
2	Collector
3	Emitter



Absolute maximum ratings (Ta=25℃)

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
V _{CBO}	Collector-base voltage	Open emitter	600	V
V _{CEO}	Collector-emitter voltage	Open base	450	V
V _{EBO}	Emitter-base voltage	Open collector	7	V
I _C	Collector current		5	A
I _{CM}	Collector current-peak		10	A
I _B	Base current		2	A
I _{BM}	Base current-peak		4	A
P _T	Total power dissipation	T _C =25℃	30	W
T _j	Junction temperature		150	℃
T _{stg}	Storage temperature		-55~150	℃

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
R _{th j-c}	Thermal resistance junction to case	4.16	℃/W

Silicon NPN Power Transistors

2SC5241

CHARACTERISTICS

T_j=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{CEO(SUS)}	Collector-emitter sustaining voltage	I _C =0.1A ; I _B =0	450			V
V _{CEsat}	Collector-emitter saturation voltage	I _C =2.5A ; I _B =0.5A			1.0	V
V _{BEsat}	Base-emitter saturation voltage	I _C =2.5A ; I _B =0.5A			1.5	V
I _{CBO}	Collector cut-off current	Rated V _{CBO}			0.1	mA
I _{CEO}	Collector cut-off current	Rated V _{CEO}			0.1	mA
I _{EBO}	Emitter cut-off current	Rated V _{EBO}			0.1	mA
h _{FE-1}	DC current gain	I _C =2.5A ; V _{CE} =5V	10			
h _{FE-2}	DC current gain	I _C =1mA ; V _{CE} =5V	5			
f _T	Transition frequency	I _C =0.5A ; V _{CE} =10V		20		MHz

Switching times

t _{on}	Turn-on time	I _C =2.5A; I _{B1} =0.5A I _{B2} =1A V _{BB2} =4V ,R _L =60Ω			0.5	μs
t _s	Storage time				2.0	μs
t _f	Fall time				0.2	μs

Silicon NPN Power Transistors

2SC5241

PACKAGE OUTLINE

