

Medium Power Amplifiers and Switches

TYPE NO.	POLARITY	CASE	MAXIMUM RATINGS			HFE		VCE(sat)		(A)	fT min (MHz)	Cob max (pF)	COMPLEMENTARY TYPE
			Pd (mW)	IC (A)	VCEO (V)	min	max	IC (mA)	VCE (V)				
BC381	P	TO-92F	625	0.2	25	60	-	2.5	5	0.25	0.05	100	10
BC387	N	TO-92F	310	0.6	30	40	300	100	1	0.5	0.1	200	10
BC388	P	TO-92F	310	0.6	30	40	300	100	1	0.5	0.1	200	10
BC425	N	TO-92F	500	0.5	60	20	250	100	10	0.25	0.1	50	4+
BC427	P	TO-92F	500	0.5	60	20	250	100	10	0.25	0.1	50	4.7+
BC431	N	TO-92F	625	0.8	60	63	240 #	100	1	0.7	0.5	100+	12+
BC432	P	TO-92F	625	0.8	60	63	240 #	100	1	0.7	0.5	100+	17+
BC440	N	TO-39	1000	1	40	40	250 #	500	4	1	1	50	25
BC441	N	TO-39	1000	1	60	40	250 #	500	4	1	1	50	25
BC445	N	TO-92F	625	0.3	60	50	460 #	2	5	0.25	0.1	100	3+
BC446	P	TO-92F	625	0.3	60	50	460 #	2	5	0.25	0.1	100	3+
BC460	P	TO-39	1000	1	40	40	250 #	500	4	1	1	50	25
BC461	P	TO-39	1000	1	60	40	250 #	500	4	1	1	50	25
BC485	N	TO-92F	625	1	45	60	400 #	100	2	0.5	0.5	200+	7+
BC486	P	TO-92F	625	1	45	60	400 #	100	2	0.5	0.5	150+	9+
BC487	N	TO-92F	625	1	60	60	400 #	100	2	0.5	0.5	200+	7+
BC488	P	TO-92F	625	1	60	60	400 #	100	2	0.5	0.5	150+	9+
BC489	N	TO-92F	625	1	80	60	400 #	100	2	0.5	0.5	200+	7+
BC490	P	TO-92F	625	1	80	60	400 #	100	2	0.5	0.5	150+	9+
BC512	P	TO-92F	300	0.2	45	60	300 #	2	5	0.6	0.1	200	5+
BC513	P	TO-92F	300	0.2	45	80	400 #	2	5	0.6	0.1	200	5+
BC514	P	TO-92F	300	0.2	20	140	400 #	2	5	0.6	0.1	200	5+
BC526	P	TO-92A	625	0.2	50	60	800 #	2	5	0.6	0.1	100	5
BC527	P	TO-92A	625	1	60	40	400 #	100	1	0.7	0.5	100	15
BC528	P	TO-92A	625	1	80	40	400 #	100	1	0.7	0.5	100	15
BC534	P	TO-92A	625	0.5	80	50	-	10	1	0.25	0.1	50	6.5
BC535	N	TO-92A	625	0.5	80	50	-	10	1	0.25	0.1	50	6
BC537	N	TO-92A	625	1	60	40	400 #	100	1	0.7	0.5	100	15
BC538	N	TO-92A	625	1	80	40	400 #	100	1	0.7	0.5	100	15
BC612	P	TO-92F	300	0.2	70	60	300	2	5	0.72	0.02	200	10
BC612L	P	TO-92B	300	0.2	70	60	300	2	5	0.72	0.02	200	10
BC635	N	TO-92B	700	1	45	40	250	150	2	0.5	0.5	50	11+
BC636	P	TO-92B	700	1	45	40	250	150	2	0.5	0.5	50	18+
BC637	N	TO-92B	700	1	60	40	160	150	2	0.5	0.5	50	11+
BC638	P	TO-92B	700	1	60	40	160	150	2	0.5	0.5	50	18+
BC639	N	TO-92B	700	1	80	40	160	150	2	0.5	0.5	50	11+
BC640	P	TO-92B	700	1	80	40	160	150	2	0.5	0.5	50	18+
BC727	P	TO-92A	625	1.5	40	63	630 #	100	1	0.7	0.5	40	20
BC728	P	TO-92A	625	1.5	25	63	630 #	100	1	0.7	0.5	40	20
BC737	N	TO-92A	625	1.5	40	63	630 #	100	1	0.7	0.5	40	20
BC738	N	TO-92A	625	1.5	25	63	630 #	100	1	0.7	0.5	40	20
BCW34	N	TO-18	360	0.6	45	100	350	10	5	0.1	0.01	150	6
BCW35	P	TO-18	360	0.6	45	100	350	10	5	0.1	0.01	150	6
BCW36	N	TO-92F	360	0.6	45	100	350	10	5	0.1	0.01	150	6
BCW37	P	TO-92F	360	0.6	45	100	350	10	5	0.1	0.01	150	6
BCW73	N	TO-18	450	0.6	32	100	630 #	100	1	0.7	0.5	100	12
BCW74	N	TO-18	450	0.8	45	100	630 #	100	1	0.7	0.5	100	12
BCW75	P	TO-18	450	0.8	32	63	400 #	100	1	0.7	0.5	100	18
BCW76	P	TO-18	450	0.8	45	63	400 #	100	1	0.7	0.5	100	18
BCW77	N	TO-39	870	0.8	32	100	630 #	100	1	0.7	0.5	100	18

HFE grouping available + typical value