



Features

- Capacities up to 8GB
- Small form factor for embedded applications
- IDE interface
- 2 million write/erase cycles
- Sustained throughput up to 10MB/s
- Low power consumption
- Engineered for harsh environments
- Industrial operating temperature ranges
- Automatic bad block management
- Configurable vendor ID/Product ID (VID/PID)
- MTBF: Over 4 million hours
- 5-year warranty
- RoHS Compliant

Mach1 FlashDisk Module

Industrial Grade Solid State Storage

SimpleTech is a global leader in Solid State Flash Storage and Memory (DRAM) Solutions.

At SimpleTech, our world-class memory and storage products allow you to offer superior solutions to your markets. Whether you choose standard or custom solutions, SimpleTech will meet your requirements to exact specification. Your time-to-market requirements are achieved without delay or compromise. From our dock to yours, you can expect an uncompromising commitment to quality and service found nowhere else.

SimpleTech: "Meeting the Evolving Needs of OEM Customers Worldwide $^{\mbox{\scriptsize TM}^{\mbox{\tiny H}}}$

SimpleTech Flash Disk Modules provide non-volatile, solid-state storage in a compact design perfectly suited for embedded applications. Built-in wear leveling algorithms, on-the-fly ECC, and over two million write/erase cycles give you superior data integrity and reliability. Available with industry standard IDE interface; Application software compatibility is ensured as no proprietary software drivers are required.

At the heart of all SimpleTech industrial grade solid state storage products is a proprietary controller that incorporates an advanced dynamic wear leveling algorithm in combination with 5 bit EDC / 4 bit ECC delivering exceptional endurance and reliability.

With no moving parts, SimpleTech flash disk modules are inherently more rugged and reliable than rotating hard drives. New applications for flash disk modules are rapidly emerging due to the low cost per megabyte. Most applications running embedded operating systems such as VxWorks, Windows, XP/embedded, and Linux do not have large data storage requirements, and a cost savings can be immediately realized.

SimpleTech also offers value-added services like customized form factors, testing, custom firmware, software imaging, controlled bill of materials, customer-specific labeling and serialization.

IDE Product Key (M Controller)

Part #: SLFDM(xx)(zzz)-(xxx)(M/G)M1U(I)

xx = Pin

xxx = Capacity

 $\begin{array}{ll} M/G = & Megabyte/Gigabyte \\ I = & Industrial Temperature \\ U = & RoHS Compliant \end{array}$

zzz = IDE Connector Orientation:

V (Vertical), H (Horizontal),

LPV (Low profile vertical), **LPH** (Low profile horizontal)

ex. SLFDM40H-512MM1U(I) =

512MB 40Pin Flash Disk Module (Horizontal)

SLFDM44LPV-8GM1U(I) =

8GB 44Pin Flash Disk Module (Low profile vertical)

Sr	pecif	ICAT	inns
	,0011	I O GI E	UIIU

INTERFACE TRUE IDE (40/44 pin)
CAPACITY 128MB to 8GB

PERFORMANCE

Data Transfer Rate

Sustained Read/Write Up to 10MB/sec
Burst Read/Write Up to 16.7MB/sec

POWER CONSUMPTION

Typical Power Consumption
Sleep Current 2mA

Read Current 60mA - 70mA
Write Current 65mA - 75mA

ENVIRONMENTAL

Operating Temperature

 Commercial
 32°F to 158°F (0°C to 70°C)

 Industrial
 -40°F to 185°F (-40°C to 85°C)

 Storage Temperature
 -40°F to 185°F (-40°C to 85°C)

 Operating Viberation
 15 G, 10-2000 Hz @ 147 meter/sec

 Operating Shock
 1000 G, 4903.3 meter/sec

RELIABILITY

Data Write/Erase Endurance 2 million cycle min.

Data Reliability 1 in 10¹⁴ bits read

Data Retention 10 years

PHYSICAL

Length 2.00 to 2.19 in. (50.80 to 55.63 mm)

Width 0.88 to 1.58 in. (22.35 to 40.13 mm)

Applications

InstrumentationData Recorders

Medical EquipmentAvionics Systems

Machine AutomationTelecommunicationsElectronic KiosksNetworking Equipment

Worldwide Headquarters

SimpleTech, Inc. 3001 Daimler Street Santa Ana, California 92705 USA Tel: (949) 476-1180 Fax: (949) 476-1209 Web: www.simpletech.com

SimpleTech Europe Donau City Strasse 1 1220 Vienna Austria

1220 Vienna, Austria Tel: +43-1-263-38-08 Fax: +43-1-263-37-65 Web: www.simpletech.com

SimpleTech Hong Kong

Unit 01-02, 10/F, 88 Hing Fat Street Causeway Bay, Hong Kong Tel: +852-3150-8398 Fax: +852-3150-8399 Web: www.simpletech.cn

SimpleTech Japan

YOKOHAMA, Landmark Tower 20/F 2-2-1, Minato-Mirai, Nishi-ku Yokohama, 220-8120, Japan Tel: +045-670-7030 Fax: +045-670-7001 Web: www.simpletech.jp

SimpleTech Taiwan

4F, No. 3, Lane 91, Dongmei Road Hsinchu City, Taiwan Tel: +886-3-5733233 Fax: +886-3-5733633 Web: www.simpletech.com