


● Features:

1. Chip material: AlGaAs/GaAs (Red)
and GaP/GaP (Green)
2. Emitted color : Super Red
and Hi-Eff Green
3. Lens Appearance : White Diffused
4. Low power consumption.
5. High efficiency.
6. Versatile mounting on P.C. Board or panel.
7. Low current requirement.
8. 3mm diameter package.
9. This product don't contained restriction
substance, compliance ROHS standard.

● Applications:

1. TV set
2. Monitor
3. Telephone
4. Computer
5. Circuit board

● Package dimensions



● Absolute Maximum Ratings(Ta=25°C)

Parameter	Symbol	Red	Green	Unit
Power Dissipation	Pd	80	80	mW
Forward Current	I _F	30	30	mA
Peak Forward Current* ¹	I _{FP}	150	150	mA
Reverse Voltage	V _R	5		V
Operating Temperature	Topr	-40°C~80°C		
Storage Temperature	Tstg	-40°C~85°C		
Soldering Temperature	Tsol	260°C (for 5 seconds)		

*¹Condition for I_{FP} is pulse of 1/10 duty and 0.1msec width.

● Electrical and optical characteristics(Ta=25°C)

Parameter	Symbol	Condition	Color	Min.	Typ.	Max.	Unit
Forward Voltage	V_F	$I_F=20mA$	Red Green	-	1.8 2.2	2.6 2.6	V
Luminous Intensity	I_v	$I_F=20mA$	Red Green	-	375 125	-	mcd
Reverse Current	I_R	$V_R=5V$	Red Green	-	-	100	μA
Peak Wave Length	λ_p	$I_F=20mA$	Red Green	-	660 568	-	nm
Dominant Wave Length	λ_d	$I_F=20mA$	Red Green	- -	643 573	- -	nm
Spectral Line Half-width	$\Delta \lambda$	$I_F=20mA$	Red Green	- -	20 30	- -	nm
Viewing Angle	$2\theta_{1/2}$	$I_F=20mA$	Red Green	-	20	-	deg

● Typical Electro-Optical Characteristics Curves




Fig.2 FORWARD CURRENT DERATING CURVE




Fig.3 FORWARD CURRENT VS. FORWARD VOLTAGE




Fig.4 RELATIVE LUMINOUS INTENSITY VS. AMBIENT TEMPERATURE




Fig.5 RELATIVE LUMINOUS INTENSITY VS. FORWARD CURRENT




Fig.6 RADIATION DIAGRAM

