### PRELIMINARY DATA

H3500 64 x 4 CMOS Nonvolatile RAM



# SEMICONDUCTOR DIVISION

Industrial Electronics Group

#### DESCRIPTION

Hughes 3500 is a CMOS Nonvolatile RAM organized as 64 x 4. The device consists of a conventional static CMOS RAM paralleled by a background Nonvolatile EEPROM array. This combination is useful for applications where the fast data access time and unlimited reprogramming capabilities of RAMs and the nonvolatile data storage of EEPROMs is required; for example, reconfigurable systems or fault protection (without battery back up).

Four modes of operation are provided: Read, Write, Store and Recall. Both Read and Write options are performed as in standard RAMs. A read is initiated by taking Chip Select  $\overline{(CS)}$  low or by a change of address while  $\overline{CS}$  is low. A Write is initiated with  $\overline{CS}$  low and pulsing the Write Enable  $\overline{(WE)}$  low.

Nonvolatile operations: A Store pulse transfers all of the data in the RAM cells, in parallel, to the background nonvolatile array. The Recall pulse restores this data from the nonvolatile array to the RAM cells.

All operations are performed at 5V supply voltage with TTL level data, address and control inputs.


The 3500 is available in an 18 lead hermetic dual-in-line ceramic package (D suffix), plastic package (P suffix), or leadless chip carrier (L suffix).

## **FEATURES**


- Nonvolatile Data Storage
- 64 x 4 Bit Organization
- Single 5V operation in all modes
- Fast access/Cycle time
   Access time 300ns typical (from CS)
   Cycle time 500ns typical
- Standard pinout 18 pin package

- Nonvolatile store operation 10ms
- Recall operation 1 µs
- Wide temperature range
   -55°C to + 125°C Ceramic Package
   -40°C to + 85°C Plastic Package
- Very Low Current
   Operational 2ma typical
   Standby 100 µa typical

## **FUNCTIONAL BLOCK DIAGRAM**



#### PIN CONFIGURATION



www.DataSheet4U.com