

CP Series Specifications

for higher current, larger heat pumping applications

Catalog Number	I _{max} (Amps)	TH = 25°C			N	Dimensions (mm)			
		Q _{max} ⁽¹⁾ (Watts)	V _{max} (Volts)	ΔT _{max} (°C)		A	B	C	D ⁽²⁾
CP0.8-7-06L	2.1	1.0	0.85	67	7	6	6	3.4	
CP0.8-17-06L	2.1	2.4	2.06	67	17	9	9	3.4	
CP0.8-31-06L	2.1	4.4	3.75	67	31	12	12	3.4	
CP0.8-63-06L	2.1	9.0	7.62	67	63	12	25	3.4	
CP0.8-71-06L	2.1	10.1	8.60	67	71	18	18	3.4	
CP0.8-127-06L	2.1	18.1	15.40	67	127	25	25	3.4	
CP0.8-254-06L	2.1/4.2	36.2	30.8/15.4	67	254	50	25	3.4	
CP0.8-127-05L	2.6	22.4	15.40	67	127	25	25	3.1	
CP0.8-254-05L	2.6/5.2	44.8	30.8/15.4	67	254	50	25	3.1	
CP1.0-7-08L	2.5	1.2	0.85	67	7	8	8	4.0	
CP1.0-17-08L	2.5	2.9	2.06	67	17	12	12	4.0	
CP1.0-31-08L	2.5	5.3	3.75	67	31	15	15	4.0	
CP1.0-63-08L	2.5	10.6	7.62	67	63	15	30	4.0	
CP1.0-71-08L	2.5	12.0	8.60	67	71	23	23	4.0	
CP1.0-127-08L	2.5	21.4	15.40	67	127	30	30	4.0	
CP1.0-254-08L	2.5/5.0	42.8	30.8/15.4	67	254	60	30	4.0	
CP1.0-7-06L	3.0	1.4	0.85	67	7	8	8	3.6	
CP1.0-17-06L	3.0	3.4	2.06	67	17	12	12	3.6	
CP1.0-31-06L	3.0	6.3	3.75	67	31	15	15	3.6	
CP1.0-63-06L	3.0	12.7	7.62	67	63	15	30	3.6	
CP1.0-71-06L	3.0	14.4	8.60	67	71	23	23	3.6	
CP1.0-127-06L	3.0	25.7	15.40	67	127	30	30	3.6	
CP1.0-254-06L	3.0/6.0	51.4	30.8/15.4	67	254	60	30	3.6	
CP1.0-7-05L	3.9	1.8	0.85	67	7	8	8	3.2	
CP1.0-17-05L	3.9	4.5	2.06	67	17	12	12	3.2	
CP1.0-31-05L	3.9	8.2	3.75	67	31	15	15	3.2	
CP1.0-63-05L	3.9	16.6	7.62	67	63	15	30	3.2	
CP1.0-71-05L	3.9	18.7	8.60	67	71	23	23	3.2	
CP1.0-127-05L	3.9	33.4	15.40	67	127	30	30	3.2	
CP1.0-254-05L	3.9/7.8	66.8	30.8/15.4	67	254	60	30	3.2	
CP1.4-11-10L	3.9	2.9	1.33	70	11	10	15	4.7	
CP1.4-17-10L	3.9	4.5	2.06	70	17	15	15	4.7	
CP1.4-31-10L	3.9	8.2	3.75	70	31	20	20	4.7	
CP1.4-35-10L	3.9	9.2	4.24	70	35	15	30	4.7	
CP1.4-71-10L	3.9	18.7	8.60	70	71	30	30	4.7	
CP1.4-127-10L	3.9	33.4	15.40	70	127	40	40	4.7	
CP1.4-11-06L	6.0	4.4	1.33	67	11	10	15	3.8	
CP1.4-17-06L	6.0	6.9	2.06	67	17	15	15	3.8	
CP1.4-31-06L	6.0	12.5	3.75	67	31	20	20	3.8	
CP1.4-35-06L	6.0	14.2	4.24	67	35	15	30	3.8	
CP1.4-71-06L	6.0	28.7	8.60	67	71	30	30	3.8	
CP1.4-127-06L	6.0	51.4	15.40	67	127	40	40	3.8	
CP1.4-11-045L	8.5	6.0	1.33	67	11	10	15	3.3	
CP1.4-17-045L	8.5	9.2	2.06	67	17	15	15	3.3	
CP1.4-31-045L	8.5	16.8	3.75	67	31	20	20	3.3	
CP1.4-35-045L	8.5	19.0	4.24	67	35	15	30	3.3	
CP1.4-71-045L	8.5	38.5	8.60	67	71	30	30	3.3	
CP1.4-127-045L	8.5	72.0	15.40	67	127	40	40	3.3	
CP2-17-10L	9.0	10.3	2.06	70	17	22	22	5.6	
CP2-31-10L	9.0	18.8	3.75	70	31	30	30	5.6	
CP2-49-10L	9.0	29.7	5.93	70	49	36	36	5.6	
CP2-71-10L	9.0	43.1	8.60	70	71	44	44	5.6	
CP2-127-10L	9.0	77.1	15.40	70	127	62	62	5.6	
CP2-17-06L	14.0	16.0	2.06	67	17	22	22	4.6	
CP2-31-06L	14.0	29.3	3.75	67	31	30	30	4.6	
CP2-49-06L	14.0	46.2	5.93	67	49	36	36	4.6	
CP2-71-06L	14.0	67.0	8.60	67	71	44	44	4.6	
CP2-127-06L	14.0	120.0	15.40	67	127	62	62	4.6	
CP2.8-31-06L	24.0	50.2	3.75	67	31	40	40	5.0	
CP5-31-10L	39.0	81.5	3.75	70	31	55	55	5.8	
CP5-31-06L	60.0	125.0	3.75	67	31	55	55	4.9	

■ 5976646 0000355 T09 ■

 1040 Spruce Street
 Trenton, NJ 08648 USA

TEL (609) 393-4178

FAX: (609) 393-9461