



Glass Diode Series Reliability & Qualification Data

This is the reliability and qualification data for the glass axial lead and surface mount Zener, rectifier and Schottky series.

Features

JAN/JANTX/JANTXV available for most
 Voltage range: 1.8 to 200 Volts
 .25 – 1.0 watt power rating
 Low noise, Low leakage and
 Tight tolerance available

Mechanical

Hermetically sealed, double slug glass
 Tin-Lead Plating
 DO-7, DO-35, DO-41, DO-213AA, DO-213AB
 Cathode indicated by band
 Metallurgical bond available

Maximum Ratings

Operating Temperatures: -65° C to 200° C
 Storage Temperature: -65° C to 200° C

Stress	Results
Moisture Classification	Level 1 Package - No Drypack Required Hermetically sealed
ESD Sensitivity	Non-sensitive – No special handling required
Estimated FIT 0.3	90% confidence, 70° C operating, 0.7 eV
Temperature Cycle	0/39936 @ 20 temp. cycles (-55° C to 175° C)
Steady State Life	0/83704 @ 25° C – Tj 150° (1000)
High Temperature Storage	0/675 @ 175° C (1000 Hours)

GLASS1101

John Freeman
 Director of Engineering

Bill Jones
 Director of Quality Control and
 Reliability Assurance

The following series are covered: 1N4370-4372, 1N746-1N759, 1N962-1N992, 1N4099-1N4135, 1N4614-1N4627, 1N4678-1N4717, 1N4728-1N4764, 1N5221-1N5281, 1N5518-

1N5546, 1N5817, 1N5819, 1N5728-1N5757, 1N5913-1N5956, 1N5985-1N6031, 1N4001-1N4006 and all MLL, DL, UR AND -1 versions.