


High Speed Infrared Emitting Diode, 850 nm, GaAIAs Double Hetero

Description

TSMG3700 is a high speed infrared emitting diode in GaAIAs double hetero (DH) technology in a miniature PLCC-2 SMD package.

DH technology combines high speed with high radiant power at wavelength of 850 nm.



94 8553

Features

- High radiant power
- High speed
- High modulation band width
- Peak wavelength $\lambda_p = 850$ nm
- High reliability
- Low forward voltage
- Suitable for high pulse current application
- Wide angle of half intensity
- Compatible with automatic placement equipment
- EIA and ICE standard package
- Suitable for infrared, vapor phase and wavesolder process
- 8 mm tape and reel standard: GS08
- Lead-free component
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC

Applications

Infrared source for CMOS cameras
High speed IR data transmission

Parts Table

Part	Ordering code	Remarks
TSMG3700-GS08	TSMG3700-GS08	MOQ: 7500 pcs
TSMG3700-GS18	TSMG3700-GS18	MOQ: 8000 pcs

Absolute Maximum Ratings

$T_{amb} = 25$ °C, unless otherwise specified

Parameter	Test condition	Symbol	Value	Unit
Reverse Voltage		V_R	5	V
Forward current		I_F	100	mA
Peak Forward Current	$t_p/T = 0.5, t_p = 100$ μ s	I_{FM}	200	mA
Surge Forward Current	$t_p = 100$ μ s	I_{FSM}	1	A
Power Dissipation		P_V	170	mW
Junction Temperature		T_j	100	°C
Operating Temperature Range		T_{amb}	- 40 to + 85	°C

Parameter	Test condition	Symbol	Value	Unit
Storage Temperature Range		T_{stg}	- 40 to + 100	°C
Soldering Temperature	$t \leq 10$ sec	T_{sd}	260	°C
Thermal Resistance Junction/ Ambient		R_{thJA}	450	K/W

Basic Characteristics

$T_{amb} = 25$ °C, unless otherwise specified

Parameter	Test condition	Symbol	Min	Typ.	Max	Unit
Forward Voltage	$I_F = 100$ mA, $t_p = 20$ ms	V_F		1.5	1.8	V
	$I_F = 1$ A, $t_p = 100$ μ s	V_F		2.3		V
Temp. Coefficient of V_F	$I_F = 100$ mA	TK_{V_F}		-2.1		mV/K
Reverse Current	$V_R = 5$ V	I_R			10	μ A
Junction capacitance	$V_R = 0$ V, $f = 1$ MHz, $E = 0$	C_j		125		pF
Radiant Intensity	$I_F = 100$ mA, $t_p = 20$ ms	I_e	6	10	22	mW/sr
	$I_F = 1$ A, $t_p = 100$ μ s	I_e		100		mW/sr
Radiant Power	$I_F = 100$ mA, $t_p = 20$ ms	ϕ_e		40		mW
Temp. Coefficient of ϕ_e	$I_F = 100$ mA	TK_{ϕ_e}		-0.35		%/K
Angle of Half Intensity		φ		± 60		deg
Peak Wavelength	$I_F = 100$ mA	λ_p		850		nm
Spectral Bandwidth	$I_F = 100$ mA	$\Delta\lambda$		40		nm
Temp. Coefficient of λ_p	$I_F = 100$ mA	TK_{λ_p}		0.25		nm/K
Rise Time	$I_F = 100$ mA	t_r		20		ns
Fall Time	$I_F = 100$ mA	t_f		13		ns
Virtual Source Diameter		\varnothing		0.44		mm

Typical Characteristics ($T_{amb} = 25$ °C unless otherwise specified)




Figure 1. Power Dissipation vs. Ambient Temperature






Figure 2. Forward Current vs. Ambient Temperature




95 9985

Figure 3. Pulse Forward Current vs. Pulse Duration




94 8013

Figure 6. Relative Radiant Intensity vs. Angular Displacement



18873




Figure 4. Forward Current vs. Forward Voltage




18874

Figure 5. Radiant Intensity vs. Forward Pulse Current

Package Dimensions in mm



Mounting Pad Layout



Dimensions: IR and Vaporphase
(Wave Soldering)

Drawing-No. : 6.541-5025.01-4
Issue: 7; 05.04.04

95 11314

Missing Devices

A maximum of 0.5 % of the total number of components per reel may be missing, exclusively missing components at the beginning and at the end of the reel. A maximum of three consecutive components may be missing, provided this gap is followed by six consecutive components.

Cover Tape Removal Force

The removal force lies between 0.1 N and 1.0 N at a removal speed of 5 mm/s. In order to prevent components from popping out of the blisters, the cover tape must be pulled off at an angle of 180 ° with regard to the feed direction.




Figure 10. Beginning and End of Reel

The tape leader is at least 160 mm and is followed by a carrier tape leader with at least 40 empty compartments. The tape leader may include the carrier tape as long as the cover tape is not connected to the carrier tape. The least component is followed by a carrier tape trailer with a least 75 empty compartments and sealed with cover tape.




Figure 11. Dimensions of Reel



Ozone Depleting Substances Policy Statement

It is the policy of Vishay Semiconductor GmbH to

1. Meet all present and future national and international statutory requirements.
2. Regularly and continuously improve the performance of our products, processes, distribution and operating systems with respect to their impact on the health and safety of our employees and the public, as well as their impact on the environment.

It is particular concern to control or eliminate releases of those substances into the atmosphere which are known as ozone depleting substances (ODSs).

The Montreal Protocol (1987) and its London Amendments (1990) intend to severely restrict the use of ODSs and forbid their use within the next ten years. Various national and international initiatives are pressing for an earlier ban on these substances.

Vishay Semiconductor GmbH has been able to use its policy of continuous improvements to eliminate the use of ODSs listed in the following documents.

1. Annex A, B and list of transitional substances of the Montreal Protocol and the London Amendments respectively
2. Class I and II ozone depleting substances in the Clean Air Act Amendments of 1990 by the Environmental Protection Agency (EPA) in the USA
3. Council Decision 88/540/EEC and 91/690/EEC Annex A, B and C (transitional substances) respectively.

Vishay Semiconductor GmbH can certify that our semiconductors are not manufactured with ozone depleting substances and do not contain such substances.

We reserve the right to make changes to improve technical design and may do so without further notice.

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use Vishay Semiconductors products for any unintended or unauthorized application, the buyer shall indemnify Vishay Semiconductors against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

Vishay Semiconductor GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany
Telephone: 49 (0)7131 67 2831, Fax number: 49 (0)7131 67 2423