

Linear Systems replaces discontinued LF5301 and PF5301

The 2N5301 is a very High Input Impedance N-Channel JFET amplifier

The 2N5301 N-channel JFET is designed to provide performance amplification at low frequencies and with low noise.

2N5301 Benefits:

- Insignificant Signal Loss/Error Voltage with High-Impedance Source
- Maximum Signal Output, Low Noise
- High Sensitivity to Low-Level Signals

2N5301 Applications:

- High-Impedance Transducer
- Smoke Detector Input
- Infrared Detector Amplifier
- Precision Test Equipment

FEATURES

DIRECT REPLACEMENT FOR LF5301 & PF5301

HIGH INPUT IMPEDANCE $I_G = 0.100 \text{ pA}$

HIGH GAIN $g_{fs} = 70 \text{ } \mu\text{S}$

ABSOLUTE MAXIMUM RATINGS

@ 25°C (unless otherwise noted)

Maximum Temperatures

Storage Temperature -65°C to +175°C

Operating Junction Temperature -65°C to +150°C

Maximum Power Dissipation

Continuous Power Dissipation 300mW

MAXIMUM CURRENT

Gate Current (Note 1) 50mA

MAXIMUM VOLTAGES

Gate to Drain or Gate to Source -30V

2N5301 ELECTRICAL CHARACTERISTICS @ 25°C (unless otherwise noted)

SYMBOL	CHARACTERISTIC	MIN	TYP.	MAX	UNITS	CONDITIONS
BV_{GSS}	Gate to Source Breakdown Voltage	-30	--	--	V	$V_{DS} = 0V, I_D = -1\mu A$
$V_{GS(off)}$	Gate to Source Cutoff Voltage	0.6	--	3.0	V	$V_{DS} = 10V, I_D = 1nA$
I_{GSS}	Gate Leakage Current	--	--	-1	pA	$V_{DG} = 0V, V_{GS} = -15V$
I_G	Gate Operating Current	--	0.04	--		$V_{DG} = 6V, I_D = 5\mu A$
I_{DSS}	Gate to Source Saturation Current	30	--	500	μA	$V_{DS} = 10V, V_{GS} = 0V$
g_{fs}	Forward Transconductance	70	--	300	μS	$V_{DS} = 10V, V_{GS} = 0V, f = 1kHz$
C_{iss}	Input Capacitance	--	--	3	pF	$V_{DS} = 10V, V_{GS} = 0V, f = 1MHz$
C_{rss}	Reverse Transfer Capacitance	--	--	1.5		
e_n	Equivalent Input Noise Voltage	--	45	150	nV/VHz	$V_{DG} = 10V, I_D = 50\mu A, f = 100Hz$

NOTES

1. Absolute maximum ratings are limiting values above which 2N5301 serviceability may be impaired.

Micross Components Europe



Tel: +44 1603 788967

Email: chipcomponents@micross.com

Web: <http://www.micross.com/distribution>

Available Packages:

2N5301 in TO-18

2N5301 in bare die.

Please contact Micross for full package and die dimensions

TO-18 (Bottom View)

