

SPECIFICATION SHEET
JFW MODEL 50P-542
RELAY PROGRAMMABLE ATTENUATOR

JFW Industries, Inc.
 Phone: 317-887-1340
 sales@jfwindustries.com
 www.jfwindustries.com

Frequency Range	DC-2800 MHz
Impedance	50 Ohms nominal
Attenuation Range	0-10 dB in 1 dB steps
Attenuation Steps	1, 2, 3, and 4 dB
VSWR	1.3:1 maximum DC-1000 MHz 1.5:1 maximum 1000-2800 MHz
Attenuation Accuracy	± 0.3 dB maximum DC-1000 MHz ± 0.5 dB maximum 1000-2800 MHz
Insertion Loss	3 dB maximum
RF Input Power	2 Watts average
Switching Speed	6 milliseconds
Control	+12 Vdc @ 30 mA per relay
DC Connector	.040 Diameter solder terminals
RF Connector	SMA, N, TNC, or BNC female
Operating Temperature Range	-20°C to +85°C
Physical Size	See outline drawing 092-745

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
9999	10/04/2002	A	TRS 10/24/2002				
14364	07/06/2007	B	TRS 07/06/2007				