



REVISION			
REV.	DESCRIPTION	DATE	APPROVED



- NOTES:**
- CABLE:** UL20276  
28AWGx1P+DW+FOIL)x7+28AWGx3C+28AWGx1P+MYLAR+FOIL+BD  
COLOR: BEIGE, OD: 8.5 ± 0.3mm  
PRINTING: E166307 AWM 20276 28AWG 80°C 30V VW-1  
LOW VOLTAGE COMPUTER CABLE
  - CONNECTORS:** DVI(24+1)P/M TO DVI(24+1)P/M
  - HOOD:** ASS'Y TYPE, COLOR: BEIGE
  - ELECTRICAL TEST:**
    - <1>.100% OPEN SHORT & MISS WIRE TEST
    - <2>.INSULATION RESISTANCE: DC400V 10M ohm MIN.
    - <3>.CONDUCTOR RESISTANCE: 1 ohm MAX.
  - PACKING:** 1PC/POLYBAG

No.	PARTS NAME	SPECIFICATION STANDARD	QTY	REMARKS
①	DVI (24+1)P/M - CONTACT	BRASS / GOLD PLATED SOLDER TYPE	50	
②	DVI (24+1)P/M - INSULATOR	THERMOPLASTIC / BLACK UL94V-0	2	
③	DVI (24+1)P/M - SHELL	GOLD PLATED	2	
④	CAN	STEEL TIN PLATED, ID: 9.0mm	2	
⑤	DVI (24+1)P/M - COVER	45P PVC/BEIGE	2	
⑥	THUMB SCREW	#4-40 2.8x45mm, GOLD PLATED	4	
⑦	SCREW - MOLD	35P PVC / COLOR: BBEIGE	4	
⑧	CABLE DVI 24+1 UL 20276	KL 3007ABK01A	1	
⑨	MINI TIE	PE/BLACK	2	
⑩	POLYBAG	PE/0.08x220x260	1	

Dim range (mm)	Tolerance +/- (mm)	<b>QQualtek Electronics Corp.</b> WCI DIVISION		
		Part Number: <b>1321038-16</b>		
0-1	0.15	Description: <b>DVI (24+1)P/M - DVI (24+1)P/M</b>		
1-6	0.20			
6-18	0.30			
18-50	0.50			
50-120	0.70	Drawn / Date	Checked / Date	Approved / Date
120-250	0.90	B.Grubb 01-25-07	01-25-07	JJH / 01-25-07
250-500	1.20			