

General Description

The National Semiconductor family of DTL is a complete line of compatible monolithic integrated circuits designed to operate at medium speed with medium power dissipation and high fan-out. The DTL family is available in 14-pin epoxy B or ceramic dual-in-line packages for operation over the 0°C to +75°C temperature range.

The DTL line is composed of a variety of NAND gates that allow complete design flexibility. The gates are available with either 6k pull-up resistors for low power dissipation, or 2k pull-up resistors for increased speed. The gate outputs can be wired together to achieve the wired-OR function.

The NAND gates are complemented with the DM932 and DM957 buffers which provide higher fan-out; the DM944 and DM958 power gates which have an open collector, and the DM933 extender which allows increased fan-in for both buffers and DM930 and DM961 gates.

The flip-flops in this family are of the direct coupled master-slave type, with direct clear and direct set lines. The dual flip-flops include ones with either common or separate clocks.

The DM945 and DM948 are R-S flip-flops which can be externally cross coupled to perform in the JK mode. They are of the master-slave type with output buffers to provide isolation from the output load. These flip-flops feature both asynchronous set and clear lines. The DM945 has a 6k pull-up resistor and the DM948 has a 2k pull-up resistor.

The DM9093 and DM9094 are dual JK flip-flops of the DM945 and DM948 variety respectively. Both flip-flops have separate clocks and no asynchronous clear lines.

The DM9097 and DM9099 are dual JK flip-flops of the DM948 and DM945 variety respectively. Both flip-flops have common clocks and both asynchronous set and clear lines.

The DM930 series is directly compatible with the TTL devices manufactured by National and can be used in conjunction with them in those portions of a system where speed is not the main consideration.

Features

■ NAND Gates

- DM930, DM961 - dual four input gates with expanders
- DM935, DM936, DM937 - hex inverters
- DM946, DM949 - quad two input gates
- DM962, DM963 - triple three input gates
- DM1800, DM1801 - dual five input gates

■ Buffers/Extenders

- DM932 - dual four input buffer with expander
- DM933 - dual four input extender
- DM944 - dual four input power gate with expander
- DM957 - quad two input buffer
- DM958 - quad two input power gate

■ Flip-Flops

- DM945, DM948 - RS flip-flops
- DM9093, DM9094, DM9097, DM9099 - dual JK flip-flops

Truth Tables

SYNCHRONOUS TRUTH TABLE

t _n				t _n + 1
S1 Pin 3	S2 Pin 4	C1 Pin 12	C2 Pin 11	Q Pin 6
L	X	L	X	Q _n
L	X	X	L	Q _n
X	L	L	X	Q _n
X	L	X	L	Q _n
L	X	H	H	L
X	L	H	H	L
H	H	L	X	H
H	H	X	L	H
H	H	H	H	*

* - Indeterminate State
X - Don't Care

ASYNCHRONOUS TRUTH TABLE


S _D Pin 10	C _D Pin 5	Q Pin 6	$\bar{Q}$ Pin 9
H	H	NC	NC
L	H	H	L
H	L	L	H
L	L	H	H

JK TRUTH TABLE


t _n		t _n + 1
S1 Pin 3	C1 Pin 12	Q Pin 6
L	L	Q _n
L	L	H
H	H	L
H	H	Q _n

(Connect S2 to $\bar{Q}$, C2 to Q) Asynchronous inputs, direct set (S_D) and direct clear (C_D), override the synchronous inputs, and are independent of all other inputs.


Connection and Logic Diagrams




930(J), (N); 932(J), (N);
944(J), (N); 961(J), (N);
1800(J), (N); 1801(J), (N)




935(J), (N); 936(J), (N);
937(J), (N)




946(J), (N); 949(J), (N)




962(J), (N); 963(J), (N)




957(J), (N); 958(J), (N)




933(J), (N)



945(J), (N); 948(J), (N)



9093(J), (N); 9094(J), (N)



9097(J), (N); 9099(J), (N)

Electrical Characteristics ($V_{CC} = 5.0V$)

PARAMETER		CONDITIONS		DM930, DM935, DM936, DM937, DM946 DM949, DM961, DM962, DM963, DM1800, DM1801						UNITS
				0°C		25°C		75°C		
				MIN	MAX	MIN	MAX	MIN	MAX	
I _{CEX}	Output Leakage Current	V _I = 0, V _O = 5V	2k Gates			100			μA	
			6k Gates			100				
V _{OH}	High Level Output Voltage(1)	V _{IL} = Max, I _{OH} = Max		2.6		2.6		2.5	V	
V _{OL}	Low Level Output Voltage	V _I = V _{IH} , I _{OL} = Max			0.45		0.45	0.50	V	
I _{IH}	High Level Input Current (1)	V _I = V _R			5		5	10	μA	
I _{IL}	Low Level Input Current	V _I = V _F			-1.40		-1.40	-1.33	mA	
I _{OS}	Short Circuit Output Current	V _i = 0	2k Gates			-1.85	-3.90		mA	
			6k Gates		1.30	-0.61	-1.30	-1.25		
I _{CC1}	Supply Current	V _{CC} = 5V, V _I = V _R	2k Gates			5.9			mA	
			6k Gates			4				
I _{CC2}	Supply Current	V _{CC} = 8V, V _i = 0				4			mA	
t _{PLH}	Propagation Delay Time, Low-to-High Level Output	C _L = 30 pF, R _L = 3.9 kΩ	2k Gates			15	60		ns	
			6k Gates			25	80			
t _{PHL}	Propagation Delay Time, High-to-Low Level Output	C _L = 50 pF, R _L = 400Ω	2k Gates			10	30		ns	
			6k Gates			10	30			

Notes

(1) Applies to all gates except DM935.

Test Conditions
GATES

TEMP.	V_{IH} VOLTS	V_{IL} VOLTS	V_R VOLTS	V_F VOLTS	V_{CEX} VOLTS	(6k) I_{OL} (mA)	(2k) I_{OL} (mA)	(6k) I_{OH} (mA)	(2k) I_{OH} (mA)
0°C	2.0	1.2	4.0	0.45	—	12.0	11.0	-0.12	-0.5
+25°C	1.9	1.1	4.0	0.45	5.0	12.0	11.0	-0.12	-0.5
+75°C	1.8	0.95	4.0	0.50	—	11.4	10.4	-0.12	-0.5

Electrical Characteristics ($V_{CC} = 5.0V$)

PARAMETER		CONDITIONS		DM932, DM933, DM944, DM957, DM958						UNITS
				0°C		25°C		75°C		
				MIN	MAX	MIN	MAX	MIN	MAX	
V _{IL}	Low Level Input Voltage	I _{IL} = I _{FD}	933	0.75	0.90	0.68	0.82	0.60	0.75	V
I _{CEX}	Output Leakage Current	V _I = 0, V _O = 5V	932, 957			100				μA
			944, 958		25	100		200		
V _{OH}	High Level Output Voltage	V _I = V _{IL} , I _{OH} = Max	932, 957	2.6		2.6		2.5		V
V _{OL}	Low Level Output Voltage	V _I = V _{IH} , I _{OL} = Max	All Except 933		0.45		0.45		0.50	V
I _{IH}	High Level Input Current	V _I = V _R	933		5		5		10	μA
			Others		5		5	10		
I _{IL}	Low Level Input Current	V _I = V _F	All Except 933		-1.40		-1.40		-1.33	mA
I _{OS}	Short Circuit Output Current	V _I = 0	932, 957		-16		-16		-14	mA
I _{CC1}	Supply Current	V _{CC} = 5V, V _I = V _R	932				30.0			mA
			944				22.5			
			957				60.0			
			958				4.5			
I _{CC2}	Supply Current	V _{CC} = 8V, V _I = 0	All Except 933				4			mA
t _{PLH}	Propagation Delay Time, Low-to-High Level Output	C _L = 500 pF, R _L = 510Ω	932, 957			25	80			ns
		C _L = 20 pF, R _L = 510Ω	944, 958			15	50			
t _{PHL}	Propagation Delay Time, High-to-Low Level Output	C _L = 500 pF, R _L = 150Ω	932, 957			15	40			ns
		C _L = 100 pF, R _L = 150Ω	944, 958			10	35			

Test Conditions

BUFFERS/EXTENDERS

TEMP.	V_{IH} VOLTS	V_{IL} VOLTS	V_R VOLTS	V_F VOLTS	V_{CEX} VOLTS	I_{FD} mA	932 957	944 958	932 957
							I_{OL} (mA)	I_{OL} (mA)	I_{OH} (mA)
0°C	2.0	1.2	4.0	0.45	—	-2	36	40	-2.0
+25°C	1.9	1.1	4.0	0.45	5.0	-2	36	40	-2.5
+75°C	1.8	0.95	4.0	0.50	—	-2	34	36	-3.0

Electrical Characteristics ($V_{CC} = 5.0V$)

PARAMETER		CONDITIONS		DM945, DM948, DM9093, DM9094 DM9097, DM9099						UNITS	
				0 °C		25 °C		75 °C			
				MIN	MAX	MIN	MAX	MIN	MAX		
I _{CEX}	Output Leakage Current	V _I = 0, V _O = 5V	945, 948			100				μA	
V _{OH}	High Level Output Voltage	V _I = V _{IL} I _{OH} = Max	Data	945, 948	2.6		2.6		2.5		V
			Set, Reset	945, 948	2.6		2.6				
			All	9093, 9094 9097, 9099	2.6		2.6		2.5		
V _{OL}	Low Level Output Voltage	V _I = V _{IH} , I _{OL} = Max	All	0.45		0.45		0.50		V	
I _{IH}	High Level Input Current	V _I = V _H	Data	945, 948	5.0		5.0		10.0		μA
			Set, Reset	945, 948	5.0		5.0		10.0		
			Clock	945, 948	30		30		40		
				9093, 9094	20		20		30		
				9097, 9099	40		40		60		
			Clear	9097, 9099	10		10		20		
			All Except Clocks, and Direct Clear on 9097, 9099	9093, 9094 9097, 9099	5.0		5.0		10.0		
I _{IL}	Low Level Input Current	V _I = V _F	Data	All	-0.95		-0.95		-0.90		mA
			Set, Reset	945, 948	-2.8		-2.8		-2.67		
			Direct Set	9093, 9094 9097, 9099	-2.8		2.8		2.67		
			Clock	945	-2.8		-2.8		-2.66		
				948, 9093 9094	-2.8		2.8		2.67		
			Clock, Direct Clear	9097, 9099	-5.6		5.6		5.34		
I _{OS}	Short Circuit Output Current	V _I = 0	2k	1.77	4.2	1.77	4.2	-1.60	-4.0	mA	
			6k	0.59	1.41	-0.59	-1.41	-0.55	-1.38		
I _{CC1}	Supply Current	V _{CC} = 5V (Inputs Open)	945			14				mA	
			948			17					
			9093, 9099			28					
			9094, 9097			34					
I _{CC2}	Supply Current	V _{CC} = 8V, V _I = 0	945			18				mA	
			948			23					
			9093, 9099			36					
			9094, 9097			45					
t _{PLH}	Propagation Delay Time, Low-to-High Level Output	C _L = 30 pF, R _L = 2 kΩ	2k			25	75			ns	
			6k			25	100				
t _{PHL}	Propagation Delay Time, High-to-Low Level Output	C _L = 50 pF, R _L = 330Ω					15	55	ns		

Test Conditions

FLIP-FLOPS

TEMP.	V_{IH} VOLTS	V_{IL} VOLTS	V_R VOLTS	V_F VOLTS	V_{CEX} VOLTS	945 9093 9099 (6k)	948 9094 9097 (2k)	945 9093 9099 (6k)	948 9094 9097 (2k)	945 9093 9099 (6k)	948 9094 9097 (2k)
						V_{CPTH} (VOLTS)	V_{CPTH} (VOLTS)	I_{OL} (mA)	I_{OL} (mA)	I_{OH} (mA)	I_{OH} (mA)
0°C	2.0	1.2	4.0	0.45	—	1.15	1.30	16.8	15.4	-0.12	-0.5
+25°C	1.9	1.1	4.0	0.45	5.0	0.95	1.15	16.8	15.4	-0.12	-0.5
+75°C	1.8	0.95	4.0	0.50	—	0.65	0.85	16.0	14.6	-0.12	-0.5

