

## Dual 1 Form A Solid State Relay

### Features

- Dual Channel (LH1546)
- Current Limit Protection
- Isolation Test Voltage 5300 V<sub>RMS</sub>
- Typical R<sub>ON</sub> 28 Ω
- Load Voltage 350 V
- Load Current 120 mA
- High Surge Capability
- Clean Bounce Free Switching
- Low Power Consumption
- SMD Lead Available on Tape and Reel
- Lead-free component
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC

### Agency Approvals



- UL1577, File No. E52744 System Code H or J, Double Protection
- CSA - Certification 093751
- BSI/BABT Cert. No. 7980
- DIN EN 60747-5-2 (VDE0884)  
DIN EN 60747-5-5 pending
- FIMKO Approval

### Applications

#### General Telecom Switching

- On/off Hook Control
- Ring Relay
- Dial Pulse
- Ground Start
- Ground Fault Protection

#### Instrumentation



Pb-free

Industrial Controls

### Description

The LH1556 dual 1 Form A relays are SPST normally open switches that can replace electromechanical relays in many applications. They are constructed using a GaAlAs LED for actuation control and an integrated monolithic die for the switch output. The die, fabricated in a high-voltage dielectrically isolated technology is comprised of a photodiode array, switch control circuitry, and MOSFET switches. In addition, the LH1556 SSRs employ current-limiting circuitry, enabling them to pass FCC 68.302 and other regulatory surge requirements when overvoltage protection is provided.

### Order Information

Part	Remarks
LH1556AB	Tubes, DIP-8
LH1556AAC	Tubes, SMD-8
LH1556AACTR	Tape and Reel, SMD-8

### Absolute Maximum Ratings, $T_{amb} = 25^\circ C$

Stresses in excess of the absolute Maximum Ratings can cause permanent damage to the device. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of this document. Exposure to absolute Maximum Ratings for extended periods of time can adversely affect reliability.

### SSR

Parameter	Test condition	Symbol	Value	Unit
LED continuous forward current		$I_F$	50	mA
LED reverse voltage	$ I_R  \leq 10 \mu A$	$V_R$	8.0	V
DC or peak AC load voltage	$ I_L  \leq 50 \mu A$	$V_L$	350	V
Continuous DC load current - one pole operating		$I_L$	120	mA
Continuous DC load current - two pole operating		$I_L$	250	mA
Peak load current (single shot)	$t = 100 \text{ ms}$	$I_P$	1)	mA
Ambient temperature range		$T_{amb}$	- 40 to + 85	$^\circ C$
Storage temperature range		$T_{stg}$	- 40 to + 150	$^\circ C$
Pin soldering temperature	$t = 10 \text{ s max}$	$T_s$	260	$^\circ C$
Input/output isolation voltage		$V_{ISO}$	5300	$V_{RMS}$
Output power dissipation (continuous)		$P_{diss}$	550	mW

1) Refer to Current Limit Performance Application Note for a discussion on relay operation during transient currents.

### Electrical Characteristics, $T_{amb} = 25^\circ C$

Minimum and maximum values are testing requirements. Typical values are characteristics of the device and are the result of engineering evaluations. Typical values are for information only and are not part of the testing requirements.

### Input

Parameter	Test condition	Symbol	Min	Typ.	Max	Unit
LED forward current, switch turn-on	$I_L = 100 \text{ mA}, t = 10 \text{ ms}$	$I_{Fon}$		1.1	2.0	mA
LED forward current, switch turn-off	$V_L = \pm 350 \text{ V}$	$I_{Foff}$	0.2	1.0		mA
LED forward voltage	$I_F = 10 \text{ mA}$	$V_F$	1.15	1.26	1.45	V

### Output

Parameter	Test condition	Symbol	Min	Typ.	Max	Unit
ON-resistance ac/dc: Pin 4 ( $\pm$ ) to 6 ( $\pm$ )	$I_F = 5.0 \text{ mA}, I_L = 50 \text{ mA}$	$R_{ON}$		28	35	$\Omega$
ON-resistance dc: Pin 4, 6 (+) to 5 (-)	$I_F = 5.0 \text{ mA}, I_L = 100 \text{ mA}$	$R_{ON}$		7.0	10.0	$\Omega$
Off-resistance	$I_F = 0 \text{ mA}, V_L = \pm 100 \text{ V}$	$R_{OFF}$	0.5	300		$G\Omega$
Current limit ac/dc	$I_F = 5.0 \text{ mA}, V_L = \pm 6.0 \text{ V}, t = 5.0 \text{ ms}$	$I_{LMT}$	170	210	250	mA
Off-state leakage current	$I_F = 0 \text{ mA}, V_L = \pm 100 \text{ V}$	$I_O$		0.35	200	nA
	$I_F = 0 \text{ mA}, V_L = \pm 350 \text{ V}$	$I_O$		0.096	1.0	$\mu A$
Output capacitance Pin 4 to 6	$I_F = 0 \text{ mA}, V_L = 1.0 \text{ V}$	$C_O$		18		pF
	$I_F = 0 \text{ mA}, V_L = 50 \text{ V}$	$C_O$		6.7		pF
Switch offset	$I_F = 5.0 \text{ mA}$	$V_{OS}$		0.3		$\mu V$

## Transfer

Parameter	Test condition	Symbol	Min	Typ.	Max	Unit
Capacitance (input-output)	$V_{ISO} = 1.0$ V	$C_{IO}$		0.67		pF
Turn-on time	$I_F = 5.0$ mA, $I_L = 50$ mA	$t_{on}$		1.14	3.0	ms
Turn-off time	$I_F = 5.0$ mA, $I_L = 50$ mA	$t_{off}$		0.71	3.0	ms

## Typical Characteristics (Tamb = 25 °C unless otherwise specified)




Figure 1. Recommended Operating Conditions




Figure 3. LED Forward Current vs. LED Forward Voltage




Figure 2. LED Voltage vs. Temperature




Figure 4. LED Reverse Current vs. LED Reverse Voltage

# LH1556AB/ AAC/ AACTR

Vishay Semiconductors




Figure 5. LED Current for Switch Turn-on vs. Temperature




Figure 8. Current Limit vs. Temperature




Figure 6. LED Dropout Voltage vs. Temperature




Figure 9. Switch Breakdown Voltage vs. Load Current




Figure 7. Load Current vs. Load Voltage




Figure 10. Switch Offset Voltage vs. LED Current




Figure 11. ON-Resistance vs. Temperature




Figure 14. Insertion Loss vs. Frequency




Figure 12. Variation in ON-Resistance vs. LED Current




Figure 15. Output Isolation




Figure 13. Switch Capacitance vs. Applied Voltage




Figure 16. Leakage Current vs. Applied Voltage at Elevated Temperatures




Figure 17. Switch Breakdown Voltage vs. Temperature




Figure 20. Turn-off Time vs. Temperature




Figure 18. Switch Offset Voltage vs. Temperature




Figure 21. Turn-on Time vs. LED Current




Figure 19. Turn-on Time vs. Temperature






Figure 22. Turn-off Time vs. LED Current

### Package Dimensions in Inches (mm)

**DIP**


i178008

### Package Dimensions in Inches (mm)

**SMD**


i178009

### Ozone Depleting Substances Policy Statement

It is the policy of Vishay Semiconductor GmbH to

1. Meet all present and future national and international statutory requirements.
2. Regularly and continuously improve the performance of our products, processes, distribution and operating systems with respect to their impact on the health and safety of our employees and the public, as well as their impact on the environment.

It is particular concern to control or eliminate releases of those substances into the atmosphere which are known as ozone depleting substances (ODSs).

The Montreal Protocol (1987) and its London Amendments (1990) intend to severely restrict the use of ODSs and forbid their use within the next ten years. Various national and international initiatives are pressing for an earlier ban on these substances.

Vishay Semiconductor GmbH has been able to use its policy of continuous improvements to eliminate the use of ODSs listed in the following documents.

1. Annex A, B and list of transitional substances of the Montreal Protocol and the London Amendments respectively
2. Class I and II ozone depleting substances in the Clean Air Act Amendments of 1990 by the Environmental Protection Agency (EPA) in the USA
3. Council Decision 88/540/EEC and 91/690/EEC Annex A, B and C (transitional substances) respectively.

Vishay Semiconductor GmbH can certify that our semiconductors are not manufactured with ozone depleting substances and do not contain such substances.

We reserve the right to make changes to improve technical design  
and may do so without further notice.

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use Vishay Semiconductors products for any unintended or unauthorized application, the buyer shall indemnify Vishay Semiconductors against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

Vishay Semiconductor GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany  
Telephone: 49 (0)7131 67 2831, Fax number: 49 (0)7131 67 2423