

**OEM Pressure Sensor
Media Compatible
Temperature Compensated
Serialized**

Features


- Solid State Reliability
- $\pm 1\text{mV}$ Zero Output
- Infinite Resolution
- 100 mV Output Span
- Ratiometric
- $\pm 0.1\%$ Accuracy
- Low Noise
- Humidity Resistant
- Low Power
- Performance Graded

Typical Applications

- Medical
- Liquid Level
- Process Control
- Water Management
- Oceanography
- Environmental Control
- Refrigeration
- Agricultural Sprayers
- Pollution Control
- Automotive

Standard Ranges

- 0 to 5 psig
- 0 to 10 psig
- 0 to 15 psig
- 0 to 30 psig
- 0 to 50 psig
- 0 to 100 psig
- 0 to 250 psig




Description

The Model 22 is a media compatible, solid state, piezoresistive pressure sensor that is packaged in a TO-8 configuration and is intended for use with corrosive or conductive fluid or gaseous media where excellent long-term stability is required. Each sensor is individually serialized.

Integral temperature compensation is provided along with zero balancing over 0-50°C with laser trimmed resistors. No external resistors are required.

Three performance grades are available in gage pressure from 0-5 psi to 0-250 psi for the Model 22 and 0-5 psi to 0-15 psi for the Model 22N.

Connections/Dimensions



Model 22

I C SENSORS INC 83 DE 4677375 0000066 5

T-65-13

Performance Specifications


Supply Current = 1.5 mA & Ambient Temperature = 25°C (Unless otherwise specified)

PARAMETER	GRADE									UNITS	NOTES
	A			B			C				
	MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX		
Full-Scale Output Span	75	100	150	75	100	150	50			mV	
Zero Pressure Output			1			2			5	±mV	2
Linearity		0.05	0.10			0.25			0.50	±% Span	3
Pressure Hysteresis		0.01	0.05			0.10			0.15	±% Span	
Input & Output Resistance	2500	4400	8000		4400	8000		4400		Ω	
Temperature Coefficient-Span		0.3	0.5			1.0			2.0	±% Span	1, 2
Temperature Coefficient-Zero		0.1	0.5			1.0			2.0	±% Span	1, 2
Temperature Coefficient-Resistance		.22			.22			.22		%/°C	1
Thermal Hysteresis-Span		0.1			0.2			0.3		±% Span	1
Thermal Hysteresis-Zero		0.1			0.2			0.3		±% Span	1
Supply Current		1.5	2.0		1.5	2.0		1.5	2.0	mA	4
Response Time (10% to 90%)		1.0			1.0			1.0		mS	5
Output Noise		1.0			2.0			5.0		μV p-p	6
Output Load Resistance	2			2			2			MΩ	7
Insulation Resistance (50VDC)	50			50			50			MΩ	
Long Term Stability		0.2			0.5			1.0		±% Span/year	
Pressure Overload			3X			3X			3X	Rated	8
Operating Temperature	-40°C to +125°C										
Storage Temperature	-55°C to +150°C										
Acceleration	50g Max										
Shock	1000g Peak for 0.5 mS										
Vibration	20g Peak at 10 to 2000 Hz										
Media	Corrosive and Conductive Liquids and Gases compatible with wetted materials										
Weight	3 grams										

Notes

- Temperature range: 0-50°C in reference to 25°C.
- Compensation resistors are an integral part of the sensor package; no additional external resistors are required. Pins 11 and 12 must be kept open. For interchangeable part see Model 23 Data Sheet and Application Note TN-003.
- Best fit straight line.
- Guarantees output/input ratiometricity.
- For a zero-to-full scale pressure step change.
- 10Hz to 1kHz.
- Prevents increase of TC-Span due to output loading.
- 3X or 500 psi maximum, whichever is less.
- Wetted materials are gold, RTV (22N only), silicon and glass. The Model 22N is available in 5, 10 and 15 psi ranges only.
- Soldering of lead pins and bottom tube: 250°C for 5 seconds maximum. Heat-sink tube while soldering.

Ordering Information



Represented By

I.C. Sensors products are warranted against defects in material and workmanship for 12 months from date of shipment. Products not subjected to misuse will be repaired or replaced. THE FOREGOING IS IN LIEU OF ALL OTHER EXPRESSED OR IMPLIED WARRANTIES. I.C. Sensors reserves the right to make changes to any product herein and assumes no liability arising out of the application or use of any product or circuit described or referenced herein.



1701 McCarthy Blvd.

Milpitas, California 95035

(408) 946-6693

Telex 350066

MO022R2-8607—Printed in USA